



US006489963B2

(12) **United States Patent**  
**Parikh et al.**

(10) **Patent No.:** **US 6,489,963 B2**  
(45) **Date of Patent:** **Dec. 3, 2002**

(54) **APPLICATION PROGRAM INTERFACE FOR A GRAPHICS SYSTEM**

(75) Inventors: **Vimal Parikh**, Santa Clara, CA (US);  
**Robert Moore**, Heathrow, FL (US);  
**Howard Cheng**, Sammamish, WA (US)

(73) Assignee: **Nintendo Co., Ltd.**, Kyoto (JP)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/885,949**

(22) Filed: **Jun. 22, 2001**

(65) **Prior Publication Data**

US 2001/0040578 A1 Nov. 15, 2001

**Related U.S. Application Data**

(63) Continuation of application No. 09/723,336, filed on Nov. 28, 2000.

(51) **Int. Cl.**<sup>7</sup> ..... **G06T 15/00**; G06F 15/16

(52) **U.S. Cl.** ..... **345/522**; 345/581; 709/328;  
712/208

(58) **Field of Search** ..... 345/501, 503,  
345/419, 581, 520, 522, 559; 709/328;  
712/208

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,388,620 A 6/1983 Sherman  
4,425,559 A 1/1984 Sherman

(List continued on next page.)

**FOREIGN PATENT DOCUMENTS**

CA 2070934 12/1993  
EP 1 074 945 2/2001  
EP 1 075 146 2/2001  
EP 1 081 649 3/2001  
JP 9-330230 12/1997

JP	11053580	2/1999
JP	11076614	3/1999
JP	11161819	6/1999
JP	11203500	7/1999
JP	11226257	8/1999
JP	11259671	9/1999
JP	11259678	9/1999
JP	2000-66985	3/2000
JP	2000-92390	3/2000
JP	2000-132704	5/2000
JP	2000-132706	5/2000
JP	2000-149053	5/2000
JP	2000-156875	6/2000
JP	2000-182077	6/2000
JP	2000-207582	7/2000
JP	2000-215325	8/2000
WO	WO 94/10641	5/1994

**OTHER PUBLICATIONS**

Photograph of Sony PlayStation II System.

Photograph of Sega Dreamcast System.

Photograph of Nintendo 64 System.

Whitepaper: 3D Graphics Demystified, Nov. 11, 1999, www.nvidia.com.

Whitepaper: "Z Buffering, Interpolation and More W-Buffering", Doug Rogers, Jan. 31, 2000, www.nvidia.com.

Whitepaper: Using GL\_NV\_vertex\_array and GL\_NV\_fence, posted Aug. 1, 2000, www.nvidia.com.

(List continued on next page.)


*Primary Examiner*—Ulka Chauhan

(74) *Attorney, Agent, or Firm*—Nixon & Vanderhye P.C.


(57) **ABSTRACT**

An interface for a graphics system includes simple yet powerful constructs that are easy for an application programmer to use and learn. Features include a unique vertex representation allowing the graphics pipeline to retain vertex state information and to mix indexed and direct vertex values and attributes; a projection matrix value set command; a display list call object command; and an embedded frame buffer clear/set command.

**4 Claims, 21 Drawing Sheets**



EXAMPLE MORE DETAILED GRAPHIC PROCESSING LOOP



## U.S. PATENT DOCUMENTS

4,570,233	A	2/1986	Yan et al.	
4,658,247	A	4/1987	Charachorloo	
4,725,831	A	2/1988	Coleman	
4,826,295	A	5/1989	Hiroyuki	
4,862,392	A	8/1989	Steiner	
4,866,637	A	9/1989	Gonzalez-Lopez et al.	
4,901,064	A	2/1990	Deering	
4,914,729	A	4/1990	Omori et al.	
4,945,500	A	7/1990	Deering	
5,136,664	A	8/1992	Bersack et al.	
5,170,468	A	12/1992	Shah et al.	
5,392,385	A	2/1995	Evangelisti et al.	
5,392,393	A	2/1995	Deering	
5,404,445	A	4/1995	Matsumoto	
5,421,028	A	5/1995	Swanson	
5,432,900	A	7/1995	Rhodes et al.	
5,438,663	A	8/1995	Matsumoto et al.	
5,457,775	A	10/1995	Johnson, Jr. et al.	
5,504,917	A	4/1996	Austin	
5,594,854	A	1/1997	Baldwin et al.	
5,608,424	A	3/1997	Takahashi et al.	
5,671,401	A	* 9/1997	Harrell .....	345/441
5,687,357	A	11/1997	Priem	
5,701,444	A	12/1997	Baldwin	
5,721,947	A	2/1998	Priem et al.	
5,727,192	A	3/1998	Baldwin	
5,751,295	A	5/1998	Becklund et al.	
5,758,182	A	5/1998	Rosenthal et al.	
5,764,243	A	6/1998	Baldwin	
5,768,626	A	6/1998	Munson et al.	
5,768,629	A	6/1998	Wise et al.	
5,774,133	A	6/1998	Neave et al.	
5,777,629	A	7/1998	Baldwin	
5,798,770	A	8/1998	Baldwin	
5,801,706	A	9/1998	Fujita et al.	
5,801,716	A	9/1998	Silverbrook	
5,805,868	A	9/1998	Murphy	
5,815,166	A	9/1998	Baldwin	
5,821,949	A	10/1998	Deering	
5,870,587	A	2/1999	Danforth et al.	
5,874,969	A	2/1999	Storm et al.	
5,917,496	A	6/1999	Fujita et al.	
5,920,326	A	7/1999	Rentschler et al.	
5,920,876	A	7/1999	Ungar et al.	
5,936,641	A	8/1999	Jain et al.	
5,940,086	A	8/1999	Rentschler et al.	
5,949,424	A	9/1999	Cabral et al.	
5,949,440	A	9/1999	Krech, Jr. et al.	
5,966,133	A	* 10/1999	Hoppe .....	345/420
5,969,726	A	10/1999	Rentschler et al.	
5,995,121	A	11/1999	Alcorn et al.	
5,999,196	A	12/1999	Storm et al.	
6,002,409	A	12/1999	Harkin	
6,023,738	A	2/2000	Priem et al.	
6,025,853	A	2/2000	Baldwin	
6,028,611	A	2/2000	Anderson et al.	
6,031,548	A	* 2/2000	Guezic et al. ....	345/440
6,037,949	A	3/2000	DeRose et al.	
6,052,133	A	4/2000	Kang	
6,057,852	A	5/2000	Krech, Jr.	
6,057,863	A	5/2000	Olarig	
6,075,540	A	* 6/2000	Hoppe .....	345/419
6,078,331	A	* 6/2000	Pulli et al. ....	345/423
6,092,124	A	7/2000	Priem et al.	
6,151,602	A	11/2000	Hejlsberg et al.	
6,173,367	B1	1/2001	Aleksic et al.	
6,177,944	B1	1/2001	Fowler et al.	
6,181,352	B1	1/2001	Kirk et al.	
6,198,488	B1	* 3/2001	Lindholm et al. ....	345/418
6,222,550	B1	* 4/2001	Rosman et al. ....	345/419
6,222,555	B1	* 4/2001	Christofferson et al. ....	345/428
6,226,012	B1	5/2001	Priem et al.	
6,256,041	B1	* 7/2001	Deering .....	345/419
6,307,551	B1	* 10/2001	Guezic et al. ....	345/419

## OTHER PUBLICATIONS

Whitepaper: Anisotropic Texture Filtering in OpenGL, posted Jul. 17, 2000, [www.nvidia.com](http://www.nvidia.com).

Whitepaper: Mapping Texels to Pixels in D3D, posted Apr. 5, 2000, [www.nvidia.com](http://www.nvidia.com).

Whitepaper: Guard Band Clipping, posted Jan. 31, 2000, [www.nvidia.com](http://www.nvidia.com).

Whitepaper: Cube Environment Mapping, posted Jan. 14, 2000, [www.nvidia.com](http://www.nvidia.com).

Whitepaper: Color Key in D3D, posted Jan. 11, 2000, [www.nvidia.com](http://www.nvidia.com).

Whitepaper: Vertex Blending Under DX7 for the GeForce 256, Jan. 5, 2000, [www.nvidia.com](http://www.nvidia.com).

Whitepaper: Optimizing Direct3D for the GeForce 256, Jan. 3, 2000, [www.nvidia.com](http://www.nvidia.com).

Whitepaper: Dot Product Texture Blending, Dec. 3, 1999, [www.nvidia.com](http://www.nvidia.com).

Whitepaper: Technical Brief: AGP 4X with Fast Writes, Nov. 10, 1999, [www.nvidia.com](http://www.nvidia.com).

Technical Brief: Transform and Lighting, Nov. 10, 1999, [www.nvidia.com](http://www.nvidia.com).

Technical Brief: What's New With Microsoft Direct X7, posted Nov. 10, 1999, [www.nvidia.com](http://www.nvidia.com).

Mitchell et al., "Multitexturing in DirectX6", Game Developer, Sep. 1998, [www.gdmag.com](http://www.gdmag.com).

VisionTek, "GeForce2 GS Graphics Processing Unit", ©2000 [www.visiontek.com](http://www.visiontek.com).

Jim Bushnell et al. "Advanced Multitexture Effects With Direct3D and OpenGL", Pyramid Peak Design & ATI Research, Inc., GameDevelopers Conference, ©1999.

Sony PlayStation II Instruction Manual, Sony Computer Entertainment Inc., ©2000.

Stand and Be Judged, Next Generation, May 2000.

PlayStation II: Hardware Heaven or Hell?, Next Generation, Jan. 2000.

Chris Charla, "Play Station II: The Latest News", Next Generation, Sep. 1999.

"First PlayStation II Gameplay Screens Revealed!", Next Generation, Sep. 1999.

Game Enthusiast Online Highlights, Mar. 18, 1999.

Game Enthusiast Online Highlights, Mar. 19, 1999.

Game Enthusiast Online Highlights, Mar. 17, 1999.

Game Enthusiast Online Highlights, Oct. 20, 1999.

Joel Easley, "PlayStation II Revealed", Game Week, Sep. 29, 1999.

Inside Sony's Next Generation Playstation, ©1999.

Press Releases, Mar. 18, 1999.

Chris Johnston, "PlayStation Part Deux", Press Start, ©1999.

Nikkei Shimbun, "Sony Making SME, Chemical and SPT into Wholly-Owned Subsidiaries", Mar. 9, 1999.

AM News: Japanese Developers Not All Sold on PS2, Next Generation, Mar. 16, 1999.

Sony To Turn PlayStation Maker Into Wholly Owned Unit-Nikkei, Dow Jones News Service, Mar. 8, 1999.

Yumiko Ono, Sony Antes Up Its Chips In Bet On New Game System, Dow Jones News Service, Mar. 4, 1999.


MacWeek.Com Gets Inside Story on Connectix VGS for Windows; Controversial Emulator of Sony PlayStation Games Curently Available for Macs Only, Business Wire, Mar. 12, 1999.

"DexDrive Bridges Gap", The Tampa Tribune, Mar. 12, 1999.

A Microprocessor With a 128b CPU, 10 Floating-Point MAC's, 4 Floating-Point Dividers, and an MPEG2 Decoder, 1999 IEEE International Solid-State Circuits Conference, Feb. 16, 1999.

- Dreamcast Instruction Manual, Sega Enterprises, Ltd., ©1998.
- “Sega To Launch Video Camera for Dreamcast”, Reuters Business News, Feb. 16, 2000.
- David Pescovitz, “Dream On”, Wired, Aug. 1999.
- Randy Nelson, “Dreamcast 101: Everything You Ever Wanted To Know About Sega’s Powerful New Console”, Official Sega Dreamcast Magazine, Jun. 1999.
- 2D/3D Graphics Card User Manual, Guillemot ©1999.
- Nintendo 64 Instruction Booklet Nintendo of America, 1998.
- Steven Levy, “Here Comes PlayStation II”, Newsweek, Mar. 6, 2000.
- David Sheff, “Sony Smackage: Test Driving The PlayStation II”, Wired, Nov. 1999.
- Introducing The Next Generation PlayStation, Sony Computer Entertainment Inc., ©1999.
- Leadtek GTS, Aug. 3, 2000, www.hexus.net.
- Voodoo 5 5500 Review, Jul. 26, 2000, www.hexus.net.
- ATI Radeon 64 Meg DDR OEM, Aug., 19, 2000, www.hexus.net.
- Microsoft Xbox—The Future of Gaming, Microsoft Xbox Performance Sheet, www.xbox.com.
- Robert L. Cook, “Shade Trees”, Computer Graphics, vol. 18, No. 3, Jul. 1984.
- Wang et al., “Second-Depth Shadow Mapping”, Department of Computer Science, Univ. N.C, Chapel Hill, N.C. pp. 1–7.
- Peercy et al., “Efficient Bump Mapping Hardware”, Computer Graphics Proceedings, Annual Conference Series, 1997.
- Gustavo Oliveira, “Refractive Texture Mappig, Part One”, www.gamasutra.com, Nov., 10, 2000.
- John Schlag, Fast Embossing Effects on Raster Image Data, Graphics Gems IV, Edited by Paul S. Heckbert, Computer Science Department, Carnegie Mellon University, Academic Press, Inc. 1994, pp. 433–437.
- James F. Blinn, “Simulation of Wrinkled Surfaces,” Caltech/JPL, pp. 286–292, SIGGRAPH 78 (1978).
- Tomas Möller and Eric Haines “Real-Time Rendering”, AK Peter, Ltd., ©1999, pp. 127–142.
- Technical Presentation: Vertex Buffers, posted Jun. 12, 2000, www.nvidia.com.
- Technical Presentation: Hardware Transform and Lighting, www.nvidia.com, posted Jun. 12, 2000.
- Technical Presentation: Hardware Bump-mapping Choices and Concepts, Jun. 7, 2000, www.nvidia.com.
- Technical Presentation: How to Bump Map a Skinned Polygonal Model, Jun. 7, 2000, www.nvidia.com.
- Technical Presentation: Computations for Hardware Lighting and Shading, Mar. 17, 2000, www.nvidia.com.
- Technical Presentation: Practical Bump-mapping for Today’s GPUs, Mar. 17, 2000 www.nvidia.com.
- Technical Presentation: Shadows, Transparency, & Fog, Mar. 17, 2000 www.nvidia.com.
- Technical Presentation: GeForce 256 Register Combiners, Mar. 17, 2000, www.nvidia.com.
- Technical Presentation: TexGen & The Texture Matrix, Mar. 15, 2000 www.nvidia.com.
- Technical Presentation: Toon Shading, Mar. 15, 2000, www.nvidia.com.
- Technical Presentation: D3D 7 Vertex Lighting, Mar. 15, 2000, www.nvidia.com.
- Technical Presentation: Per-Pixel Lighting (by S. Dietrich) Mar. 14, 2000 www.nvidia.com.
- Technical Presentation: GeForce 256 and RIVA TNT Combiners, Dec. 8, 1999, www.nvidia.com.
- Technical Presentation: Vertex Cache Optimization, Nov. 12, 1999, www.nvidia.com.
- Technical Presentation: Vertex Blending, Nov. 12, 1999, www.nvidia.com.
- Technical Presentation: Hardware Transform and Lighting, Nov. 12, 1999, www.nvidia.com.
- Technical Presentation: GeForce 256 Overview, Nov. 12, 1999, www.nvidia.com.
- Technical Presentation: DirectX 7 and Texture Management, Nov. 12, 1999 www.nvidia.com.
- Technical Presentation: Dot Product Lighting, Nov. 12, 1999, www.nvidia.com.
- Technical Presentation: Texture Coordinate Generation, Nov. 3, 1999, www.nvidia.com.
- Technical Presentation: Phong Shading and Lightmaps, Nov. 3, 1999, www.nvidia.com.
- Technical Presentation: The ARB\_multitexture Extension, Nov. 3, 1999 www.nvidia.com.
- Technical Presentation: Multitexture Combiners, Nov. 3, 1999, www.nvidia.com.
- Technical Presentation: Emboss Bump Mapping, Nov. 3, 1999, www.nvidia.com.
- Technical Presentation: Hardware Accelerated Anisotropic Lighting, Nov. 3, 1999 www.nvidia.com.
- Technical Presentation: Guard Band Clipping, Nov. 3, 1999, www.nvidia.com.
- The RenderMan Interface, Stephan R. Keith, Version 3.1, Pixar Animation Studios, Sep. 1989.
- The RenderMan Interface, Version 3.2, Pixar Animation Studios, Jul. 2000, www.pixar.com.
- NVIDIA Product Overview, “GeForce2Ultra”, NVIDIA Corporation, Aug. 21, 2000, www.nvidia.com.
- Duke, “Dreamcast Technical Specs”, Sega Dreamcast Review, Sega, 2/99, www.game-revolution.com.
- Marlin Rowley, “GeForce 1 & 2 GPU Speed Tests”, May 11, 2000, www.g256.com.
- “Dreamcast: The Full Story”, Next Generation, Sep. 1998.
- DirectX 7.0 Programmer’s Reference, Microsoft Corporation, 1995–1999 (as part of the DirectX 7.0 SDK on the Companion CD included with “Inside Direct3D”, Microsoft Programming Series, Peter J. Kovach, Microsoft Press, 1999).
- “Inside Direct3D”, Microsoft Programming Series, Peter J. Kovach, Microsoft Press, 1999.
- “OpenGL Programming Guide, The Official Guide to Learning OpenGL, Release 1”, Jackie Nieder, Tom David, Mason Woo, Addison-Wesley Publishing Co., 1993.
- “Procedural Elements for Computer Graphics,” Second Edition, David F. Rogers, McGraw Hill, 1998.
- “Real-Time Rendering,” Tomas Molleir, Eric Haines, AK Peters, 1999.
- “Computer Graphics, Principles and Practice,” Second Edition, The Systems Programming Series, Foley, van Dam, Fiener, Hughes, Addison Wesley, 1990.
- “Principles of Three-Dimensional Computer Animation”, Revised Edition, Michael O’Rourke, W.W. Norton & Company, 1998.

\* cited by examiner








Fig. 3




Fig. 4




Fig. 5 EXAMPLE GRAPHICS PROCESSOR FLOW






Fig. 6

EXAMPLE GRAPHICS PROCESSING LOOP



EXAMPLE MORE DETAILED GRAPHIC PROCESSING LOOP

Fig. 7



EXAMPLE SIMPLE GRAPHIC APPLICATION

Fig. 8

EXAMPLE GX SET COPY CLEAR (BLACK,0x00FFFFFF):





Fig. 9



EXAMPLE PIXEL ENGINE COPY CLEAR REGISTER FORMATS

Fig. 9a




Fig. 10 EXAMPLE (VERTEX AND ATTRIBUTE DESCRIPTION)




Fig. 11 GX SET ARRAY ( GX ATTR, ATTR, VOID + BASE APTR, .8 STRIDE)




Fig. 12

GX SET VTX ATTR ATTR

GX SET VTX ATTR FMT( );




Fig. 13A




Fig. 13B

	GX_VTXFMT0	GX_VTXFMT1	GX_VTXFMT2	GX_VTXFMT3	GX_VTXFMT4	GX_VTXFMT5	GX_VTXFMT6	GX_VTXFMT7
GX_VA_POS								
GX_VA_NRM	n elements format/size scale			format/size				
GX_VA_CLR0							n elements format/size	
GX_VA_CLR1								
GX_VA_TEX0								
GX_VA_TEX1	n elements format/size scale							
GX_VA_TEX2								
GX_VA_TEX3								
GX_VA_TEX4								
GX_VA_TEX5								
GX_VA_TEX6								
GX_VA_TEX7								

Fig. 14 (VERTEX ATTRIBUTE FORMAT TABLE)




Fig. 15 EXAMPLE (GRAPHICS PRIMITIVES)




Fig. 16

GX Call Display List ( )




Fig. 17




Fig. 18A




Fig. 18B

## APPLICATION PROGRAM INTERFACE FOR A GRAPHICS SYSTEM

This application is a continuation of application Ser. No. 09/723,336, filed Nov. 28, 2000.

### CROSS-REFERENCE TO RELATED APPLICATIONS

See the following copending patent applications incorporated herein by reference:

application Ser. No. 09/465,754, filed Dec. 17, 1999 of Moore et al. entitled "Vertex Cache For 3D Computer Graphics"; claiming benefit from provisional application Ser. No. 60/161,915, filed Oct. 28, 1999,

application Ser. No. 09/726,215, filed Nov. 28, 2000 (att. dkt. no. 723-959), of Fouladi et al. entitled "Method and Apparatus for Buffering Graphics Data in a Graphics System" claiming benefit from provisional application Ser. No. 60/226,912 filed Aug. 23, 2000;

application Ser. No. 09/722,367, filed Nov. 28, 2000 (att. dkt. no. 723-968) of Drebin et al. entitled "Recirculating Shade Tree Blender For A Graphics System" claiming benefit from provisional application Ser. No. 60/226,888, filed Aug. 23, 2000;

application Ser. No. 09/722,663, filed Nov. 28, 2000 (att. dkt. no. 723-963) of Fouladi et al. entitled "Graphics System With Copy Out Conversions Between Embedded Frame Buffer And Main Memory" claiming benefit from provisional application Ser. No. 60/227,030, filed Aug. 23, 2000;

application Ser. No. 09/722,390, filed Nov. 28, 2000 (att. dkt. no. 723-972) of Demers, entitled "Low Cost Graphics System With Stitching Hardware Support For Skeletal Animation" claiming benefit from provisional application Ser. No. 60/226,914, filed Aug. 23, 2000;

application Ser. No. 09/726,216, filed Nov. 28, 2000 (att. dkt. no. 723-967) of Drebin et al., entitled "Achromatic Lighting in a Graphics System and Method" claiming benefit from provisional application Ser. No. 60/227,007, filed Aug. 23, 2000.

### FIELD OF THE INVENTION

The present invention relates to computer graphics, and more particularly to interactive graphics systems including but not limited to home video game platforms. Still more particularly this invention relates to an advantageous software programming interface including binary command functions for controlling a graphics chip and to methods for generating, storing and decoding same.

### BACKGROUND AND SUMMARY OF THE INVENTION

Many of us have seen films containing remarkably realistic dinosaurs, aliens, animated toys and other fanciful creatures. Such animations are made possible by computer graphics. Using such techniques, a computer graphics artist can specify how each object should look and how it should change in appearance over time, and a computer then models the objects and displays them on a display such as your television or a computer screen. The computer takes care of performing the many tasks required to make sure that each part of the displayed image is colored and shaped just right based on the position and orientation of each object in a scene, the direction in which light seems to strike each object, the surface texture of each object, and other factors.

Because computer graphics generation is complex, computer-generated three-dimensional graphics just a few years ago were mostly limited to expensive specialized flight simulators, high-end graphics workstations and supercomputers. The public saw some of the images generated by these computer systems in movies and expensive television advertisements, but most of us couldn't actually interact with the computers doing the graphics generation. All this has changed with the availability of relatively inexpensive 3D graphics platforms such as, for example, the Nintendo 64® and various 3D graphics cards now available for personal computers. It is now possible to interact with exciting 3D animations and simulations on relatively inexpensive computer graphics systems in your home or office.

A problem graphics system designers confronted in the past was how to provide a control interface for a graphics system that enables fast, efficient and flexible use of the graphics system by applications designed to be executed thereon. Various application programming interfaces (APIs) and application binary interfaces (ABIs) have been developed in the past for the purpose of enabling graphics application programmers to control the operation of a graphics chip provided in a graphics system. Perhaps the most commonly-used 3D graphics application programming interfaces in current use are Microsoft's Direct3D interface and the OpenGL interface developed through cooperation with Silicon Graphics. See, for example, Kovach, *Inside Direct3D: The Definitive Guide to Real-Time 3D Power and Performance for Microsoft Windows* (Microsoft Press 2000); and Neider et al., *OpenGL Programming Guide: The Official Guide to Learning OpenGL Release 1* (Addison-Wesley Publishing Co. 1993).

As explained in the Kovach book, Microsoft's DirectX application programming interface (API) provides a set of interfaces offering efficient control of multimedia hardware on a computer running Microsoft Windows. Kovach states that DirectX lets programmers work with commands and data structures that are very close to those that the hardware can natively process, without being so low level that code has to be written differently for each device. By writing device-independent code, programmers can create software that will theoretically always perform at its best (according to Kovach)—even as users enhance their systems with new and improved 3D graphics accelerators, sound cards, input devices and other system capabilities.

Kovach explains that the device-independence of DirectX is obtained because the DirectX APIs are built on a hardware abstraction layer (HAL) that hides the device-specific dependencies of the hardware. In fact, DirectX defines some hardware acceleration support features that aren't available on much of the hardware built today in order to provide extensibility for the future.

While the DirectX approach has been widely adopted and is successful in providing compatibility across a wide range of different platform configurations, the use of a thick hardware abstraction layer and associated hardware emulation layer is not particularly suitable for current low cost dedicated video game platforms at the current time. The DirectX API was primarily designed for personal computers costing many hundreds or thousands of dollars and manufactured in a variety of different configurations and permutations. While the DirectX API has been successful in providing compatibility across a wide range of such different platform configurations, this compatibility has come at the expense of efficiency and performance. In the context of a dedicated low-cost video game platform, it is possible to do much better in terms of providing a fully capable program-

ming interface that is very close to the hardware while providing a highly capable and flexible interface for achieving a wide variety of interesting 3-dimensional graphics effects.

One prior approach is described in U.S. patent application Ser. No. 08/990,133 filed Dec. 12, 1997 by Van Hook et al., entitled "Interface For A High Performance Low Cost Video Game System With Coprocessor Providing High Speed Efficient 3D Graphics And Digital Audio Signal Processing." However, further improvements are possible and desirable. In particular, some people criticized the interface described in this prior Van Hook et al., patent application because they thought it was difficult to write applications to. In the home video game arena, it is desirable to maximize performance while keeping the interface used to invoke and control such performance and capabilities as simple and easy to use as possible. Requiring application programmers to write to an unduly complicated interface may increase the time it takes to develop such applications. This can have devastatingly negative effects when it comes time to launch a new video game platform—since the success of the platform may often depend on achieving a certain "critical mass" in terms of the number of games or other applications available at launch time. As some developers of prior new home video game platforms found out, no one wants to buy a new video game system if there are no games to play on it. It is therefore desirable to provide a graphics programming interface that is simple and easy to use and yet is very powerful and flexible.

The present invention solves this problem by providing new and improved interface for graphics systems that is designed to be as thin as possible in order to achieve high performance, while also providing a logical and orthogonal view of the graphics hardware.

The present invention provides a graphics system programming interface with graphics commands allowing geometry to be rendered with many attributes. The interface provides two main methods for drawing geometry. An immediate mode allows the command stream source to send a stream of graphics commands directly to the graphics processor for consumption. This immediate mode interface is useful when the main processor must synthesize geometry data from a higher-level description (e.g., a height field or Bezier patch). The second method feeds a command stream to the graphics processor using a memory-resident display list format. This interface provides superior performance for static data. The immediate interface and the display list interface both support configurable vertex representations. The configurable vertex representations include, for example, direct or indexed vertex components. Vertex components (e.g., position, normal, color and texture coordinates for a number of textures) can all be indexed independently from arrays, or placed directly in the command stream. Additional flexibility is provided by allowing each vertex component to have a differently-sized representation and precision. The available direct types may include, for example, 8-bit signed and unsigned integer, 16-bit signed and unsigned integer, and 32-bit floating point. A scale is available to position the decimal point for the integer types. The indirect types (e.g., 8-bit index or 16-bit index) can be used to index into an array of any of the direct types. This flexible representation allows the game developer to organize vertex data in a way that is appropriate for the game. The ability to index each component separately eliminates a great deal of data duplication.

#### BRIEF DESCRIPTION OF THE DRAWINGS

These and other features and advantages provided by the invention will be better and more completely understood by

referring to the following detailed description of presently preferred embodiments in conjunction with the drawings, of which:

FIG. 1 is an overall view of an example interactive computer graphics system;

FIG. 2 is a block diagram of the FIG. 1 example computer graphics system;

FIG. 3 is a block diagram of the example graphics and audio processor shown in FIG. 2;

FIG. 4 is a block diagram of the example 3D graphics processor shown in FIG. 3;

FIG. 5 is an example logical flow diagram of the FIG. 4 3D graphics processor;

FIG. 6 is a general flow chart of functions performed by an example application for the FIG. 1 graphics system;

FIG. 7 is a flow chart showing the functions of FIG. 6 in more detail;

FIG. 8 shows example simple graphics command stream;

FIG. 9 shows an example binary level interface for setting the embedded color and depth buffer of the FIG. 1 system to a particular (e.g., initial) value;

FIG. 9A shows example pixel engine copy clear register formats;

FIG. 10 shows an example vertex data structure hierarchy including example description information;

FIG. 11 shows an example binary level interface defining a vertex attribute array;

FIG. 12 shows an example binary level interface defining a vertex descriptor;

FIGS. 13A and 13B together show an example binary level interface defining a vertex attribute table;

FIG. 14 schematically illustrates an example vertex attribute format table;

FIG. 15 shows example graphics primitives that may be represented using the vertex data structures herein;

FIG. 16 shows an example binary level interface defining a projection matrix;

FIG. 17 shows an example binary level interface defining a display list to be called; and

FIGS. 18A and 18B show example alternative compatible implementations.

#### DETAILED DESCRIPTION OF EXAMPLE EMBODIMENTS OF THE INVENTION

FIG. 1 shows an example interactive 3D computer graphics system 50. System 50 can be used to play interactive 3D video games with interesting stereo sound. It can also be used for a variety of other applications.

In this example, system 50 is capable of processing, interactively in real time, a digital representation or model of a three-dimensional world. System 50 can display some or all of the world from any arbitrary viewpoint. For example, system 50 can interactively change the viewpoint in response to real time inputs from handheld controllers 52a, 52b or other input devices. This allows the game player to see the world through the eyes of someone within or outside of the world. System 50 can be used for applications that do not require real time 3D interactive display (e.g., 2D display generation and/or non-interactive display), but the capability of displaying quality 3D images very quickly can be used to create very realistic and exciting game play or other graphical interactions.

To play a video game or other application using system 50, the user first connects a main unit 54 to his or her color

television set **56** or other display device by connecting a cable **58** between the two. Main unit **54** produces both video signals and audio signals for controlling color television set **56**. The video signals are what controls the images displayed on the television screen **59**, and the audio signals are played back as sound through television stereo loudspeakers **61L**, **61R**.

The user also needs to connect main unit **54** to a power source. This power source may be a conventional AC adapter (not shown) that plugs into a standard home electrical wall socket and converts the house current into a lower DC voltage signal suitable for powering the main unit **54**. Batteries could be used in other implementations.

The user may use hand controllers **52a**, **52b** to control main unit **54**. Controls **60** can be used, for example, to specify the direction (up or down, left or right, closer or further away) that a character displayed on television **56** should move within a 3D world. Controls **60** also provide input for other applications (e.g., menu selection, pointer/cursor control, etc.). Controllers **52** can take a variety of forms. In this example, controllers **52** shown each include controls **60** such as joysticks, push buttons and/or directional switches. Controllers **52** may be connected to main unit **54** by cables or wirelessly via electromagnetic (e.g., radio or infrared) waves.

To play an application such as a game, the user selects an appropriate storage medium **62** storing the video game or other application he or she wants to play, and inserts that storage medium into a slot **64** in main unit **54**. Storage medium **62** may, for example, be a specially encoded and/or encrypted optical and/or magnetic disk that stores commands for graphics and audio processor **114** and/or instructions controlling main processor **110** to develop such commands. The user may operate a power switch **66** to turn on main unit **54** and cause the main unit to begin running the video game or other application based on the software stored in the storage medium **62**. The user may operate controllers **52** to provide inputs to main unit **54**. For example, operating a control **60** may cause the game or other application to start. Moving other controls **60** can cause animated characters to move in different directions or change the user's point of view in a 3D world. Depending upon the particular software stored within the storage medium **62**, the various controls **60** on the controller **52** can perform different functions at different times.

#### EXAMPLE ELECTRONICS OF OVERALL SYSTEM

FIG. 2 shows a block diagram of example components of system **50**. The primary components include:

- a main processor (CPU) **110**,
- a main memory **112**, and
- a graphics and audio processor **114**.

In this example, main processor **110** (e.g., an enhanced IBM Power PC **750**) receives inputs from handheld controllers **108** (and/or other input devices) via graphics and audio processor **114**. Main processor **110** interactively responds to user inputs, and executes a video game or other program supplied, for example, by external storage media **62** via a mass storage access device **106** such as an optical disk drive. As one example, in the context of video game play, main processor **110** can perform collision detection and animation processing in addition to a variety of interactive and control functions.

In this example, main processor **110** generates 3D graphics and audio commands and sends them to graphics and

audio processor **114**. The graphics and audio processor **114** processes these commands to generate interesting visual images on display **59** and interesting stereo sound on stereo loudspeakers **61R**, **61L** or other suitable sound-generating devices.

Example system **50** includes a video encoder **120** that receives image signals from graphics and audio processor **114** and converts the image signals into analog and/or digital video signals suitable for display on a standard display device such as a computer monitor or home color television set **56**. System **100** also includes an audio codec (compressor/decompressor) **122** that compresses and decompresses digitized audio signals and may also convert between digital and analog audio signaling formats as needed. Audio codec **122** can receive audio inputs via a buffer **124** and provide them to graphics and audio processor **114** for processing (e.g., mixing with other audio signals the processor generates and/or receives via a streaming audio output of mass storage access device **106**). Graphics and audio processor **114** in this example can store audio related information in an audio memory **126** that is available for audio tasks. Graphics and audio processor **114** provides the resulting audio output signals to audio codec **122** for decompression and conversion to analog signals (e.g., via buffer amplifiers **128L**, **128R**) so they can be reproduced by loudspeakers **61L**, **61R**.

Graphics and audio processor **114** has the ability to communicate with various additional devices that may be present within system **100**. For example, a parallel digital bus **130** may be used to communicate with mass storage access device **106** and/or other components. A serial peripheral bus **132** may communicate with a variety of peripheral or other devices including, for example:

- a programmable read-only memory and/or real time clock **134**,
- a modem **136** or other networking interface (which may in turn connect system **100** to a telecommunications network **138** such as the Internet or other digital network from/to which program instructions and/or data can be downloaded or uploaded), and
- flash memory **140**.

A further external serial bus **142** may be used to communicate with additional expansion memory **144** (e.g., a memory card) or other devices. Connectors may be used to connect various devices to busses **130**, **132**, **142**.

#### EXAMPLE GRAPHICS AND AUDIO PROCESSOR

FIG. 3 is a block diagram of an example graphics and audio processor **114**. Graphics and audio processor **114** in one example may be a single-chip ASIC (application specific integrated circuit). In this example, graphics and audio processor **114** includes:

- a processor interface **150**,
- a memory interface/controller **152**,
- a 3D graphics processor **154**,
- an audio digital signal processor (DSP) **156**,
- an audio memory interface **158**,
- an audio interface and mixer **160**,
- a peripheral controller **162**, and
- a display controller **164**.

3D graphics processor **154** performs graphics processing tasks. Audio digital signal processor **156** performs audio processing tasks. Display controller **164** accesses image information from main memory **112** and provides it to video

encoder **120** for display on display device **102**. Audio interface and mixer **160** interfaces with audio codec **122**, and can also mix audio from different sources (e.g., streaming audio from mass storage access device **106**, the output of audio DSP **156**, and external audio input received via audio codec **122**). Processor interface **150** provides a data and control interface between main processor **110** and graphics and audio processor **114**.

Memory interface **152** provides a data and control interface between graphics and audio processor **114** and memory **112**. In this example, main processor **110** accesses main memory **112** via processor interface **150** and memory interface **152** that are part of graphics and audio processor **114**. Peripheral controller **162** provides a data and control interface between graphics and audio processor **114** and the various peripherals mentioned above. Audio memory interface **158** provides an interface with audio memory **126**.

#### EXAMPLE GRAPHICS PIPELINE

FIG. 4 shows a more detailed view of an example 3D graphics processor **154**. 3D graphics processor **154** includes, among other things, a command processor **200** and a 3D graphics pipeline **180**. Main processor **110** communicates streams of data (e.g., graphics command streams and display lists) to command processor **200**. Main processor **110** has a two-level cache **112** to minimize memory latency, and also has a write-gathering buffer **111** for uncached data streams targeted for the graphics and audio processor **114**. The write-gathering buffer **111** collects partial cache lines into fill cache lines and sends the data out to the graphics and audio processor **114** one cache line at a time for maximum bus usage.

Command processor **200** receives display commands in binary format from main processor **110** and parses and decodes them—obtaining any additional data necessary to process them from shared memory **112**. The command processor **200** provides a stream of vertex commands to graphics pipeline **180** for 2D and/or 3D processing and rendering. Graphics pipeline **180** generates images based on these commands. The resulting image information may be transferred to main memory **112** for access by display controller/video interface unit **164**—which displays the frame buffer output of pipeline **180** on display **102**.

FIG. 5 is a logical flow diagram of graphics processor **154**. Main processor **110** may store graphics command streams **210**, display lists **212** and vertex arrays **214** in main memory **112**, and pass pointers to command processor **200** via bus interface **150**. The main processor **110** stores graphics commands in one or more graphics first-in-first-out (FIFO) buffers **210** it allocates in main memory **110** or elsewhere. The command processor **200** fetches:

- command streams from main memory **112** via an on-chip FIFO memory buffer **216** that receives and buffers the graphics commands for synchronization/flow control and load balancing,

- display lists **212** from main memory **112** via an on-chip call FIFO memory buffer **218**, and

- vertex attributes from the command stream and/or from vertex arrays **1000** in main memory **112** via a vertex cache **220**.

Command processor **200** performs command processing operations **200a** that convert attribute types to floating point format, and passes the resulting complete vertex polygon data to graphics pipeline **180** for rendering/rasterization. A programmable memory arbitration circuitry **130** (see FIG. 4) arbitrates access to shared main memory **112** between graph-

ics pipeline **180**, command processor **200** and display controller/video interface unit **164**.

FIG. 4 shows that graphics pipeline **180** may include:

- a transform unit **300**,

- a setup/rasterizer **400**,

- a texture unit **500**,

- a texture environment unit **600**, and

- a pixel engine **700**.

Transform unit **300** performs a variety of 2D and 3D transform and other operations **300a** (see FIG. 5). Transform unit **300** may include one or more matrix memories **300b** for storing matrices used in transformation processing **300a**. Transform unit **300** transforms incoming geometry per vertex from object space to screen space; and transforms incoming texture coordinates and computes projective texture coordinates (**300c**). Transform unit **300** may also perform polygon clipping/culling **300d**. Lighting processing **300e** also performed by transform unit **300b** provides per vertex lighting computations for up to eight independent lights in one example embodiment. Transform unit **300** can also perform texture coordinate generation (**300c**) for embossed type bump mapping effects, as well as polygon clipping/culling operations (**300d**).

Setup/rasterizer **400** includes a setup unit which receives vertex data from transform unit **300** and sends triangle setup information to one or more rasterizer units (**400b**) performing edge rasterization, texture coordinate rasterization and color rasterization.

Texture unit **500** (which may include an on-chip texture memory (TMEM) **502**) performs various tasks related to texturing including for example:

- retrieving textures **504** from main memory **112**,

- texture processing (**500a**) including, for example, multi-texture handling, post-cache texture decompression, texture filtering, embossing, shadows and lighting through the use of projective textures, and BLIT with alpha transparency and depth,

- bump map processing for computing texture coordinate displacements for bump mapping, pseudo texture and texture tiling effects (**500b**), and

- indirect texture processing (**500c**).

Texture unit **500** outputs filtered texture values to the texture environment unit **600** for texture environment processing (**600a**). Texture environment unit **600** blends polygon and texture color/alpha/depth, and can also perform texture fog processing (**600b**) to achieve inverse range based fog effects. Texture environment unit **600** can provide multiple stages to perform a variety of other interesting environment-related functions based for example on color/alpha modulation, embossing, detail texturing, texture swapping, clamping, and depth blending.

Pixel engine **700** performs depth (z) compare (**700a**) and pixel blending (**700b**). In this example, pixel engine **700** stores data into an embedded (on-chip) frame buffer memory **702**. Graphics pipeline **180** may include one or more embedded DRAM memories **702** to store frame buffer and/or texture information locally. Z compares **700a'** can also be performed at an earlier stage in the graphics pipeline **180** depending on the rendering mode currently in effect (e.g., z compares can be performed earlier if alpha blending is not required). The pixel engine **700** includes a copy operation **700c** that periodically writes on-chip frame buffer **702** to main memory **112** for access by display/video interface unit **164**. This copy operation **700c** can also be used to copy embedded frame buffer **702** contents to textures in the main memory **112** for dynamic texture synthesis effects. Anti-

aliasing and other filtering can be performed during the copy-out operation. The frame buffer output of graphics pipeline 180 (which is ultimately stored in main memory 112) is read each frame by display/video interface unit 164. Display controller/video interface 164 provides digital RGB pixel values for display on display 102.

#### EXAMPLE GRAPHICS SYSTEM APPLICATION INTERFACE

As described above, main processor 110 sends graphics commands to graphics and audio processor 114. These graphics commands tell the graphics and audio processor 114 what to do. For example, the graphics commands can tell the graphics and audio processor 114 to draw a particular image onto display device 56. Commands might also tell the graphics and audio processor 114 to produce a particular sound for output by loudspeakers 61. Still other commands might tell the graphics and audio processor 114 to perform so-called "housekeeping" commands and/or to set up a particular state in preparation for a subsequent "action" command.

In the example embodiment, the commands that main processor 110 sends to graphics and audio processor 114 can come from a number of sources. One source of commands is the main processor 110 itself. Under control of program instructions provided, for example, by mass storage access device 106 and/or boot ROM 134, main processor 110 can dynamically create or generate graphics commands under program control to send to graphics and audio processor 114. Main processor 110 can create and send graphics and audio processor 114 any command that the graphics and audio processor understands. Graphics and audio processor 114 will act on the commands and perform the action requested by the command.

Another source of graphics commands for graphics and audio processor 114 is mass storage access device 106. It takes some time for main processor 110 to dynamically create graphics commands. When system 50 is animating a scene in response to real-time inputs from hand controllers 52 or the like, there may be no alternative other than for main processor 110 to dynamically create the graphics commands telling the graphics and audio processor 114 to draw a particular cartoon or other character in a particular position. That way, as the user operates hand controllers 52 of system 50 responds to other input devices, main processor 110 can dynamically adjust or animate the displayed scene in response to those real-time inputs to provide interactive animation. Such fun and exciting interactive animation is generally provided by main processor 110 dynamically creating graphics commands "on the fly."

Sometimes, however, some part of a scene to be displayed is relatively static and does not change in response to real-time inputs. For example, a complicated 3D world background such as a castle, a mountain fortress, a landscape or an undersea world may not change much or at all as animated characters move through the world. In such cases, it is possible to use an offline authoring computer to develop the complex series of graphics commands required to draw the particular scene or portion of the scene and store them in a preconstructed display list. Similarly, sound effects, music and other sounds can be pre-generated off-line by a sound authoring system. The resulting display list(s) and/or audio list(s) can be stored on an optical disk 62 or other mass storage device. When it comes time to draw the scene and/or play the sound, the associated display list(s) and/or audio list(s) can simply be read from the mass storage

device 62 and stored into main memory 112. Main processor 110 may then, under program control, tell the graphics and audio processor 114 where to find the preconstructed display list(s) and/or audio list(s), and instruct the graphics and audio processor to execute the lists. In this way, main processor 110 does not have to devote its processing resources to develop complicated display lists and/or audio lists since that task is off-loaded to an off-line authoring system that pre-compiles the lists in preparation for use by the graphics and audio processor 114. Such display lists can be stored by any storage device within system 50 or accessible to it, including but not limited to memory card 144, flash memory 140, boot ROM 134, audio memory 126, etc. The commands could be embedded in hardware such as gate arrays or the like, and communicated to system 50 via any of the external interfaces such as bus 142, bus 132, handheld controller ports, parallel bus 130, infrared, etc.

Still another possibility is for commands intended for processing by the graphics and audio processor 114 to arrive via a data communications connection such as network 138. In one example, graphics commands, audio commands and/or other commands intended to be processed by graphics and audio processor 114 may arrive from a data communications network 138 via modem 136. Such commands could be transmitted, for example, from a remote system 50 of the same configuration as that shown in FIG. 2 in order to provide interactive multi-user remote game play. The commands could originate from any other source including a personal computer, a mini-computer or main frame computer, a data transmitter, or any other data source.

Irrespective of how commands intended for graphics and audio processor 114 arrive and how they are stored before and/or after arrival, the first step in causing such commands to be processed by the graphics and audio processor 114 is to make them available to the graphics and audio processor. In the example embodiment, making the commands available to graphics and audio processor 114 can be accomplished either by having main processor 110 send the commands directly to the graphics and audio processor via a data bus in an immediate mode of command transfer, or by storing the commands in some memory accessible to the graphics and audio processor 114 (e.g., main memory 112, audio memory 126, or any other memory device to which the graphics and audio processor 114 is coupled) and informing the graphics and audio processor where to find the commands and instructing it to begin processing those commands.

#### GRAPHICS COMMAND STREAM

In the example embodiment, graphics and audio processor 114 may receive register and other commands from main processor 110 and/or some other source (e.g., main memory 112) in the form of a graphics command stream. Generally, the data that is sent from main processor 110 to the graphics and audio processor 114 can be called the "command stream." The command stream holds drawing commands along with vertices and their attributes and mechanisms for loading registers and changing modes in the graphics pipeline 180. The stream of graphics commands are sent to the graphics and audio processor 114 for processing in a generally sequential manner. Such stream commands can be provided in a so-called "immediate mode" directly from main processor 110 to the graphics and audio processor 114 through a sprite gatherer arrangement (see FIG. 4) to provide very efficient transfer of graphics and audio commands from the main processor 110 to the graphics and audio processor 114. The graphics command stream can also be provided to

11

graphics and audio processor 114 via main memory 112 or other memory or other data communications capabilities within system 50. The cache/command processor 200 within the graphics and audio processor 114 performs tasks such as, for example, fetching the command stream from main memory 112; fetching vertex attributes (e.g., either from the command stream or from arrays in main memory); converting attribute types to appropriate formats (e.g., floating point); and transferring complete vertices to the remainder of the graphics pipeline 180 for processing.

As shown in FIG. 5, the command stream is fetched from the first-in-first-out buffer 210 (see also above-referenced Provisional Application No. 60/226,912, filed Aug. 23, 2000

12

and its corresponding utility Application No.09/726,215, filed Nov. 28, 2000 (atty. dkt. no. 723-959), both entitled "Method and Apparatus for Buffering Graphics Data in a Graphics System ", and read into a FIFO buffer 216. The command processor 200 strips and decodes the commands to decide the number of data associated with it. The data is then taken from the stream and/or fetched from an array in main memory 112, based on an index value. The vertex attributes are converted to floating point data that can be consumed by the transform engine 300.

The following are example command stream formats in the example embodiment:

TABLE I

Opcode	Opcode(7:0)	Next	Followed by
NOP	00000000	none	none
Draw_Quads	10000vat(2:0)	VertexCount(15:0)	Vertex attribute stream
Draw_Triangles	10010vat(2:0)	VertexCount(15:0)	Vertex attribute stream
Draw_Triangle_strip	10011vat(2:0)	VertexCount(15:0)	Vertex attribute stream
Draw_Triangle_fan	10100vat(2:0)	VertexCount(15:0)	Vertex attribute stream
Draw_Lines	10101vat(2:0)	VertexCount(15:0)	Vertex attribute stream
Draw_Line_strip	10110vat(2:0)	VertexCount(15:0)	Vertex attribute stream
Draw_Points	10111vat(2:0)	VertexCount(15:0)	Vertex attribute stream
CP_LoadRegs (for CP only registers)	0000lxxx	Address[7:0]	32 bits data
XF_LoadRegs (This is used for loading all XF registers, including matrices. It can be used to load matrices with immediate data)	00010xxx	none	(N+2)*32 bits First 32 bit: 15:00 register address in XF 19:16 number of 32 bit registers to be loaded (N+1, 0 means 1, 0xff means 16) 31:20 unused Next N+1 32 bits: 31:00 register data 32 bits
XF_IndexLoadRegA (registers are in the first 4K address space of the XF. It can be used to block load matrix and light registers)	00100xxx	none	11:0 register address in XF 15:12 number of 32 bit data, (0 means 1, 0xff means 16) 31:16 Index to the register Array A
XF_IndexLoadRegB (registers are in the first 4K address space of the XF. It can be used to block load matrix and light registers)	0010lxxx	none	32 bits 11:0 register address in XF 15:12 number of 32 bit data, (0 means 1, 0xff means 16) 31:16 Index to the register Array B
XF_IndexLoadRegC (registers are in the first 4K address space of the XF. It can be used to block load matrix and light registers)	00110xxx	none	32 bits 11:0 register address in XF 15:12 number of 32 bit data. (0 means 1, 0xff means 16) 31:16 Index to the register Array C
XF_IndexLoadRegD (registers are in the first 4K address space of the XF. It can be used to block load matrix and light registers)	00111xxx	none	32 bits 11:0 register address in XF 15:12 number of 32 bit data, (0 means 1, 0xff means 16) 31:16 Index to the register Array D
Call_Object	01000xxx	none	2x32 25:5 address (need to be 32 byte align) 25:5 count (32 byte count)
V\$ Invalidate	0100lxxx	none	none
SU_ByPassCmd (This includes all the register load below XF and all setup unit commands, which bypass XF)	0110,SUattr(3:0)	none	32 bit data

## 13

As shown in Table I above, the graphics command stream can include register load commands. Register commands are, in general, commands that have the effect of writing particular state information to particular registers internal to the graphics and audio processor **114**. The graphics and audio processor **114** has a number of internal registers addressable by main processor **110**. To change the state of the graphics and audio processor **114** in particular way, main processor can write a particular value to a particular register internal to the graphics and audio processor **114**. Register commands have the advantage of allowing the graphics pipeline to retain drawing state information that main processor **110** can selectively change by sending further register load commands.

For example, the vertices in a draw command can all share the same vertex attribute data structure defining a number of attributes associated with a vertex. Sending all of the vertex attribute information before a draw command could be costly. It therefore may be desirable to store most of the common vertex types in registers within the graphics and audio processor **114** and to simply pass an index to the stored table. These tables may not need to be updated each time a new draw command is sent down, but may only need to be updated every once in a while. In the example embodiment, command processor **200** holds a vertex com-

## 14

mand descriptor register (VCD) and a eight-entry vertex attribute table (VAT) defining whether the attribute is present and if so whether it is indexed or direct. A "load\_VCD" register command is used to update the register whenever updating is necessary.

In certain situations, main processor **110** may also read the graphics and audio processor **114** internal registers to determine the state of the graphics and audio processor. For example, the main processor **110** can start and stop the graphics and audio processor **114** and/or determine its general status by reading from and/or writing to internal registers within the graphics and audio processor. Main processor **110** can also load a number of graphics values (e.g., transformation matrices, pixel formats, vertex formats, etc.) by writing to registers within the graphics and audio processor **114**. As another example, main processor **110** can write to a series of FIFO control registers within the graphics and audio processor **114** that control where the graphics and audio processor **114** obtains further commands for processing.

The following are example command registers used for defining transformation matrices, vertex control data, vertex attribute tables, vertex arrays, vertex stride, and other state parameters:

TABLE II

Register name	Register address[7:0]	Bit fields
MatrixIndexA	0011xxxx	5:0 index for position/normal matrix 11:6 index for tex0 matrix 17:12 index for tex1 matrix 23:13 index for tex2 matrix 29:24 index for tex3 matrix
MatrixIndexB	0100xxxx	5:0 index for tex4 matrix 11:6 index for tex5 matrix 17:12 index for tex6 matrix 23:18 index for tex7 matrix
VCD_Lo	0101xxxx	16:00 VCD 12 to 0 0 PosMatIdx 1 Tex0MatIdx 2 Tex1MatIdx 3 Tex2atIdx 4 Tex3MatIdx 5 Tex4MatIdx 6 Tex5MatIdx 7 Tex6MatIdx 8 Tex7MatIdx 10:9 Position 12:11 Normal 14:13 ColorDiffused 16:15 ColorSpecular
VCD_H1	0110xxxx	15:00 VCD 20 to 13 01:00 Tex0Coord 03:02 Tex1Coord 05:04 Tex2Coord 07:06 Tex3Coord 09:08 Tex4Coord 11:10 Tex5Coord 13:12 Tex6Coord 15:14 Tex7Coord
VAT_group0	0111x,vat[2:0]	32 bits 08:00 Position parameters 12:09 Normal parameters 16:13 ColorDiffused parameters 20:17 ColorSpecular parameters 29:21 Tex0Coord parameters 30:30 ByteDequant 31:31 NormalIndex3
VAT_group1	1000x,vat[2:0]	32 bits 08:00 Tex1Coord parameters 17:09 Tex2Coord parameters 26:18 Tex3Coord parameters

TABLE II-continued

Register name	Register address[7:0]	Bit fields
VAT_group2	1001x.vat[2:0]	30:27 Tex4Coord parameters sub-field[3:0] 31 unused 32 bits 04:00 Tex4Coord parameters sub-field[8:4] 13:05 Tex5Coord parameters 22:14 Tex6Coord parameters 31:23 Tex7Coord parameters
ArrayBase	1010.array[3:0]  array[3:0]: 0000 = attribute9 base register 0001 = attribute10 base register 0010 = attribute11 base register 0011 = attribute12 base register 0100 = attribute13 base register 0101 = attribute14 base register 0110 = attribute15 base register 0111 = attribute16 base register 1000 = attribute17 base register 1001 = attribute18 base register 1010 = attribute19 base register 1011 = attribute20 base register 1100 = IndexRegA base register 1101 = IndexRegB base register 1110 = IndexRegC base register 1111 = IndexRegD base register	32 bit data 25:00 Base(25:0) 31:26 unused
ArrayStride	1011.array[3:0]  array[3:00]: 0000 = attribute9 stride register 0001 = attribute10 stride register 0010 = attribute11 stride register 0011 = attribute12 stride register 0100 = attribute13 stride register 0101 = attribute14 stride register 0110 = attribute15 stride register 0111 = attribute16 stride register 1000 = attribute17 stride register 1001 = attribute18 stride register 1010 = attribute19 stride register 1011 = attribute20 stride register 1100 = IndexRegA stride register 1101 = IndexRegB stride register 1110 = IndexRegC stride register 1111 = IndexRegD stride register	32 bit data 07:00 Stride(7:0) 31:08 unused

In the example embodiment, the command processor **200** converts the command stream to a vertex stream which it sends to transform unit **300** for further processing. The vertex stream sent to the transform unit **300** can change based on the current mode, but the data ordering per vertex is essentially the same and is fixed as shown in the following table:

supplied, then the first texture will start at word 6 instead of word 8. Texture comes after color.

EXAMPLE GRAPHICS APPLICATION PROCESSING LOOP

FIG. 6 shows an example summary flow chart of steps that may be performed by system **50** under control of an application such as a video game program to develop

TABLE III

Location in stream (in words)	Data	Description
0 to 2	X, Y, Z in 32b SPFP	Geometry information in single precision floating point format
3 to 5	Nx, Ny, Nz in 32b SPFP	Normal vector
6	RGBA in 32b integer (8b/comp)	Color0 per vertex (RGBA)
7	RGBA in 32b integer (8b/comp)	Color1 per vertex (RGBA)
8 to 10	Tx, Ty, Tz in 32b SPFP	Binormal vector T
11 to 13	Bx, By, Bz in 32b SPFP	Binormal vector B
14 to 15	S0, T0 in 32b SPFP	Texture 0 data
16 to 29	Sn, Tn in 32b SPFP	Texture 1 to n data

The location of words in the stream is order dependent, but not exact. For example, if the per-vertex color is not

65

graphics for display on the display **56**. System **50** is first booted from boot ROM **134** (block **610**). During or after

system boot, main processor 110 and graphics and audio processor 114 are initialized and the operating system is also initialized (block 612). System 50 is then ready to have its logic set up for a specific application, such as a videogame (block 614). The state of the graphics and audio processor 114 is set by sending an appropriate graphics command stream to the graphics and audio processor (block 616). The system 50 is then ready to process vertex information provided through a further command stream describing a primitive in terms of vertex data structure, and draw commands (block 618). Once the embedded frame buffer 702 has a completed frame of data, further commands sent to the graphics and audio processor 114 cause the processor to copy its embedded frame buffer to an external frame buffer 113 allocated in main memory 112 (block 620). The video interface 164 is then used to display the image data in the external frame buffer on a display device (block 622). Once a completed frame is copied from the embedded frame buffer, the system is ready to begin processing the next frame, as indicated by the frame loop 624 in FIG. 6. FIG. 7 shows is greater detail some of the possible graphics commands that can be performed in connection with each of the various steps shown in FIG. 6.

EXAMPLE SIMPLE GRAPHICS COMMAND STREAM

For purposes of illustration FIG. 8 shows an example simple graphics command stream drawing a single graphics primitive (e.g., a single triangle) on display 56. In this example simple graphics command stream, the first set of graphics commands initializes the graphics pipeline 180 (GXInit( )) (block 1002). When the graphics and audio processor 114 comes out of hardware reset, its internal register values are undefined and therefore need to be set by main processor 110 under control of boot ROM 134 and/or the application program. A series of initialization commands such as register load commands may be issued to set the state of graphics and audio processor 114 to a known, pre-defined state that is suitable for the particular application that is to be performed. Of course, the application can reset any of these values to any other desired value on a dynamic basis. However, to save the application work, it may be desirable for boot ROM 134 to provide a series of state-setting graphics initialization commands that set up the graphics and audio processor 114 so that it is operating in a known functioning default graphics mode.

One example initialization may be to clear (set) the internal embedded frame buffer 702 to an all-black color value with z (distance) of the corresponding embedded depth buffer being set to infinite distance at each location. Such a "set copy clear" instruction effectively sets up a clean canvas onto which graphics and audio processor 114 can draw the next image, and is re-formed during an embedded frame buffer copy operation in the example embodiment. FIG. 9 shows an example binary data stream that may be

sent to the graphics and audio processor 114 to control it to clear (set) its internal frame buffer 113 to a black color at each and every pixel location and to set the corresponding internal depth buffer to infinite distance at every pixel. In the particular example shown, such a command stream comprises three pixel engine register load commands:

- pixel engine copy clear (alpha red),
- pixel engine copy clear (green blue),
- pixel engine copy clear (z).

In this example, the first portion of each register load command includes a "cp\_cmd\_su\_bypass" command string (0x61) (where "0x" indicates hexadecimal). As explained in Table I above, this command string provides access to registers within graphics pipeline 180 below transform unit 300. This string is followed by a pixel engine register designation (1x4F in the case of a pixel engine copy clear alpha/red command), a 1-byte pad; and a 1-byte alpha value and a 1-byte red value (FF for black).

A similar format is used for the pe\_copy\_clear\_green blue command except that the last two bytes indicate the green and blue values (FF for black), and a different pixel engine register designation (0x50) is used for the green/blue register values. Similarly, the pe\_copy\_clear\_z command is issued by sending a cp\_cmd\_su\_bypass string (0x61) followed by a register designator 0x51 (designating a pixel engine z value register) followed by a 24-bit z (depth) value. The three set copy clear commands shown in FIG. 9 could be issued in any order (e.g., set z copy clear or set green/blue copy clear could be issued first). See FIG. 9A which shows example register formats.

In response to receipt of the FIG. 9 commands, pixel engine 700 writes the specified alpha, red, green, blue and z values into embedded frame buffer 702.

Referring once again to FIG. 8, a next step in preparing to display an image onto display 56 may be to define the various data structures associated with the vertices of the primitive to be drawn. The FIG. 10 diagram shows, for purposes of illustration, example vertex and vertex attribute descriptors that can be used to describe vertices. In the example embodiment, all vertices within a given primitive share the same vertex descriptor and vertex attribute format. The vertex descriptor in the example embodiment describes which attributes are present in a particular vertex format and how they are transmitted from the main processor 110 (or other source) to the graphics processor 114 (e.g., either direct or indexed). The vertex attribute format describes the format (e.g., type, size, format, fixed point scale, etc.) of each attribute in a particular vertex format. The vertex attribute format together with the vertex descriptor may be thought of as the overall vertex format.

The following is an example of a vertex attribute table (VAT) (see also above-referenced application Ser. No. 09/465,754 filed Dec. 17, 1999 entitled "Vertex Cache For 3D Computer Graphics") indexed by a draw command "vat" field, with each entry in the table specifying characteristics for all of the thirteen attributes:

TABLE IV

VERTEX ATTRIBUTE TABLE (VAT)

Attribute number	Attribute name	bits	Encoding
0	PosMatIdx	0	Position/normal matrix index. Always direct if present 0: not present 1: present NOTE: position and normal matrices are stored in 2 separate RAMs in the Xform unit, but there is a one to one correspondence between normal and position index. If index "A" is used for the

TABLE IV-continued

VERTEX ATTRIBUTE TABLE (VAT)			
Attribute number	Attribute name	bits	Encoding
1	Tex0MatIdx	1	position. then index "A" needs to be used for the normal as well. TextCoord0 matrix index, always direct if present 0: not present 1: present
2	Tex1MatIdx	2	TextCoord0 matrix index, always direct if present 0: not present 1: present
3	Tex2MatIdx	3	TextCoord0 matrix index, always direct if present 0: not present 1: present
4	Tex3MatIdx	4	TextCoord0 matrix index, always direct if present 0: not present 1: present
5	Tex4MatIdx	5	TextCoord0 matrix index, always direct if present 0: not present 1: present
6	Tex5MatIdx	6	TextCoord0 matrix index, always direct if present 0: not present 1: present
7	Tex6MatIdx	7	TextCoord0 matrix index, always direct if present 0: not present 1: present
8	Tex7MatIdx	8	TextCoord0 matrix index, always direct if present 0: not present 1: present
9	Position	10:9	00: reserved 10:8 bit index 01: direct 11:16 bit index
10	Normal	12:11	00: not present 10:8 bit index 01: direct 11:16 bit index
11	Color0	14:13	00: not present 10:8 bit index 01: direct 11:16 bit index
12	Color1	16:15	00: not present 10:8 bit index 01: direct 11:16 bit index
13	Tex0Coord	18:17	00: not present 01: direct 10:8 bit index 11:16 bit index
14	Tex1Coord	20:19	00: not present 01: direct 10:8 bit index 11:16 bit index
15	Tex2Coord	22:21	00: not present 01: direct 10:8 bit index 11:16 bit index
16	Tex3Coord	24:23	00: not present 01: direct 10:8 bit index 11:16 bit index
17	Tex4Coord	26:25	00: not present 01: direct 10:8 bit index 11:16 bit index
18	Tex5Coord	28:27	Same as above
19	Tex6Coord	30:29	00: not present 01: direct 10:8 bit index 11:16 bit index
20	Tex7Coord	32:31	00: not present 01: direct 10:8 bit index 11:16 bit index

As described in application Ser. No. 09/465,754, as well as above, entries in the vertex descriptor information can be either direct or indexed. Indexed vertex attributes include an index to an array instead of a value. The index may be an 8-bit or 16-bit pointer into an array of attributes. In the example embodiment, there is one base address register per attribute in the command processor **200**. The index is not simply an offset into the array, but rather depends on a number of factors including, for example, the number of components in the attribute; the size of the component; padding between attributes for alignment purposes; and whether multiple attributes are interleaved in the same array. To provide maximum flexibility, there is also an array stride register for each attribute. The distance between two attributes (computed by software) is loaded into this register.

Calculations are used to calculate the offset and to calculate the actual memory address based on an index value. An example address calculation is as follows:

$$\text{Memory address} = \text{ArrayBase}[I] + \text{index} * \text{ArrayStride}[I],$$

where I is the attribute number. In one particular implementation, the ArrayBase value is a 26-bit byte address, and ArrayStride is an 8-bit value.

A vertex can have direct and indirect attributes intermixed. For short values, it may be more efficient to send the actual value than a pointer to the value. Any attribute in the example embodiment can be sent directly or as in index into an array.

In general, the steps required to draw a primitive include describing which attributes are present in the vertex format

(i.e., define the vertex attribute table); describing whether the attributes are indexed or referenced directly (i.e., define the vertex descriptor); for indexed data, delivering a vertex array that can be referenced by array pointers and strides; describing the number of elements in each attribute and their type; describing the primitive type; and then, finally, drawing the primitive by sending the graphics processor **114** draw command with a stream of vertices that match the vertex description in attribute format (see FIG. 8, blocks **1004**, **1006**, **1008**).

FIG. 11 shows an example "set array" command used to help define a vertex format (see FIG. 8 block **1004**, "Define and Align Vertex Arrays"). In the example embodiment, the example "set array" command sets the command processor array base register for a particular vertex array and also sets the array stride register for the array. FIG. 11 shows particular example binary bit patterns that may be used for this command. In this example, to set an array base register, the graphics command stream may include:

an initial "0x08" value indicating "cp\_cmd\_load reg" (i.e., load a command processor **200** register) followed by

a 2-byte value indicating which array base register is to be loaded, followed by

an additional 4-byte value providing an address to the array in memory.

In this particular example, the 2-byte value indicating which array base register is to be loaded has the format "1xAx", where the byte "x" following the "A" value encodes a particular one of the attributes set forth in Table IV above. Note that some of the Table IV attributes (i.e., the matrix indices) are not included in the encoding in the example embodiment. In the example embodiment, the 4-byte address in memory is encoded by providing six initial bits of 0 padding followed by a 26-bit address. Setting the array stride register value is similar except that the third and fourth bytes indicate an array stride register (e.g., "1xBx" and the following value comprises four bytes containing an initial 24-bit 0 padded value and an 8-bit stride value for the array.

Referring once again to FIG. 8, a further step preliminary to issuing a draw command may be to set up a vertex descriptor and a vertex attribute table (block **1006**). FIG. 12 shows an example command stream used to set a vertex descriptor. In the example embodiment, setting a vertex descriptor involves setting two associated register values ("vcd\_lo" "vcd\_hi") within command processor **200** in order to specify the particular vertex descriptor attributes associated with the primitive to be displayed. FIG. 12 shows particular binary encodings used to tell the graphics and audio processor **114** to load the vcd\_lo and vcd\_hi registers (e.g., "0x0850" for an example vcd\_lo register and "0x0860" to specify loading a cp\_vcd\_hi register). Values following each of these 4-byte commands indicates particular vertex attribute values as shown in Table 4 above, and as encoded in the particular binary bit patterns slots shown in FIG. 12.

In more detail, the vertex descriptor stored in the VCD\_lo VCD\_hi register includes at least one bit for each of the twenty attributes shown in Table IV, that bit generally indicating whether the attribute is provided directly or via an array. In the example embodiment, the VCD\_lo register contains a 17-bit value, providing bit flags indicating direct or indexed for each of the first twelve attributes in Table IV. The particular bit encodings are shown in the last column of Table IV. Note that certain attribute encodings indicate whether or not the attribute is present (since the attribute is

always direct if it is present), and certain other encodings span multiple bits and provide information as to the type of index if the attribute is indexed (e.g., the "position" value may span two bits with a value "01" for direct, "10" for 8-bit index, and "11" for 16-bit index). Similarly, the VCD\_hi register contains bit fields corresponding to attributes 13-20 (i.e., texture 0 coordinate through texture 7 coordinate) as shown in Table IV above.

On a more abstract level, the GXSetVtxDesc command is used to indicate whether an attribute is present in the vertex data, and whether it is indexed or direct. There is only one active vertex descriptor, known as the current vertex descriptor. A GXSetVtxDesc command can be used to set a value of GX\_NONE for all the attributes in the current vertex descriptor to indicate that no data for this attribute will be present in the vertex. Once the VCD registers are cleared, the application only needs to describe attributes that it intends to provide. As shown in Table IV, possible attributes are:

Position, GX\_VA\_POS (this attribute is required for every vertex descriptor).

Normal, GX\_VA\_NRM, or normal/binormal/tangent, GX\_VA\_NBT.

Color\_0, GX\_VA\_CLR0.

Color\_1, GX\_VA\_CLR1.

Up to 8 texture coordinates, GX\_VA\_TEX0-7.

A position/normal matrix index, GX\_VA\_PNMTXIDX.

A texture matrix index, GX\_VA\_TEXOMTXIDX-GX\_VA\_TEX7MTXIDX.

The last two attributes listed are 8-bit indices which are used for referencing a transformation matrix in the on-chip matrix memory. This supports simple skinning of a character, for example. These indices are different from the other attributes in that they may only be sent as direct data.

The graphics processor (GP) **114** assumes that the application will send any attribute data you have specified in the ascending order shown in Table IV, that is:

Order Attribute

0 GX\_VA\_PNMTXIDX

1 GX\_VA\_TEXOMTXIDX

2 GX\_VA\_TEX1MTXIDX

3 GX\_VA\_TEX2MTXIDX

4 GX\_VA\_TEX3MTXIDX

5 GX\_VA\_TEX4MTXIDX

6 GX\_VA\_TEX5MTXIDX

7 GX\_VA\_TEX6MTXIDX

8 GX\_VA\_TEX7MTXIDX

9 GX\_VA\_POS

10 GX\_VA\_NRMorGX\_VA\_NBT

11 GX\_VA\_CLR1

12 GX\_VA\_CLR0

13 GX\_VA\_TEX1

14 GX\_VA\_TEX0

15 GX\_VA\_TEX2

16 GX\_VA\_TEX3

17 GX\_VA\_TEX4

18 GX\_VA\_TEX5

19 GX\_VA\_TEX6

20 GX\_VA\_TEX7

Texture coordinates are enabled sequentially, starting at GX\_VA\_TEX0.

#### DESCRIBING ATTRIBUTE DATA FORMATS

FIGS. 13A and 13B show an example command stream for setting vertex attribute formats. The Vertex Attribute

Format Table (VAT) allows the application to specify the format of each attribute for up to eight different vertex formats. The VAT is organized as shown in FIG. 14. The application can store eight predefined vertex formats in the table. For each attribute in a vertex, the applicaiton can specify the following:

- The number of elements for the attribute.
- The format and size information.
- The number of fractional bits for fixed-point formats using the scale parameter (the scale parameter is not relevant to color or floating-point data).

**EXAMPLE VERTEX ATTRIBUTE FORMAT COMMAND (GXSETVTXATTRFMT)**

```
//format index attribute n elements format n frac bits
GXSetVtxAttrFmt(GX_VTXFMT0, GX_VA_POS,
GX_POS_XYZ, GX_S8, 0);
GXSetVtxAttrFmt(GX_VTXFMT0, GX_VA_CLRO,
GX_CLR_RGBA, GX_RGBA8, 0);
The high-level code above defines vertex attribute format zero. GX_VTXFMT0 indicates that "position" is a 3-element coordinate (x, y, z) where each element is an 8-bit 2's complement signed number. The scale value indicates the number of fractional bits for a fixed-point number, so zero indicates that the data has no fractional bits. The second command specifies that the GX_VA_CLRO attribute has four elements (r, g, b, a) where each element is 8 bits. The matrix index format is not specified in the table because it is always an unsigned 8-bit value. The scale value is implied for normals (scale=6 or scale=14) and not needed for colors. Also, normals are assumed to have three elements, Nx, Ny, Nz (for GX_VA_NRM), and nine elements, Nx, Ny, Nz, Bx, By, Bz, Tx, Ty, Tz (for GX_VA_NBT). Normals are generally always signed values. The normal format (GX_VA_NRM) is also used for binormals/tangents (GX_VA_NBT) when they are enabled in the current vertex descriptor. The VAT in the Graphics Processor has room for eight vertex
```

formats. The application can describe most of its attribute quantization formats early in the application, loading this table as required. Then the application provides an index into this table, which specifies the vertex attribute data format, when it starts drawing a group of primitives. If the application requires more than eight vertex formats it must manage the VAT table by reloading new vertex formats as needed.

FIGS. 13A and 13B show example binary-level commands for controlling the graphics and audio processor 114 to load an example vertex attribute table (VAT). In the example embodiment, the VAT spins three separate register loads (VAT\_A, VAT\_B, VAT\_C) so that setting a vertex attribute format involves writing values to three internal "VAT" registers within the graphics and audio processor 114, i.e.:

- "0x0870" [4-byte value] to write to the cp\_VAT\_A register,
- "0x0880" [4-byte value] to write to the cp\_VAT\_B register, and
- "0x0890" [4-byte value] to write to the cp\_VAT\_C register.

As shown in FIG. 13A, the binary bit field encoding for the VAT\_A register write involves providing position, normal, color 1, color 2, texture 0 coordinate, and other information (i.e., byte dequantization and normal index bits) in the binary pattern slots shown. Similarly, the binary bit field encoding for the VAT\_B register write involves providing formatting information for texture coordinate 1, texture coordinate 2, texture coordinate 3 and part of texture coordinate 4; and the information to be stored in the VAT\_C register provides attribute format information for the rest of texture coordinate 4, texture coordinate 5, texture coordinate 6 and texture coordinate 7. FIGS. 13A and 13B show the particular bit pattern encodings that may be used. Additional explanation of these particular attributes is set forth in Table V:

TABLE V

Bit field	Attribute number	Attribute name	.CompCount sub-field(0)	.CompSize sub-field(3:1)	Shift amount sub-field(8:4)
8:0	9	Position	0: two (x,y) 1:three (x,y,z)	0:ubyte 1:byte 2:ushort 3:short 4:float 5-7 reserved	Location of decimal point from LSB. This shift applies to all u/short components and to u/byte components where ByteDequant is asserted (Below). NA (Byte: 6, Short: 14)
12:9	10	Normal	0: three normals 1: nine normals	0:reserved 1:byte 2:reserved 3:short 4:float 5-7 reserved	
16:13	11	Color0	0: three (r,g,b)  1: four (r,g,b,a)	0:16 bit 565 (three comp) 1:24 bit 888 (three comp) 2:32 bit 888x (three comp) 3:16 bit 4444 (four comp) 4:24 bit 6666 (four comp) 5:32 bit 8888 (four comp)	NA
20:17	12	Color1	0: three (r,g,b)  1: four (r,g,b,a)	0:16 bit 565 (three comp) 1:24 bit 888 (three comp) 2:32 bit 888x (three comp) 3:16 bit 4444 (four comp) 4:24 bit 6666 (four comp) 5:32 bit 8888 (four comp)	NA
29:21	13	Tex0Coord	0: one (s) 1: two (s,t)	0:ubyte 2:ushort 4:float 1:byte 3:short 5-7 reserved	Location of decimal point from LSB. This shift applies to all u/short components and to u/byte components where

TABLE V-continued

Bit field	Attribute number	Attribute name	.CompCount sub-field(0)	.CompSize sub-field(3:1)	Shift amount sub-field(8:4)
38:30	14	Tex1Coord	0: one (s) 1: two (s,t)	0:u.byte 2:ushort 4:float 1:byte 3:short 5-7 reserved	ByteDequant is asserted (Below). Location of decimal point from LSB. This shift applies to all u/short components and to u/byte components where ByteDequant is asserted (Below).
47:39	15	Tex2Coord	0: one (s) 1: two (s,t)	0:u.byte 2:ushort 4:float 1:byte 3:short 5-7 reserved	Location of decimal point from LSB. This shift applies to all u/short components and to u/byte components where ByteDequant is asserted (Below).
56:48	16	Tex3Coord	0: one (s) 1: two (s,t)	0:u.byte 2:ushort 4:float 1:byte 3:short 5-7 reserved	Location of decimal point from LSB. This shift applies to all u/short components and to u/byte components where ByteDequant is asserted (Below).
65:57	17	Tex4Coord	0: one (s) 1: two (s,t)	0:u.byte 2:ushort 4:float 1:byte 3:short 5-7 reserved	Location of decimal point from LSB. This shift applies to all u/short components and to u/byte components where ByteDequant is asserted (Below).
74:66	18	Tex5Coord	0: one (s) 1: two (s,t)	0:u.byte 2:ushort 4:float 1:byte 3:short 5-7 reserved	Location of decimal point from LSB. This shift applies to all u/short components and to u/byte components where ByteDequant is asserted (Below).
83:75	19	Tex6Coord	0: one (s) 1: two (s,t)	0:u.byte 2:ushort 4:float 1:byte 3:short 5-7 reserved	Location of decimal point from LSB. This shift applies to all u/short components and to u/byte components where ByteDequant is asserted (Below).
92:84	20	Tex7Coord	0: one (s) 1: two (s,t)	0:u.byte 2:ushort 4:float 1:byte 3:short 5-7 reserved	Location of decimal point from LSB. This shift applies to all u/short components and to u/byte components where ByteDequant is asserted (Below).
93:93	FLAG	ByteDequant	(Rev B Only)	0: Shift does not apply to u/byte 1: Shift does apply to u/byte	Shift applies for u/byte components of position and texture attributes.
94:94	FLAG	NormalIndex3	(Rev B Only)	0: Single index per Normal 1: Triple index per nine-Normal	When nine normals selected in indirect mode, input will be treated as three staggered indices (one per triple biased by component size), into normal table. NOTE!! First index internally biased by 0. Second index internally biased by 1. Third index internally biased by 2.

DEFINING AND DRAWING GRAPHICS PRIMITIVES

FIG. 15 illustrates some of the different types of primitives supported by the graphics system 50, including:

- GX\_POINTS—draws a point at each of the n vertices.
- GX\_LINES—draws a series of unconnected line segments. Segments are drawn between v0 and v1, v2 and v3, etc. The number of vertices drawn should be a multiple of 2.

- GX\_LINESTRIP—draws a series of connected lines, from v0 to v1, then from v1 to v2, and so on. If n vertices are drawn, n-1 lines are drawn.
- GX\_TRIANGLES—draws a series of triangles (three-sided polygons) using vertices v0, v1, v2, then v3, v4, v5, and so on. The number of vertices drawn should be a multiple of 3 and the minimum number is 3.
- GX\_TRIANGLSTRIP—draws a series of triangles (three-sided polygons) using vertices v0, v1, v2, then v1, v3, v2 (note the order), then v2, v3, v4, and so on. The number of vertices must be at least 3.

GX\_TRIANGLEFAN—draws a series of triangles (three-sided polygons) using vertices v0, v1, v2, then v0, v2, v3, and so on. The number of vertices must be at least 3.

GX\_QUADS—draws a series of non-planar quadrilaterals (4-sided polygons) beginning with v0, v1, v2, v3, then v4, v5, v6, v7, and so on. The quad is actually drawn using two triangles, so the four vertices are not required to be coplanar. It is noted that the diagonal common edge between the two triangles of a quad is oriented as shown in FIG. 11. The minimum number of vertices is 4.

The application draws primitives by calling vertex functions (GXPosition, GXColor, etc.) between GXBegin/GXEnd pairs. The application should call a vertex function for each attribute it enables using GXSetVtxDesc(). Each vertex function has a suffix of the form GXData[n][t], which describes the number (n) and type (t) of elements passed to the vertex function.

The following case fragment demonstrates how to draw primitives using vertex functions:

```
GXBegin(GX_TRIANGLES, GX_VTXFMT0, 3);
GXPosition1x8(0); // index to position
GXColor1x16(0); // index to color
GXPosition1x8(1);
GXColor1x16(1);
GXPosition1x8(2);
GXColor1x16(2);
GXEnd();
```

GXBegin specifies the type of primitive, an index into the VAT, and the number of vertices between the GXBegin/GXEnd pair. This information, along with the latest call to GXSetVtxDesc(), fully describes the primitive, vertex, and attribute format. GXEnd() is actually a null macro that can be used to make sure that GXBegin and GXEnd are paired properly.

LOADING A PROJECTION MATRIX

FIG. 16 shows an example binary bit stream used to load a projection matrix into transform unit 300 (see FIG. 8, block 1004). As described above in connection with FIG. 8, the application generally defines a projection matrix in order to transform a primitive from one space into another space (e.g., object space to world space). The transform unit 300 automatically transforms the vertices in the primitive using this projection matrix.

FIG. 16 shows an example binary bit stream that can be used to load a projection matrix into transform unit 300. In the example embodiment, this loading process involves sending a binary bit pattern of "0x10" to the graphics and audio processor 114 indicating "cp<sub>13</sub>cmd<sub>13</sub>xf<sub>13</sub>loadregs" followed by a 4-byte value. In this 4-byte value, the first eleven bits are 0 padding and the succeeding bits indicated a register address within the transform unit 300 (bits 0-15) and the number of 32-bit registers within the transform unit to be loaded (bits 16-19). Following these bit patterns are a sequence of from one to sixteen 32-bit words specifying projection matrix values.

In the example embodiment, every register in the transform unit 300 is mapped to a unique 32b address. All addresses are available to the xform register load command (command 0x30). The first block is formed by the matrix memory. Its address range is 0 to 1k, but only 256 entries are used. This memory is organized in a 64 entry by four 32b words. Each word has a unique address and is a single

precision floating point number. For block writes, the addresses auto increment. The memory is implemented in less than 4-32b rams, then it is possible that the memory writes to this block will require a minimum write size larger than 1 word:

Register Address	Definition	Configuration
0x0000	Matrix Ram word 0	32b matrix data
0x0001-0x00ff	Matrix Ram word (n)	32b matrix data
0x0100-0x03ff	Not used	

The second block of memory is mapped to the 1 k~1.5 k range. This memory is the normal matrix memory. It is organized as 32 rows of 3 words. Each word has a unique address and is a single precision floating point number. Also, each word written is 32b, but only the 20 most significant bits are kept. For simplicity, the minimum granularity of writes will be 3 words:

Register Address	Definition	Configuration
0x0400-0x402	Normal Ram words 0,1,2	20b data
0x0403-0x045f	Normal Ram word (n)	20b data
0x0460-0x05ff	Not used	

The third block of memory holds the dual texture transform matrices. The format is identical to the first block of matrix memory. There are also 64 rows of 4 words for these matrices. These matrices can only be used for the dual transform of regular textures:

Register Address	Definition	Configuration
0x0500	Matrix Ram word 0	32b matrix data
0x0501-0x05ff	Matrix Ram word (n)	32b matrix data

The fourth block of memory is the light memory. This holds all the lighting information (light vectors, light parameters, etc.). Both global state and ambient state are stored in this memory. Each word written is 32b, but only the 20 most significant bits are kept. Each row is 3 words wide. Minimum word write size is 3 words.

EXAMPLE CALL DISPLAY LIST COMMAND

As described in the above-referenced patent application Ser. No. 09/726,215, filed Nov. 28, 2000 (atty. dkt. no. 723-959) entitled "Method and Apparatus for Buffering Graphics Data in a Graphics System", system 50 includes a capability for calling a display list. FIG. 17 shows an example binary bit stream format used to call a display object such as a display list. In the example shown, the binary bit pattern format includes an initial "0x40" indicating "CP<sub>13</sub>CMD<sub>13</sub>CALLOBJECT", followed by a 4-byte address of the display list in memory as well as a 4-byte count or size of the display list. The 4-byte address field may include an initial seven bits of 0 padding followed by a 25-bit value. The 4-byte count value may include an initial seven bits of padding followed by a 25-bit count value indicating the count or size of the display list in 32-byte chunks.

OTHER EXAMPLE COMPATIBLE IMPLEMENTATIONS

Certain of the above-described system components 50 can be implemented as other than the home video game

console configuration described above. For example, one could run graphics application or other software written for system 50 on a platform with a different configuration that emulates system 50 or is otherwise compatible with it. If the other platform can successfully emulate, simulate and/or provide some or all of the hardware and software resources of system 50, then the other platform will be able to successfully execute the software.

As one example, an emulator may provide a hardware and/or software configuration (platform) that is different from the hardware and/or software configuration (platform) of system 50. The emulator system might include software and/or hardware components that emulate or simulate some or all of hardware and/or software components of the system for which the application software was written. For example, the emulator system could comprise a general purpose digital computer such as a personal computer, which executes a software emulator program that simulates the hardware and/or firmware of system 50.

Some general purpose digital computers (e.g., IBM or Macintosh personal computers and compatibles) are now equipped with 3D graphics cards that provide 3D graphics pipelines compliant with DirectX or other standard 3D graphics command APIs. They may also be equipped with stereophonic sound cards that provide high quality stereophonic sound based on a standard set of sound commands. Such multimedia-hardware-equipped personal computers running emulator software may have sufficient performance to approximate the graphics and sound performance of system 50. Emulator software controls the hardware resources on the personal computer platform to simulate the processing, 3D graphics, sound, peripheral and other capabilities of the home video game console platform for which the game programmer wrote the game software.

FIG. 18A illustrates an example overall emulation process using a host platform 1201, an emulator component 1303, and a game software executable binary image provided on a storage medium 62. Host 1201 may be a general or special purpose digital computing device such as, for example, a personal computer, a video game console, or any other platform with sufficient computing power. Emulator 1303 may be software and/or hardware that runs on host platform 1201, and provides a real-time conversion of commands, data and other information from storage medium 62 into a form that can be processed by host 1201. For example, emulator 1303 fetches "source" binary-image program instructions intended for execution by system 50 from storage medium 62 and converts these program instructions to a target format that can be executed or otherwise processed by host 1201.

As one example, in the case where the software is written for execution on a platform using an IBM PowerPC or other specific processor and the host 1201 is a personal computer using a different (e.g., Intel) processor, emulator 1203 fetches one or a sequence of binary-image program instructions from storage medium 1305 and converts these program instructions to one or more equivalent Intel binary-image program instructions. The emulator 1203 also fetches and/or generates graphics commands and audio commands intended for processing by the graphics and audio processor 114, and converts these commands into a format or formats that can be processed by hardware and/or software graphics and audio processing resources available on host 1201. As one example, emulator 1303 may convert these commands into commands that can be processed by specific graphics and/or sound hardware of the host 1201 (e.g., using standard DirectX, OpenGL and/or sound APIs).

An emulator 1303 used to provide some or all of the features of the video game system described above may also be provided with a graphic user interface (GUI) that simplifies or automates the selection of various options and screen modes for games run using the emulator. In one example, such an emulator 1303 may further include enhanced functionality as compared with the host platform for which the software was originally intended.

FIG. 18B illustrates an emulation host system 1201 suitable for use with emulator 1303. System 1201 includes a processing unit 1203 and a system memory 1205. A system bus 1207 couples various system components including system memory 1205 to processing unit 1203. System bus 1207 may be any of several types of bus structures including a memory bus or memory controller, a peripheral bus, and a local bus using any of a variety of bus architectures. System memory 1207 includes read only memory (ROM) 1252 and random access memory (RAM) 1254. A basic input/output system (BIOS) 1256, containing the basic routines that help to transfer information between elements within personal computer system 1201, such as during start-up, is stored in the ROM 1252. System 1201 further includes various drives and associated computer-readable media. A hard disk drive 1209 reads from and writes to a (typically fixed) magnetic hard disk 1211. An additional (possible optional) magnetic disk drive 1213 reads from and writes to a removable "floppy" or other magnetic disk 1215. An optical disk drive 1217 reads from and, in some configurations, writes to a removable optical disk 1219 such as a CD ROM or other optical media. Hard disk drive 1209 and optical disk drive 1217 are connected to system bus 1207 by a hard disk drive interface 1221 and an optical drive interface 1225, respectively. The drives and their associated computer-readable media provide nonvolatile storage of computer-readable instructions, data structures, program modules, game programs and other data for personal computer system 1201. In other configurations, other types of computer-readable media that can store data that is accessible by a computer (e.g., magnetic cassettes, flash memory cards, digital video disks, Bernoulli cartridges, random access memories (RAMs), read only memories (ROMs) and the like) may also be used.

A number of program modules including emulator 1303 may be stored on the hard disk 1211, removable magnetic disk 1215, optical disk 1219 and/or the ROM 1252 and/or the RAM 1254 of system memory 1205. Such program modules may include an operating system providing graphics and sound APIs, one or more application programs, other program modules, program data and game data. A user may enter commands and information into personal computer system 1201 through input devices such as a keyboard 1227, pointing device 1229, microphones, joysticks, game controllers, satellite dishes, scanners, or the like. These and other input devices can be connected to processing unit 1203 through a serial port interface 1231 that is coupled to system bus 1207, but may be connected by other interfaces, such as a parallel port, game port Fire wire bus or a universal serial bus (USB). A monitor 1233 or other type of display device is also connected to system bus 1207 via an interface, such as a video adapter 1235.

System 1201 may also include a modem 1154 or other network interface means for establishing communications over a network 1152 such as the Internet. Modem 1154, which may be internal or external, is connected to system bus 123 via serial port interface 1231. A network interface 1156 may also be provided for allowing system 1201 to communicate with a remote computing device 1150 (e.g.,

another system 1201) via a local area network 1158 (or such communication may be via wide area network 1152 or other communications path such as dial-up or other communications means). System 1201 will typically include other peripheral output devices, such as printers and other standard peripheral devices.

In one example, video adapter 1235 may include a 3D graphics pipeline chip set providing fast 3D graphics rendering in response to 3D graphics commands issued based on a standard 3D graphics application programmer interface such as Microsoft's DirectX 7.0 or other version. A set of stereo loudspeakers 1237 is also connected to system bus 1207 via a sound generating interface such as a conventional "sound card" providing hardware and embedded software support for generating high quality stereophonic sound based on sound commands provided by bus 1207. These hardware capabilities allow system 1201 to provide sufficient graphics and sound speed performance to play software stored in storage medium 1305.

EXAMPLE HIGHER-LEVEL API CELLS

The following show example higher level API cells that a library interprets and/or computes to create the binary level command streams described above:

GXSetCopyClear

Argument:

GXColor	ClearColor;	//Color value to clear the framebuffer to during copy.
u32	ClearZ;	//24 bit Z value to clear the framebuffer to during copy.

This sets the two clear values used for clearing the framebuffer during copy operations.

GXSetVtxDesc

Arguments:

GXAttr	Attr;	//Which attribute (Position, Normal, Color, etc.)
GXAttrType	Type;	//Attribute Type (None, Direct, Indexed, etc.)

This function is used for setting the type of a single attribute in the current vertex descriptor (i.e., vertex attribute register). The vertex attribute register defines which attributes are present in a vertex and how each attribute is referenced.

GXSetVtxAttrFmt

Argument:

GXVtxFmt	vtxfmt;	//Index into the Vertex Attribute Table (0-7).
GXAttr	Attr;	//Attribute Type.
GXCompCnt	CompCnt;	//Number of components for the attribute.
GXCompType	CompType	//Type of each Component.
u8	Shift;	//Locatin of decimal point for fixed point format types.

This function sets the attribute format for a single attribute in the vertex attribute format table (VAT). There are 8 vertex formats in the VAT vertex attribute array. Each register describes the data type and component types of all attributes

that can be used in a vertex packet. The application can preprogram all 8 registers and then select one of them during actual drawing of the geometry.

GXSetArray

Arguments:

GXAttr	Attr;	//Attribute type.
u32	Base;	//Address (25:0) of the attribute data array in main memory.
u8	Stride;	//Number of bytes between successive elements in the attribute array.

This function sets the address and stride of the data array in main memory for each indexed attribute. The system uses these arrays to get actual data when an indexed attribute is sent with a vertex packet.

GXSetProjection

Arguments:

f32	Matrix[4][4]	//Projection matrix.
GXProjMtxType	type;	//Indicates if the projection is orthographic.

Sets projection matrix parameters. The projection matrix is specified as follows:

Perspective Projection:

$$\begin{bmatrix} X \\ Y \\ Z \\ W \end{bmatrix} = \begin{bmatrix} p0 & 0 & p1 & 0 \\ 0 & p2 & p3 & 0 \\ 0 & 0 & p4 & p5 \\ 0 & 0 & -1 & 0 \end{bmatrix} \begin{bmatrix} Xe \\ Ye \\ Ze \\ 1 \end{bmatrix}$$

Orthographic Projection:

$$\begin{bmatrix} X \\ Y \\ Z \\ W \end{bmatrix} = \begin{bmatrix} p0 & 0 & 0 & p1 \\ 0 & p2 & 0 & p3 \\ 0 & 0 & p4 & p5 \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} Xe \\ Ye \\ Ze \\ 1 \end{bmatrix}$$

All documents referred to herein are expressly incorporated by reference as if expressly set forth.

As used herein, the notation "0x" indicates a hexadecimal value. For example, "0x61" indicates a hexadecimal value. For example, "0x61" indicates a two-byte hexadecimal value of "61" —which people of ordinary skill in the art understand has a binary format of "01100001". See Table VI below for conversion of hexadecimal notation to binary notation:

TABLE VI

Hex	Binary
0	0000
1	0001
2	0010
3	0011
4	0100
5	0101
6	0110
7	0111

TABLE VI-continued

Hex	Binary
8	1000
9	1001
A	1010
B	1011
C	1100
D	1101
E	1110
F	1111

While the invention has been described in connection with what is presently considered to be the most practical and preferred embodiment, it is to be understood that the invention is not to be limited to the disclosed embodiment, but on the contrary, is intended to cover various modifications and equivalent arrangements included within the scope of the appended claims.

We claim:

1. A graphics command stream for use in a graphics system, the command stream being operable upon execution to load vertex attribute registers, the graphics command stream comprising:

a graphics command 0x 0870 followed by a 4-byte value including attribute information for position, normal, a first color, a second color, a texture **0** coordinate, and further including a byte dequantization flag and a normal index flag, and

at least one additional stream command defining at least one texture coordinate attribute,

wherein upon execution of the graphics command stream the vertex attribute registers are loaded.

2. A computer readable storage medium encoded with executable instructions for loading vertex attribute registers, comprising:

a graphics command 0x0870 followed by a 4-byte value including attribute information for position, normal, a first color, a second color, a texture **0** coordinate, and further including a byte dequantization flag and a normal index flag, and

at least one additional stream command defining at least one texture coordinate attribute,

wherein execution of the encoded instructions loads the vertex attribute registers.

3. A graphics command stream decoder comprising:

a first decoding section decoding a graphics command 0x0870 followed by a 4-byte value including attribute information for position, normal, a first color, a second color, a texture **0** coordinate, and further including a byte dequantization flag and a normal index flag, and at least one additional decoding section decoding at least one additional stream command defining at least one texture coordinate attribute.

4. A method of loading vertex attribute registers in a graphics system using a graphics command stream, the method comprising:

generating a graphics command 0x0870 followed by a 4-byte value including attribute information for position, normal, a first color, a second color, a texture **0** coordinate, and further including a byte dequantization flag and a normal index flag, and

generating at least one additional stream command defining at least one texture coordinate attribute,

wherein upon execution of the graphics command stream the vertex attribute registers are loaded.

\* \* \* \* \*