



US008098255B2

(12) **United States Patent**
Fouladi et al.

(10) **Patent No.:** **US 8,098,255 B2**
(45) **Date of Patent:** **Jan. 17, 2012**

(54) **GRAPHICS PROCESSING SYSTEM WITH
ENHANCED MEMORY CONTROLLER**

(56) **References Cited**

(75) Inventors: **Farhad Fouladi**, Los Altos Hills, CA
(US); **Winnie W. Yeung**, San Jose, CA
(US); **Howard Cheng**, Sammamish, WA
(US)

(73) Assignee: **Nintendo Co., Ltd.**, Kyoto (JP)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **12/470,712**

(22) Filed: **May 22, 2009**

(65) **Prior Publication Data**
US 2009/0225094 A1 Sep. 10, 2009

Related U.S. Application Data
(62) Division of application No. 09/726,220, filed on Nov.
28, 2000, now Pat. No. 7,538,772.
(60) Provisional application No. 60/226,894, filed on Aug.
23, 2000.

(51) **Int. Cl.**
G09G 5/36 (2006.01)
G06F 13/18 (2006.01)
G06F 13/00 (2006.01)
(52) **U.S. Cl.** **345/558; 345/535; 345/536**
(58) **Field of Classification Search** **345/519,**
345/530, 531, 535, 536, 542, 558, 559; 711/154,
711/158, 167, 137, 5, 113, 106, 100, 163,
711/151, 156, 140, 141; 365/222; 709/235;
710/240, 100, 310, 105, 117

See application file for complete search history.

U.S. PATENT DOCUMENTS

4,275,413	A	6/1981	Sakamoto et al.
4,357,624	A	11/1982	Greenberg
4,388,620	A	6/1983	Sherman
4,425,559	A	1/1984	Sherman
4,463,380	A	7/1984	Hooks, Jr.
4,491,836	A	1/1985	Collmeyer et al.
4,570,233	A	2/1986	Yan et al.

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0 637 813 A2 2/1995

(Continued)

OTHER PUBLICATIONS

"5.13.1 How to Project a Texture," from web site: www.sgi.com, 2
pages.

(Continued)


Primary Examiner — Joni Hsu

(74) *Attorney, Agent, or Firm* — Nixon & Vanderhye P.C.

(57) **ABSTRACT**

A graphics system including a custom graphics and audio processor produces exciting 2D and 3D graphics and surround sound. The system includes a graphics and audio processor including a 3D graphics pipeline and an audio digital signal processor. A memory controller performs a wide range of memory control related functions including arbitrating between various competing resources seeking access to main memory, handling memory latency and bandwidth requirements of the resources requesting memory access, buffering writes to reduce bus turn around, refreshing main memory, and protecting main memory using programmable registers. The memory controller minimizes memory read/write switching using a "global" write queue which queues write requests from various diverse competing resources. In this fashion, multiple competing resources for memory writes are combined into one resource from which write requests are obtained. Memory coherency issues are addressed both within a single resource that has both read and write capabilities and among different resources by efficiently flushing write buffers associated with a resource.

8 Claims, 16 Drawing Sheets



U.S. PATENT DOCUMENTS

4,586,038 A	4/1986	Sims et al.	5,438,663 A	8/1995	Matsumoto et al.
4,600,919 A	7/1986	Stern	5,448,689 A	9/1995	Matsuo et al.
4,615,013 A	9/1986	Yan et al.	5,457,775 A	10/1995	Johnson, Jr. et al.
4,625,289 A	11/1986	Rockwood	5,461,712 A	10/1995	Chelstowski et al.
4,653,012 A	3/1987	Duffy et al.	5,467,438 A	11/1995	Nishio et al.
4,658,247 A	4/1987	Gharachorloo	5,467,459 A	11/1995	Alexander et al.
4,692,880 A	9/1987	Merz et al.	5,469,535 A	11/1995	Jarvis et al.
4,695,943 A	9/1987	Keeley et al.	5,473,736 A	12/1995	Young
4,710,876 A	12/1987	Cline et al.	5,475,803 A	12/1995	Stearns et al.
4,725,831 A	2/1988	Coleman	5,487,146 A	1/1996	Guttag et al.
4,768,148 A	8/1988	Keeley et al.	5,490,240 A	2/1996	Foran et al.
4,785,395 A	11/1988	Keeley	5,495,563 A	2/1996	Winser
4,790,025 A	12/1988	Inoue et al.	5,504,499 A	4/1996	Horie et al.
4,808,988 A	2/1989	Burke et al.	5,504,917 A	4/1996	Austin
4,812,988 A	3/1989	Duthuit et al.	5,506,604 A	4/1996	Nally et al.
4,817,175 A	3/1989	Tenenbaum et al.	5,535,374 A	7/1996	Olive
4,829,295 A	5/1989	Hiroyuki	5,543,824 A	8/1996	Priem et al.
4,829,452 A	5/1989	Kang et al.	5,544,292 A	8/1996	Winser
4,833,601 A	5/1989	Barlow et al.	5,548,709 A	8/1996	Hannah et al.
4,855,934 A	8/1989	Robinson	5,553,228 A	9/1996	Erb et al.
4,862,392 A	8/1989	Steiner	5,557,712 A	9/1996	Guay
4,866,637 A	9/1989	Gonzalez-Lopez et al.	5,559,954 A	9/1996	Sakoda et al.
4,888,712 A	12/1989	Barkans et al.	5,561,746 A	10/1996	Murata et al.
4,897,806 A	1/1990	Cook et al.	5,561,752 A	10/1996	Jevans
4,901,064 A	2/1990	Deering	5,563,989 A	10/1996	Billyard
4,907,174 A	3/1990	Priem	5,566,285 A	10/1996	Okada
4,914,729 A	4/1990	Omori et al.	5,569,935 A	10/1996	Takemura et al.
4,918,625 A	4/1990	Yan	5,573,402 A	11/1996	Gray
4,935,879 A	6/1990	Ueda	5,579,456 A	11/1996	Cosman
4,945,500 A	7/1990	Deering	5,586,234 A	12/1996	Sakuraba et al.
4,965,751 A	10/1990	Thayer et al.	5,593,350 A	1/1997	Bouton et al.
4,974,176 A	11/1990	Buchner et al.	5,594,854 A	1/1997	Baldwin et al.
4,974,177 A	11/1990	Nishiguchi	5,600,763 A	2/1997	Greene et al.
4,975,977 A	12/1990	Kurosu et al.	5,606,650 A	2/1997	Kelley et al.
4,989,138 A	1/1991	Radochonski	5,607,157 A	3/1997	Nagashima
5,003,496 A	3/1991	Hunt, Jr. et al.	5,608,424 A	3/1997	Takahashi et al.
5,016,183 A	5/1991	Shyong	5,608,864 A	3/1997	Bindlish et al.
5,018,076 A	5/1991	Johary et al.	5,616,031 A	4/1997	Logg
5,043,922 A	8/1991	Matsumoto	5,621,867 A	4/1997	Murata et al.
5,056,044 A	10/1991	Frederickson et al.	5,628,686 A	5/1997	Svancarek et al.
5,062,057 A	10/1991	Blacken et al.	5,638,535 A	6/1997	Rosenthal et al.
5,086,495 A	2/1992	Gray et al.	5,644,364 A	7/1997	Kurtze et al.
5,091,967 A	2/1992	Ohsawa	5,649,082 A	7/1997	Burns
5,097,427 A	3/1992	Lathrop et al.	5,650,955 A	7/1997	Puar et al.
5,136,664 A	8/1992	Bersack et al.	5,651,104 A	7/1997	Cosman
5,144,291 A	9/1992	Nishizawa	5,657,045 A	8/1997	Katsura et al.
5,163,126 A	11/1992	Einkauf et al.	5,657,443 A	8/1997	Krech, Jr.
5,170,468 A	12/1992	Shah et al.	5,657,478 A	8/1997	Recker et al.
5,179,638 A	1/1993	Dawson et al.	5,659,671 A	8/1997	Tannenbaum et al.
5,204,944 A	4/1993	Wolberg et al.	5,659,673 A	8/1997	Nonoshita
5,224,208 A	6/1993	Miller, Jr. et al.	5,659,715 A	8/1997	Wu et al.
5,239,624 A	8/1993	Cook et al.	5,661,311 A	8/1997	Takemura et al.
5,241,658 A	8/1993	Masterson et al.	5,664,162 A	9/1997	Dye
5,255,353 A	10/1993	Itoh	5,666,439 A	9/1997	Ishida et al.
5,268,995 A	12/1993	Diefendorff et al.	5,666,494 A	9/1997	Mote, Jr.
5,268,996 A	12/1993	Steiner et al.	5,678,037 A	10/1997	Osugi et al.
5,278,948 A	1/1994	Luken, Jr.	5,682,522 A	10/1997	Huang et al.
5,307,450 A	4/1994	Grosssman	5,684,941 A	11/1997	Dye
5,315,692 A	5/1994	Hansen et al.	5,687,304 A	11/1997	Kiss
5,345,541 A	9/1994	Kelley et al.	5,687,357 A	11/1997	Priem
5,353,424 A	10/1994	Partovi et al.	5,691,746 A	11/1997	Shyu
5,357,579 A	10/1994	Buchner et al.	5,694,143 A	12/1997	Fielder et al.
5,361,386 A	11/1994	Watkins et al.	5,696,892 A	12/1997	Redmann et al.
5,363,475 A	11/1994	Baker et al.	5,701,444 A	12/1997	Baldwin
5,377,313 A	12/1994	Scheibl	5,703,806 A	12/1997	Puar et al.
5,392,385 A	2/1995	Evangelisti et al.	5,706,481 A	1/1998	Hannah et al.
5,392,393 A	2/1995	Deering	5,706,482 A	1/1998	Matsushima et al.
5,394,516 A	2/1995	Winser	5,714,981 A	2/1998	Scott-Jackson et al.
5,402,532 A	3/1995	Epstein et al.	5,721,947 A	2/1998	Priem et al.
5,404,445 A	4/1995	Matsumoto	5,724,561 A	3/1998	Tarolli et al.
5,408,650 A	4/1995	Arsenault	5,726,689 A	3/1998	Negishi et al.
5,412,796 A	5/1995	Olive	5,726,947 A	3/1998	Yamazaki et al.
5,415,549 A	5/1995	Logg	5,727,192 A	3/1998	Baldwin
5,416,606 A	5/1995	Katayama et al.	5,734,386 A	3/1998	Cosman
5,421,028 A	5/1995	Swanson	5,739,819 A	4/1998	Bar-Nahum
5,422,997 A	6/1995	Nagashima	5,740,343 A	4/1998	Tarolli et al.
5,432,895 A	7/1995	Myers	5,740,383 A	4/1998	Nally et al.
5,432,900 A	7/1995	Rhodes et al.	5,740,406 A	4/1998	Rosenthal et al.
			5,742,749 A	4/1998	Foran et al.

5,742,788 A	4/1998	Priem et al.	5,894,300 A	4/1999	Takizawa
5,745,118 A	4/1998	Alcorn et al.	5,900,881 A	5/1999	Ikedo
5,745,125 A	4/1998	Deering et al.	5,903,283 A	5/1999	Selwan et al.
5,748,199 A	5/1998	Palm	5,909,218 A	6/1999	Naka et al.
5,748,986 A	5/1998	Butterfield et al.	5,909,225 A	6/1999	Schinnerer et al.
5,751,291 A	5/1998	Olsen et al.	5,912,675 A	6/1999	Laperriere
5,751,292 A	5/1998	Emmot	5,912,676 A	6/1999	Malladi et al.
5,751,295 A	5/1998	Becklund et al.	5,914,721 A	6/1999	Lim
5,751,930 A	5/1998	Katsura et al.	5,914,725 A	6/1999	Mcinnnis et al.
5,754,191 A	5/1998	Mills et al.	5,914,729 A	6/1999	Lippincott
5,757,382 A	5/1998	Lee	5,917,496 A	6/1999	Fujita et al.
5,758,182 A	5/1998	Rosenthal et al.	5,920,326 A	7/1999	Rentschler et al.
5,760,783 A	6/1998	Migdal et al.	5,920,876 A	7/1999	Ungar et al.
5,764,228 A	6/1998	Baldwin	5,923,332 A	7/1999	Izawa
5,764,237 A	6/1998	Kaneko	5,923,334 A	7/1999	Luken
5,767,856 A	6/1998	Peterson et al.	5,926,182 A	7/1999	Menon et al.
5,767,858 A	6/1998	Kawase et al.	5,926,647 A	7/1999	Adams et al.
5,768,626 A	6/1998	Munson et al.	5,933,150 A	8/1999	Ngo et al.
5,768,629 A	6/1998	Wise et al.	5,933,154 A	8/1999	Howard et al.
5,774,133 A	6/1998	Neave et al.	5,933,155 A	8/1999	Akeley
5,777,623 A	7/1998	Small	5,933,529 A	8/1999	Kim
5,777,629 A	7/1998	Baldwin	5,936,641 A	8/1999	Jain et al.
5,781,927 A	7/1998	Wu et al.	5,936,683 A	8/1999	Lin
5,791,994 A	8/1998	Hirano et al.	5,940,086 A	8/1999	Rentschler et al.
5,798,770 A	8/1998	Baldwin	5,940,089 A	8/1999	Dilliplane
5,801,706 A	9/1998	Fujita et al.	5,940,538 A	8/1999	Spiegel et al.
5,801,711 A	9/1998	Koss et al.	5,943,058 A	8/1999	Nagy
5,801,716 A	9/1998	Silverbrook	5,943,060 A	8/1999	Cosman et al.
5,801,720 A	9/1998	Norrod et al.	5,945,997 A	8/1999	Zhao et al.
5,805,175 A	9/1998	Priem	5,949,421 A	9/1999	Ogletree et al.
5,805,868 A	9/1998	Murphy	5,949,423 A	9/1999	Olsen
5,808,619 A	9/1998	Choi et al.	5,949,428 A	9/1999	Toelle et al.
5,808,630 A	9/1998	Pannell	5,949,440 A	9/1999	Krech, Jr. et al.
5,809,219 A	9/1998	Pearce et al.	5,956,042 A	9/1999	Tucker et al.
5,809,278 A	9/1998	Watanabe et al.	5,956,043 A	9/1999	Jensen
5,815,165 A	9/1998	Blixt	5,958,020 A	9/1999	Evoy et al.
5,815,166 A	9/1998	Baldwin	5,959,640 A	9/1999	Rudin et al.
5,818,456 A	10/1998	Cosman et al.	5,963,220 A	10/1999	Lee et al.
5,819,017 A	10/1998	Akeley et al.	5,966,134 A	10/1999	Arias
5,821,940 A	10/1998	Morgan et al.	5,969,726 A	10/1999	Rentschler et al.
5,821,949 A	10/1998	Deering	5,977,979 A	11/1999	Clough et al.
5,822,516 A	10/1998	Krech, Jr.	5,977,984 A	11/1999	Omori
5,828,382 A	10/1998	Wilde	5,982,376 A	11/1999	Abe et al.
5,828,383 A	10/1998	May et al.	5,982,390 A	11/1999	Stoneking et al.
5,828,416 A *	10/1998	Ryan 348/512	5,986,286 A	11/1999	Yamazaki et al.
5,828,907 A	10/1998	Wise et al.	5,986,659 A	11/1999	Gallery et al.
5,831,624 A	11/1998	Tarolli et al.	5,986,663 A	11/1999	Wilde
5,831,625 A	11/1998	Rich et al.	5,986,677 A	11/1999	Jones et al.
5,831,640 A	11/1998	Wang et al.	5,987,567 A	11/1999	Rivard et al.
5,835,096 A	11/1998	Baldwin	5,990,903 A	11/1999	Donovan
5,835,792 A	11/1998	Wise et al.	5,995,120 A	11/1999	Dye
5,838,334 A	11/1998	Dye	5,995,121 A	11/1999	Alcokrn et al.
5,844,576 A	12/1998	Wilde et al.	5,999,189 A	12/1999	Kajiya et al.
5,850,229 A	12/1998	Edelsbrunner et al.	5,999,196 A	12/1999	Storm et al.
5,852,451 A	12/1998	Cox et al.	5,999,198 A	12/1999	Horan et al.
5,856,829 A	1/1999	Gray, III et al.	6,002,407 A	12/1999	Fadden
5,859,645 A	1/1999	Latham	6,002,410 A	12/1999	Battle
5,861,888 A	1/1999	Dempsey	6,005,582 A	12/1999	Gabriel et al.
5,861,893 A	1/1999	Strugess	6,005,583 A	12/1999	Morrison
5,867,166 A	2/1999	Myhrvold et al.	6,005,584 A	12/1999	Kitamura et al.
5,870,097 A	2/1999	Snyder et al.	6,007,428 A	12/1999	Nishiumi et al.
5,870,098 A	2/1999	Gardiner	6,008,820 A	12/1999	Chauvin
5,870,102 A	2/1999	Tarolli et al.	6,010,924 A	1/2000	Takemura et al.
5,870,109 A	2/1999	McCormack et al.	6,011,562 A	1/2000	Gagne et al.
5,870,587 A	2/1999	Danforth et al.	6,011,565 A	1/2000	Kuo et al.
5,872,902 A	2/1999	Kuchkuda et al.	6,014,144 A	1/2000	Nelson et al.
5,874,969 A	2/1999	Storm et al.	6,016,150 A	1/2000	Lengyel et al.
5,877,741 A	3/1999	Chee et al.	6,016,151 A	1/2000	Lin
5,877,770 A	3/1999	Hanaoka	6,018,350 A	1/2000	Lee et al.
5,877,771 A	3/1999	Drebin et al.	6,020,931 A	2/2000	Bilbrey et al.
5,880,736 A	3/1999	Peercy et al.	6,021,417 A	2/2000	Massarksy
5,880,737 A	3/1999	Griffen et al.	6,022,274 A	2/2000	Takeda et al.
5,883,638 A	3/1999	Rouet et al.	6,023,261 A	2/2000	Ugajin
5,886,701 A	3/1999	Chauvin et al.	6,023,738 A	2/2000	Priem et al.
5,886,705 A	3/1999	Lentz	6,025,853 A	2/2000	Baldwin
5,887,155 A	3/1999	Laidig	6,026,182 A	2/2000	Lee et al.
5,890,190 A	3/1999	Rutman	6,028,608 A	2/2000	Jenkins
5,892,517 A	4/1999	Rich	6,028,611 A	2/2000	Anderson et al.
5,892,974 A	4/1999	Koizumi et al.	6,031,542 A	2/2000	Wittig

6,035,360 A	3/2000	Doidge et al.	6,215,497 B1	4/2001	Leung
6,037,948 A	3/2000	Liepa	6,226,012 B1	5/2001	Priem et al.
6,037,949 A	3/2000	DeRose et al.	6,226,713 B1	5/2001	Mehrotra
6,038,031 A	3/2000	Murphy	6,232,981 B1	5/2001	Gossett
6,038,348 A	3/2000	Carley	6,236,413 B1	5/2001	Gossett et al.
6,040,843 A	3/2000	Monroe et al.	6,239,810 B1	5/2001	Van Hook et al.
6,040,844 A	3/2000	Yamaguchi et al.	6,252,608 B1	6/2001	Snyder et al.
6,041,010 A	3/2000	Puar et al.	6,252,610 B1	6/2001	Hussain
6,043,804 A	3/2000	Greene	6,264,558 B1	7/2001	Nishiumi et al.
6,043,821 A	3/2000	Sprague et al.	6,268,861 B1	7/2001	Sanz-Pastor et al.
6,046,746 A	4/2000	Deering	6,275,235 B1	8/2001	Morgan, III
6,046,747 A	4/2000	Saunders et al.	6,285,779 B1	9/2001	Lapidous et al.
6,046,752 A	4/2000	Kirkland et al.	6,292,194 B1	9/2001	Powell, III
6,049,337 A	4/2000	Van Overveld	6,329,997 B1	12/2001	Wu et al.
6,049,338 A	4/2000	Anderson et al.	6,330,647 B1 *	12/2001	Jeddeloh et al. 711/158
6,052,125 A	4/2000	Gardiner et al.	6,331,856 B1	12/2001	Van Hook et al.
6,052,126 A	4/2000	Sakuraba et al.	6,339,428 B1	1/2002	Fowler et al.
6,052,127 A	4/2000	Vaswani et al.	6,342,892 B1	1/2002	Van Hook et al.
6,052,129 A	4/2000	Fowler et al.	6,348,368 B1	2/2002	Yamazaki et al.
6,052,133 A	4/2000	Kang	6,353,438 B1	3/2002	Van Hook
6,054,993 A	4/2000	Devic et al.	6,356,497 B1	3/2002	Puar et al.
6,054,999 A	4/2000	Strandberg	6,408,362 B1	6/2002	Arimilli et al.
6,057,847 A	5/2000	Jenkins	6,417,858 B1	7/2002	Bosch et al.
6,057,849 A	5/2000	Haubner et al.	6,426,747 B1	7/2002	Hoppe et al.
6,057,851 A	5/2000	Luken et al.	6,437,781 B1	8/2002	Tucker et al.
6,057,852 A	5/2000	Krech, Jr.	6,452,600 B1	9/2002	Parikh et al.
6,057,859 A	5/2000	Handelman et al.	6,459,429 B1	10/2002	Deering
6,057,861 A	5/2000	Lee et al.	6,466,223 B1	10/2002	Dorbie et al.
6,057,862 A	5/2000	Margulis	6,469,707 B1	10/2002	Voorhies
6,057,863 A	5/2000	Olarig	6,476,808 B1	11/2002	Kuo et al.
6,061,462 A	5/2000	Tostevin et al.	6,476,822 B1	11/2002	Burbank
6,064,392 A	5/2000	Rohner	6,496,187 B1	12/2002	Deering et al.
6,067,098 A	5/2000	Dye	6,501,479 B1	12/2002	Root et al.
6,070,204 A	5/2000	Poisner	6,564,304 B1	5/2003	Van Hook et al.
6,072,496 A	6/2000	Guenther et al.	6,580,430 B1	6/2003	Hollis et al.
6,075,543 A	6/2000	Akeley	6,606,689 B1	8/2003	Cheng et al.
6,075,546 A	6/2000	Hussain et al.	6,609,977 B1	8/2003	Shimizu et al.
6,078,311 A	6/2000	Pelkey	6,618,048 B1	9/2003	Leather
6,078,333 A	6/2000	Wittig et al.	6,636,214 B1	10/2003	Leather et al.
6,078,334 A	6/2000	Hanaoka et al.	6,639,595 B1	10/2003	Drebin et al.
6,078,338 A	6/2000	Horan et al.	6,664,958 B1	12/2003	Leather et al.
6,081,274 A	6/2000	Shiraishi	6,664,962 B1	12/2003	Komsthoef et al.
6,088,035 A	7/2000	Sudarsky et al.	6,700,586 B1	3/2004	Demers
6,088,042 A	7/2000	Handelman et al.	6,707,458 B1	3/2004	Leather et al.
6,088,487 A	7/2000	Kurashige	6,717,577 B1	4/2004	Cheng et al.
6,088,701 A	7/2000	Whaley et al.	6,811,489 B1	11/2004	Shimizu et al.
6,091,431 A	7/2000	Saxena et al.	6,825,072 B2	11/2004	Yamazaki et al.
6,092,124 A	7/2000	Priem et al.	6,825,851 B1	11/2004	Leather
6,092,158 A *	7/2000	Harriman et al. 711/151	6,867,781 B1	3/2005	Van Hook et al.
6,094,200 A	7/2000	Olsen et al.	6,937,245 B1	8/2005	Van Hook et al.
6,097,435 A	8/2000	Stanger et al.	6,980,218 B1	12/2005	Demers et al.
6,097,437 A	8/2000	Hwang	6,999,100 B1	2/2006	Leather et al.
6,104,415 A	8/2000	Gossett	7,002,591 B1	2/2006	Leather et al.
6,104,417 A	8/2000	Nielsen et al.	7,034,828 B1	4/2006	Drebin et al.
6,105,094 A	8/2000	Lindeman	7,061,502 B1	6/2006	Law et al.
6,108,743 A	8/2000	Debs et al.	7,119,813 B1	10/2006	Hollis et al.
6,111,582 A	8/2000	Jenkins	7,184,059 B1	2/2007	Fouladi et al.
6,111,584 A	8/2000	Murphy	7,196,710 B1	3/2007	Fouladi et al.
6,115,047 A	9/2000	Deering			
6,115,049 A	9/2000	Winner et al.			
6,118,462 A	9/2000	Margulis			
6,128,026 A	10/2000	Brothers, III	EP	1 074 945	2/2001
6,144,365 A	11/2000	Young et al.	EP	1 075 146	2/2001
6,144,387 A	11/2000	Liu et al.	EP	1 081 649	3/2001
6,151,602 A	11/2000	Hejlsberg et al.	JP	07-066424	3/1995
6,154,600 A *	11/2000	Newman et al. 386/4	JP	08-022954	1/1996
6,155,926 A	12/2000	Miyamoto et al.	JP	08-204206	8/1996
6,157,387 A	12/2000	Kotani	JP	9-330230	12/1997
6,166,748 A	12/2000	Van Hook et al.	JP	11-053580	2/1999
6,172,678 B1	1/2001	Shiraishi	JP	11-076614	3/1999
6,173,367 B1	1/2001	Aleksic et al.	JP	11-161819	6/1999
6,177,944 B1	1/2001	Fowler et al.	JP	11-191628	7/1999
6,181,352 B1	1/2001	Kirk et al.	JP	11-203500	7/1999
6,191,794 B1	2/2001	Priem et al.	JP	11-226257	8/1999
6,198,488 B1	3/2001	Lindholm et al.	JP	11-259671	9/1999
6,200,253 B1	3/2001	Nishiumi et al.	JP	11-259678	9/1999
6,202,101 B1 *	3/2001	Chin et al. 710/5	JP	2000-66985	3/2000
6,204,851 B1	3/2001	Netschke et al.	JP	2000-92390	3/2000
6,215,496 B1	4/2001	Szeliski et al.	JP	2000-132704	5/2000
			JP	2000-132706	5/2000

FOREIGN PATENT DOCUMENTS

JP	2000-149053	5/2000
JP	2000-156875	6/2000
JP	2000-182077	6/2000
JP	2000-207582	7/2000
JP	2000-215325	8/2000
WO	93/04429	3/1993
WO	94/10641	5/1994

OTHER PUBLICATIONS

10.2 Alpha Blending, <http://www.sgi.com/software/opengl/advanced98/notes/node146.html>.

10.3 Sorting, <http://www.sgi.com/software/opengl/advanced98/notes/node147.html>.

10.4 Using the Alpha Function, <http://www.sgi.com/software/opengl/advanced98/notes/node148.html>.

2D/3D Graphics Card User Manual, Guillemot, Copyright 1999.

A Microprocessor With a 128b CPU, 10 Floating-Point MAC's, 4 Floating-Point Dividers, and an MPEG2 Decoder, 1999 IEEE International Solid-State Circuits Conference, Feb. 16, 1999.

Akeley, Kurt, "Reality Engine Graphics", 1993, Silicon Graphics Computer Systems, pp. 109-116.

Alpha (transparency) Effects, Future Technology Research Index, <http://www.futuretech.vuurwerk.nl/alpha.html>.

AM News: Japanese Developers Not All Sold on PS2, Next Generation, Mar. 16, 1999.

Arkin, Alan, email, subject: "Texture distortion problem," from web site: <http://reality.sgi.com> (Jul. 1997).

ATI Radeon 64 Meg DDR OEM, Aug. 19, 2000, www.hexus.net.

Blinn, James F., "Simulation of Wrinkled Surfaces," Caltech/JPL, pp. 286-292, SIGGRAPH 78 (1978).

Blythe, David, 5.6 Transparency Mapping and Trimming with Alpha, <http://toolbox.sgi.com/TasteOfDT/d...penGL/advanced98/notes/node41.html>, Jun. 11, 1998.

Bushnell, et al. "Advanced Multitexture Effects With Direct3D and OpenGL", Pyramid Peak Design & ATI Research, Inc., Game Developers Conference, .COPYRGT. 1999.

Cambridge Animo—Scene III, info sheet, Cambridge Animation Systems, 2 pages, <http://www.cam-ani.co.uk/casweb/products/software/SceneIII.htm>.

"Cartoon Shading, Using Shading Mapping," 1 page, <http://www.goat.com/alias/shaders.html#toonshad>.

Charla, Chris, "Play Station II: The Latest News", Next Generation, Sep. 1999.

Computer Graphics World, Dec. 1997.

Cook, Robert L., "Shade Trees", Computer Graphics, vol. 18, No. 3, Jul. 1984.

Datasheet, SGS-Thomson Microelectronics, nVIDIA™, RIVA 128™ 128-Bit 3D Multimedia Accelerator (Oct. 1997).

Debevec, Paul, et al., "Efficient View-Dependent Image-Based Rendering with Projective Texture-Mapping," University of California at Berkeley.

Decaudin, Philippe, "Cartoon-Looking Rendering of 3D Scenes," Syntim Project Inria, 6 pages, <http://www-syntim.inria.fr/syntim/recherche/decaudin/cartoon-eng.html>.

"Developer Relations, ATI Summer 2000 Developer Newsletter," from ATI.com web site, 5 pages (Summer 2000).

"Developer's Lair, Multitexturing with the ATI Rage Pro," (7 pages) from ati.com web site (2000).

"DexDrive Bridges Gap", The Tampa Tribune, Mar. 12, 1999.

Digimation Inc., "The Incredible Comicshop," info sheet, 2 pages, http://www.digimation.com/asp/product.asp?product_id=33.

DirectX 7.0 Programmer's Reference, Microsoft Corporation, 1995-1999 (as part of the DirectX 7.0 SDK on the Companion CD included with "Inside Direct3D", Microsoft Programming Series, Peter J. Kovach, Microsoft Press, 1999).

Dreamcast Instruction Manual, Sega Enterprises, Ltd., .COPYRGT. 1998.

"Dreamcast: The Full Story", Next Generation, Sep. 1998.

Duke, "Dreamcast Technical Specs", Sega Dreamcast Review, Sega, Feb. 1999, www.game-revolution.com.

Easley, Joel, "PlayStation II Revealed", Game Week, Sep. 29, 1999.

Efficient Command/Data Interface Protocol for Graphics, IBM TDB, vol. 36, issue 9A, Sep. 1, 1993, pp. 307-312.

Elber, Gershon, "Line Art Illustrations of Parametric and Implicit Forms," IEEE Transactions on Visualization and Computer Graphics, vol. 4, No. 1, Jan.-Mar. 1998.

Feth, Bill, "Non-Photorealistic Rendering," wif3@cornell.edu, CS490—Bruce Land, 5 pages (Spring 1998).

"First PlayStation II Gameplay Screens Revealed!", Next Generation, Sep. 1999.

Foley, van Dam, Fiener, Hughes, Addison Wesley, "Computer Graphics, Principles and Practice," Second Edition, The Systems Programming Series, 1990.

Game Enthusiast Online Highlights, Mar. 17, 1999.

Game Enthusiast Online Highlights, Mar. 18, 1999.

Game Enthusiast Online Highlights, Mar. 19, 1999.

Game Enthusiast Online Highlights, Oct. 20, 1999.

GDC 2000: Advanced OpenGL Game Development, "A Practical and Robust Bump-mapping Technique for Today's GPUs," by Mark Kilgard, Jul. 5, 2000, www.nvidia.com.

Gibson, Simon, et al., "Interactive Rendering with Real-World Illumination," Rendering Techniques 2000; 11th Eurographics Workshop on Rendering, pp. 365-376 (Jun. 2000).

Gustavo Oliveira, "Refractive Texture Mappig, Part One", www.gamasutra.com, Nov. 10, 2000.

Hachigian, Jennifer, "Super Cel Shader 1.00 Tips and Tricks," 2 pages, [wysiwyg://thePage.13/http://members.xoom.com/.sub.—XMCM.jarvia/3D/celsha-de.html](http://members.xoom.com/.sub.—XMCM.jarvia/3D/celsha-de.html).

Haerberli, Paul et al., "Texture Mapping as a Fundamental Drawing Primitive," Proceedings of the Fourth Eurographics Workshop on Rendering, 11 pages, Paris, France (Jun. 1993).

"Hardware Technology," from ATI.com web site, 8 pages (2000).

Hart, Evan et al., "Graphics by rage," Game Developers Conference 2000, from ATI.com web site (2000).

Hart, Evan et al., "Vertex Shading with Direct3D and OpenGL," Game Developers Conference 2001, from ATI.com web site (2001).

Heidrich et al., "Applications of Pixel Textures in Visualization and Realistic Image Synthesis," Proceedings 1999 Symposium on Interactive 3D Graphics, pp. 127-134 (Apr. 1999).

Hook, Brian, "An Incomplete Guide to Programming DirectDraw and Direct3D Immediate Mode (Release 0.46)," printed from web site: www.wksoftware.com, 42 pages.

Hoppe, Hugues, "Optimization of Mesh Locality for Transparent Vertex Caching," Proceedings of SIGGRAPH, pp. 269-276 (Aug. 8-13, 1999).

Hourcade et al., "Algorithms for Antialiased Cast Shadows", Computers and Graphics, vol. 9, No. 3, pp. 259-265 (1985).

"HOWTO: Animate Textures in Direct3D Immediate Mode," printed from web site support.microsoft.com, 3 pages (last reviewed Dec. 15, 2000).

INFO: Rendering a Triangle Using an Execute Buffer, printed from web site support.microsoft.com, 6 pages (last reviewed Oct. 20, 2000).

Inside Sony's Next Generation Playstation, .COPYRGT. 1999.

Introducing The Next Generation PlayStation, Sony Computer Entertainment Inc., .COPYRGT. 1999.

Johnston, Chris, "PlayStation Part Deux", Press Start, .COPYRGT. 1999.

Kovach, Peter J., "Inside Direct3D", Microsoft Programming Series, Microsoft Press, 1999.

Kovach, Peter J., INSIDE DIRECT 3D, "Alpha Testing," pp. 289-291 (1999).

Leadtek GTS, Aug. 3, 2000, www.hexus.net.

MacWeek.Com Gets Inside Story on Connectix VGS for Windows; Controversial Emulator of Sony PlayStation Games Currently Available for Macs Only, Business Wire, Mar. 12, 1999.

Markosian, Lee et al., "Real-Time Nonphotorealistic Rendering," Brown University site of the NSF Science and Technology Center for Computer Graphics and Scientific Visualization, Providence, RI, 5 pages (undated).


Marlin Rowley, "GeForce 1 & 2 GPU Speed Tests", May 11, 2000, www.g256.com.

McCool, Michael, "Shadow Volume Reconstruction from Depth Maps", ACM Transactions on Graphics, vol. 19, No. 1, Jan. 2000, pp. 1-26.

- Microsoft Xbox—The Future of Gaming, Microsoft Xbox Performance Sheet, www.xbox.com.
- Mitchell et al., "Multitexturing in DirectX6", Game Developer, Sep. 1998, www.gdmag.com.
- Moller, Tomas et al., "Real-Time Rendering," pp. 179-183 (AK Peters Ltd., 1999).
- Mulligan, Vikram, "Toon," info sheet, 2 pages, <http://digitalcarversguild.com/products/toon/toon.html>.
- Nelson, Randy, "Dreamcast 101: Everything You Ever Wanted to Know About Sega's Powerful New Console", Official Sega Dreamcast Magazine, Jun. 1999.
- Nieder, Jackie, David, Tom, Woo, Mason, "OpenGL Programming Guide, The Official Guide to Learning OpenGL, Release 1," Addison-Wesley Publishing Co., 1993.
- Nikkei Shimbun, "Sony Making SME, Chemical and SPT into Wholly-Owned Subsidiaries", Mar. 9, 1999.
- Nintendo 64 Instruction Booklet, Nintendo of America, 1998.
- NVIDIA Product Overview, "GeForce2Ultra", NVIDIA Corporation, Aug. 21, 2000, www.nvidia.com.
- NVIDIA.com, technical presentation, "Advanced Pixel Shader Details" (Nov. 10, 2000).
- NVIDIA.com, technical presentation, "AGDC Per-Pixel Shading" (Nov. 15, 2000).
- NVIDIA.com, technical presentation, Introduction to DX8 Pixel Shaders (Nov. 10, 2000).
- "OpenGL Projected Textures," from web site: [HTTP:// reality.sgi.com](http://reality.sgi.com), 5 pages.
- O'Rourke, Michael, "Principles of Three-Dimensional Computer Animation", Revised Edition, W.W. Norton & Company, 1998.
- Peercy et al., "Efficient Bump Mapping Hardware", Computer Graphics Proceedings, Annual Conference Series, 1997.
- Pescovitz, David, "Dream on", Wired, Aug. 1999.
- Photograph of Nintendo 64 System.
- Photograph of Sega Dreamcast System.
- Photograph of Sony PlayStation II System.
- PlayStation II: Hardware Heaven or Hell?, Next Generation, Jan. 2000.
- Press Releases, "ATI's RADEON family of products delivers the most comprehensive support for the advance graphics features of DirectX 8.0," Canada, from ATI.com web site, 2 pages (Nov. 9, 2000).
- Press Releases, Mar. 18, 1999.
- Product Presentation, "RIVA128™Leadership 3D Acceleration," 2 pages.
- Raskar, Ramesh et al., "Image Precision Silhouette Edges," Symposium on Interactive 3D Graphics1999, Atlanta, 7 pages (Apr. 26-29, 1999).
- Render Man Artist Tools, Using Arbitrary Output Variables in Photorealistic Renderman (With Applications), PhotoRealistic Renderman Application Note #24, 8 pages, Jun. 1998, <http://www.pixar.com/products/renderman/toolkit/Toolkit/AppNotes/appnote.24.html>.
- "Renderman Artist Tools, PhotoRealistic RenderMan Tutorial," Pixar (Jan. 1996).
- RenderMan Artist Tools, PhotoRealistic RenderMan 3.8 User's Manual, Pixar (Aug. 1998).
- Reynolds, Craig, "Stylized Depiction in Computer Graphics, Non-Photorealistic, Painterly and 'Toon Rendering," an annotated survey of online resources, 13 pages, last update May 30, 2000, <http://www.red.com/cwr/painterly.html>.
- Rogers, David F., "Procedural Elements for Computer Graphics," Second Edition, McGraw Hill, 1998.
- Schlag, John, Fast Embossing Effects on Raster Image Data, Graphics Gems IV, Edited by Paul S. Heckbert, Computer Science Department, Carnegie Mellon University, Academic Press, Inc., 1994, pp. 433-437.
- Schlechtweg, Stefan et al., "Emphasising in Line-drawings," Norsk samarbeid innen grafisk databehandling: NORSIGD Info, medlemsblad for NORSIGD, Nr 1/95, pp. 9-10.
- Schlechtweg, Stefan et al., Rendering Line-Drawings with Limited Resources, Proceedings of GRAPHICON '96, 6th International Conference and Exhibition on Computer Graphics and Visualization in Russia, (St. Petersburg, Jul. 1-5, 1996) vol. 2, pp. 131-137.
- Search Results for: skinning, from ATI.com web site, 5 pages (May 24, 2001).
- "Sega to Launch Video Camera for Dreamcast", Reuters Business News, Feb. 16, 2000.
- Segal, Mark, et al., "Fast Shadows and Lighting Effects Using Texture Mapping," Computer Graphics, 26, 2, pp. 249-252 (Jul. 1992).
- Shade, Jonathan et al., "Layered Depth Images," Computer Graphics Proceedings, Annual Conference Series, pp. 231-242 (1998).
- Shaders, Toony, "Dang I'm tired of photorealism," 4 pages, <http://www.visi.com/~mcdonald/toony.html>.
- Sheff, David, "Sony Smackage: Test Driving the PlayStation II", Wired, Nov. 1999.
- Singh, Karan et al., "Skinning Characters using Surface-Oriented Free-Form Deformations," Toronto Canada.
- "Skeletal Animation and Skinning," from ATI.com web site, 2 pages (Summer 2000).
- Slide Presentation, Sébastien Dominé, "nVIDIA Mesh Skinning, OpenGL".
- Softimage/3D Full Support, "Toon Assistant," 1998 Avid Technology, Inc., 1 page, http://www.softimage.com/3dsupport/techn...uments/3.8/features3.8/rel_notes.56.html.
- Sony PlayStation II Instruction Manual, Sony Computer Entertainment Inc., COPYRIGHT. 2000.
- Sony to Turn PlayStation Maker Into Wholly Owned Unit-Nikkei, Dow Jones News Service, Mar. 8, 1999.
- Stand and Be Judged, Next Generation, May 2000.
- Steven Levy, "Here Comes PlayStation II", Newsweek, Mar. 6, 2000.
- Technical Brief: Transform and Lighting, Nov. 10, 1999, www.nvidia.com.
- Technical Brief: What's New With Microsoft DirectX7, posted Nov. 10, 1999, www.nvidia.com.
- Technical Presentation: Computations for Hardware Lighting and Shading, Mar. 17, 2000, www.nvidia.com.
- Technical Presentation: D3D 7 Vertex Lighting, Mar. 15, 2000, www.nvidia.com.
- Technical Presentation: DirectX 7 and Texture Management, Nov. 12, 1999 www.nvidia.com.
- Technical Presentation: Dot Product Lighting, Nov. 12, 1999, www.nvidia.com.
- Technical Presentation: Emboss Bump Mapping, Nov. 3, 1999, www.nvidia.com.
- Technical Presentation: GeForce 256 and RIVA TNT Combiners, Dec. 8, 1999, www.nvidia.com.
- Technical Presentation: GeForce 256 Overview, Nov. 12, 1999, www.nvidia.com.
- Technical Presentation: GeForce 256 Register Combiners, Mar. 17, 2000, www.nvidia.com.
- Technical Presentation: Guard Band Clipping, Nov. 3, 1999, www.nvidia.com.
- Technical Presentation: Hardware Accelerated Anisotropic Lighting, Nov. 3, 1999 www.nvidia.com.
- Technical Presentation: Hardware Bump-mapping Choices and Concepts, Jun. 7, 2000, www.nvidia.com.
- Technical Presentation: Hardware Transform and Lighting, Nov. 12, 1999, www.nvidia.com.
- Technical Presentation: Hardware Transform and Lighting, www.nvidia.com, posted Jun. 12, 2000.
- Technical Presentation: How to Bump Map a Skinned Polygonal Model, Jun. 7, 2000, www.nvidia.com.
- Technical Presentation: Multitexture Combiners, Nov. 3, 1999, www.nvidia.com.
- Technical Presentation: Per-Pixel Lighting (by S. Dietrich) Mar. 14, 2000 www.nvidia.com.
- Technical Presentation: Phong Shading and Lightmaps, Nov. 3, 1999, www.nvidia.com.
- Technical Presentation: Practical Bump-mapping for Today's GPUs, Mar. 17, 2000 www.nvidia.com.
- Technical Presentation: Shadows, Transparency, & Fog, Mar. 17, 2000 www.nvidia.com.
- Technical Presentation: TexGen & the Texture Matrix, Mar. 15, 2000 www.nvidia.com.
- Technical Presentation: Texture Coordinate Generation, Nov. 3, 1999, www.nvidia.com.

- Technical Presentation: The ARB.sub.—multitexture Extension, Nov. 3, 1999 www.nvidia.com.
- Technical Presentation: Toon Shading, Mar. 15, 2000, www.nvidia.com.
- Technical Presentation: Vertex Blending, Nov. 12, 1999, www.nvidia.com.
- Technical Presentation: Vertex Buffers, posted Jun. 12, 2000, www.nvidia.com.
- Technical Presentation: Vertex Cache Optimization, Nov. 12, 1999, www.nvidia.com.
- Technical Presentations: "Texture Space Bump Mapping," Sim Dietrich, Nov. 10, 2000, www.nvidia.com.
- The RenderMan Interface Version 3.1, (Sep. 1989).
- The RenderMan Interface, Stephan R. Keith, Version 3.1, Pixar Animation Studios, Sep. 1989.
- The RenderMan Interface, Version 3.2, Pixar Animation Studios, Jul. 2000, www.pixar.com.
- Thomas Moller and Eric Haines "Real-Time Rendering", AK Peters, Ltd., .COPYRGT. 1999, pp. 127-142.
- Thompson, Nigel, "Rendering with Immediate Mode," Microsoft Interactive Developer Column: Fun and Games, printed from web site msdn.microsoft.com, 8 pages (Mar. 1997).
- Thompson, Tom, "Must-See 3-D Engines," Byte Magazine, printed from web site www.byte.com, 10 pages (Jun. 1996).
- Videum Conference Pro (PCI) Specification, product of Winnov (Winnov), published Jul. 21, 1999.
- VIDI Presenter 3D Repository, "Shaders." 2 pages, <http://www.webnation.com/vidirep/panels/renderman/shaders/toon.phtml>.
- VisionTek, "GeForce2 GF Graphics Processing Unit", .COPYRGT. 2000 www.visiontek.com.
- Voodoo 5 5500 Review, Jul. 26, 2000, www.hexus.net.
- Wang et al., "Second-Depth Shadow Mapping", Department of Computer Science, Univ. N.C., Chapel Hill, N.C. pp. 1-7.
- Web site information, CartoonReyes, <http://www.zentertainment.com/zentropy/review/cartoonreyes.html>.
- Web site information, CartoonReyes, REM Infografica, <http://www.digimotion.co.uk/cartoonreyes.htm>.
- White paper, Dietrich, Sim, "Cartoon Rendering and Advanced Texture Features of the GeForce 256 Texture Matrix, Projective Textures, Cube Maps, Texture Coordinate Generation and DOTPRODUCT3 Texture Blending" (Dec. 16, 1999).
- White paper, Huddy, Richard, "The Efficient Use of Vertex Buffers," (Nov. 1, 2000).
- White paper, Kilgard, Mark J., "Improving Shadows and Reflections via the Stencil Buffer" (Nov. 3, 1999).
- White paper, Rogers, Douglas H., "Optimizing Direct3D for the GeForce 256" (Jan. 3, 2000).
- White paper, Spitzer, John, et al., "Using GL_NV_array_range and GL_NV_Fence on GeForce Products and Beyond" (Aug. 1, 2000).
- Whitepaper: "Z Buffering, Interpolation and More W-Buffering", Doug Rogers, Jan. 31, 2000, www.nvidia.com.
- Whitepaper: 3D Graphics Demystified, Nov. 11, 1999, www.nvidia.com.
- Whitepaper: Anisotropic Texture Filtering in OpenGL, posted Jul. 17, 2000, www.nvidia.com.
- Whitepaper: Color Key in D3D, posted Jan. 11, 2000, www.nvidia.com.
- Whitepaper: Cube Environment Mapping, posted Jan. 14, 2000, www.nvidia.com.
- Whitepaper: Dot Product Texture Blending, Dec. 3, 1999, www.nvidia.com.
- Whitepaper: Guard Band Clipping, posted Jan. 31, 2000, www.nvidia.com.
- Whitepaper: Implementing Fog in Direct3D, Jan. 3, 2000, www.nvidia.com.
- Whitepaper: Mapping Texels to Pixels in D3D, posted Apr. 5, 2000, www.nvidia.com.
- Whitepaper: Optimizing Direct3D for the GeForce 256, Jan. 3, 2000, www.nvidia.com.
- Whitepaper: Technical Brief: AGP 4X with Fast Writes, Nov. 10, 1999, www.nvidia.com.
- Whitepaper: Using GL.sub.—NV.sub.—vertex.sub.—array and GL.sub.—NV.sub.—fence, posted Aug. 1, 2000, www.nvidia.com.
- Whitepaper: Vertex Blending Under DX7 for the GeForce 256, Jan. 5, 2000, www.nvidia.com.
- Whitepapers: "Texture Addressing," Sim Dietrich, Jan. 6, 2000, www.nvidia.com.
- Williams, Lance, "Casting Curved Shadows on Curved Surfaces," Computer Graphics (SIGGRAPH '78 Proceedings), vol. 12, No. 3, pp. 270-274 (Aug. 1978).
- Winner, Stephanie, et al., "Hardware Accelerated Rendering of Antialiasing Using a Modified A-buffer Algorithm," Computer Graphics Proceedings, Annual Conference Series, 1997, pp. 307-316.
- Woo et al., "A Survey of Shadow Algorithms," IEEE Computer Graphics and Applications, vol. 10, No. 6, pp. 13-32 (Nov. 1990).
- Yumiko Ono, Sony Antes Up Its Chips in Bet on New Game System, Dow Jones News Service, Mar. 4, 1999.
- ZDNet Reviews, from PC Magazine, "Other Enhancements," Jan. 15, 1999, [wysiwyg://16/http://www4.zdnet.com...ies/reviews/0,4161,2188286,00.html](http://www4.zdnet.com...ies/reviews/0,4161,2188286,00.html).
- ZDNet Reviews, from PC Magazine, "Screen Shot of Alpha-channel Transparency," Jan. 15, 1999, [wysiwyg://16/http://www4.zdnet.com...ies/reviews/0,4161,2188286,00.html](http://www4.zdnet.com...ies/reviews/0,4161,2188286,00.html).
- Zelevnik, Robert et al. "SKETCH: An Interface for Sketching 3D Scenes," Computer Graphics Proceedings, Annual Conference Series 1996, pp. 163-170.

* cited by examiner







Fig. 2






Fig. 4




Fig. 5 EXAMPLE GRAPHICS PROCESSOR FLOW





Fig. 6A






Fig. 7





Fig. 8






Fig. 10
Read Data Path




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16A




Fig. 16B

GRAPHICS PROCESSING SYSTEM WITH ENHANCED MEMORY CONTROLLER

CROSS-REFERENCES TO RELATED APPLICATIONS

This application is a divisional of application Ser. No. 09/726,220, filed Nov. 28, 2000, now U.S. Pat. No. 7,538,772 which claims the benefit of provisional application No. 60/226,894, filed on Aug. 23, 2000. The contents of these applications are incorporated herein in their entirety.

BACKGROUND AND SUMMARY

The present invention relates to computer graphics, and more particularly to interactive graphics systems such as home video game platforms. Still more particularly this invention relates to a memory controller for use in such an interactive graphics system that controls resource access to main memory.

Many of us have seen films containing remarkably realistic dinosaurs, aliens, animated toys and other fanciful creatures. Such animations are made possible by computer graphics. Using such techniques, a computer graphics artist can specify how each object should look and how it should change in appearance over time, and a computer then models the objects and displays them on a display such as your television or a computer screen. The computer takes care of performing the many tasks required to make sure that each part of the displayed image is colored and shaped just right based on the position and orientation of each object in a scene, the direction in which light seems to strike each object, the surface texture of each object, and other factors.

Because computer graphics generation is complex, computer-generated three-dimensional graphics just a few years ago were mostly limited to expensive specialized flight simulators, high-end graphics workstations and supercomputers. The public saw some of the images generated by these computer systems in movies and expensive television advertisements, but most of us couldn't actually interact with the computers doing the graphics generation. All this has changed with the availability of relatively inexpensive 3D graphics platforms such as, for example, the Nintendo 64® and various 3D graphics cards now available for personal computers. It is now possible to interact with exciting 3D animations and simulations on relatively inexpensive computer graphics systems in your home or office.

In generating exciting 3D animations and simulations on relatively inexpensive computer graphics systems, it is important to efficiently control access to main memory among competing resources. Any such access control system is burdened with considerable constraints. For example, the main application program executing CPU, which is but one of many resources seeking access to main memory, must be granted memory access with a fixed memory read latency allowing for high speed execution of instructions. Accordingly, such a CPU should be awarded high priority access to main memory. In order to generate exciting graphics, certain graphics related resources seeking memory access must likewise be guaranteed high speed access to memory sufficient for the graphics processing to be rapidly completed.

The present invention is embodied in the disclosed illustrative memory controller described herein, which performs a wide range of memory control related functions including arbitrating between various competing resources seeking access to main memory. Other tasks performed by the unique memory controller include handling memory latency and

bandwidth requirements of the resources requesting memory access, buffering writes to reduce turn around, refreshing main memory, protecting main memory using programmable registers, and numerous other functions.

In controlling memory access between resources seeking to read from and write to main memory, the memory controller minimizes switching between memory reads and memory writes to avoid wasting memory bandwidth due to idle cycles resulting from such switching and thereby enhancing memory access time. The illustrative memory controller minimizes such switching by incorporating a unique write buffering methodology that uses a "global" write queue which queues write requests from various diverse competing resources to reduce read/write switching. In this fashion, multiple competing resources for memory writes are combined into one resource from which write requests are obtained.

The memory controller in accordance with the illustrative embodiment described herein, advantageously optimizes access to main memory taking into account resource memory latency and bandwidth requirements.

The memory controller described herein uniquely resolves memory coherency issues to avoid accessing stale data from memory due to reading data from a main memory address location prior to when that same location had been updated by a write operation. Coherency issues are addressed both within a single resource that has both read and write capability and difference resources. The exemplary embodiment addresses such coherency issues by efficiently flushing buffers associated with a resource. For example, a resource that is writing to main memory may send a flush signal to the memory controller to indicate that the resource's write buffer should be flushed. In accordance with an exemplary implementation, the memory controller generates a flush acknowledge handshake signal to indicate to competing resources that data written to main memory is actually stored in main memory rather than in an associated resource buffer.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other features and advantages provided by the invention will be better and more completely understood by referring to the following detailed description of presently preferred embodiments in conjunction with the drawings, of which:

FIG. 1 is an overall view of an example interactive computer graphics system;

FIG. 2 is a block diagram of the FIG. 1 example computer graphics system;

FIG. 3 is a block diagram of the example graphics and audio processor shown in FIG. 2;

FIG. 4 is a block diagram of the example 3D graphics processor shown in FIG. 3;

FIG. 5 is an example logical flow diagram of the FIG. 4 graphics and audio processor;

FIGS. 6A and 6B are block diagrams depicting memory controller and competing resources coupled thereto;

FIG. 7 is an exemplary block diagram depicting various resources accessing main memory.

FIG. 8 is a more detailed block diagram of the memory controller shown in FIGS. 6A and 6B;

FIG. 9 illustrates a memory controller address path;

FIG. 10 illustrates a memory controller read data path;

FIG. 11 is a block diagram showing an exemplary set of communication signals exchanged between the memory controller and the processor interface (PI);

3

FIG. 12 is a block diagram showing an exemplary set of communication signals exchanged between the memory controller and video interface;

FIG. 13 is a block diagram showing an exemplary set of communication signals exchanged between the memory controller and cache/command processor;

FIG. 14 is a block diagram showing an exemplary set of communication signals exchanged between the memory controller and the texture unit 500;

FIG. 15 is a block diagram showing an exemplary set of communication signals exchanged between the memory controller and the pixel engine (PE) 700; and

FIGS. 16A and 16B show example alternative compatible implementations.

DETAILED DESCRIPTION OF EXAMPLE EMBODIMENTS

FIG. 1 shows an example interactive 3D computer graphics system 50. System 50 can be used to play interactive 3D video games with interesting stereo sound. It can also be used for a variety of other applications.

In this example, system 50 is capable of processing, interactively in real time, a digital representation or model of a three-dimensional world. System 50 can display some or all of the world from any arbitrary viewpoint. For example, system 50 can interactively change the viewpoint in response to real time inputs from handheld controllers 52a, 52b or other input devices. This allows the game player to see the world through the eyes of someone within or outside of the world. System 50 can be used for applications that do not require real time 3D interactive display (e.g., 2D display generation and/or non-interactive display), but the capability of displaying quality 3D images very quickly can be used to create very realistic and exciting game play or other graphical interactions.

To play a video game or other application using system 50, the user first connects a main unit 54 to his or her color television set 56 or other display device by connecting a cable 58 between the two. Main unit 54 produces both video signals and audio signals for controlling color television set 56. The video signals are what controls the images displayed on the television screen 59, and the audio signals are played back as sound through television stereo loudspeakers 61L, 61R.

The user also needs to connect main unit 54 to a power source. This power source may be a conventional AC adapter (not shown) that plugs into a standard home electrical wall socket and converts the house current into a lower DC voltage signal suitable for powering the main unit 54. Batteries could be used in other implementations.

The user may use hand controllers 52a, 52b to control main unit 54. Controls 60 can be used, for example, to specify the direction (up or down, left or right, closer or further away) that a character displayed on television 56 should move within a 3D world. Controls 60 also provide input for other applications (e.g., menu selection, pointer/cursor control, etc.). Controllers 52a and 52b can take a variety of forms. In this example, controllers 52 shown each include controls 60a or 60b such as joysticks, push buttons and/or directional switches. Controllers 52 may be connected to main unit 54 by cables or wirelessly via electromagnetic (e.g., radio or infrared) waves.

To play an application such as a game, the user selects an appropriate storage medium 62 storing the video game or other application he or she wants to play, and inserts that storage medium into a slot 64 in main unit 54. Storage medium 62 may, for example, be a specially encoded and/or

4

encrypted optical and/or magnetic disk. The user may operate a power switch 66 to turn on main unit 54 and cause the main unit to begin running the video game or other application based on the software stored in the storage medium 62. The user may operate controllers 52a, 52b to provide inputs to main unit 54. For example, operating a control 60a, 60b may cause the game or other application to start. Moving other controls 60a, 60b can cause animated characters to move in different directions or change the user's point of view in a 3D world. Depending upon the particular software stored within the storage medium 62, the various controls 60a, 60b on a controller 52a, 52b can perform different functions at different times.

Example Electronics of Overall System

FIG. 2 shows a block diagram of example components of system 50. The primary components include:

- a main processor (CPU) 110,
- a main memory 112, and
- a graphics and audio processor 114.

In this example, main processor 110 (e.g., an enhanced IBM Power PC 750) receives inputs from handheld controllers 52 (and/or other input devices) via graphics and audio processor 114. Main processor 110 interactively responds to user inputs, and executes a video game or other program supplied, for example, by external storage media 62 via a mass storage access device 106 such as an optical disk drive. As one example, in the context of video game play, main processor 110 can perform collision detection and animation processing in addition to a variety of interactive and control functions.

In this example, main processor 110 generates 3D graphics and audio commands and sends them to graphics and audio processor 114. The graphics and audio processor 114 processes these commands to generate dynamic visual images on display 59 and high quality stereo sound on stereo loudspeakers 61R, 61L or other suitable sound-generating devices.

Example system 50 includes a video encoder 120 that receives image signals from graphics and audio processor 114 and converts the image signals into analog and/or digital video signals suitable for display on a standard display device such as a computer monitor or home color television set 56. System 50 also includes an audio codec (compressor/decompressor) 122 that compresses and decompresses digitized audio signals and may also convert between digital and analog audio signaling formats as needed. Audio codec 122 can receive audio inputs via a buffer 124 and provide them to graphics and audio processor 114 for processing (e.g., mixing with other audio signals the processor generates and/or receives via a streaming audio output of mass storage access device 106). Graphics and audio processor 114 in this example can store audio related information in an audio memory 126 that is available for audio tasks. Graphics and audio processor 114 provides the resulting audio output signals to audio codec 122 for decompression and conversion to analog signals (e.g., via buffer amplifiers 128L, 128R) so they can be reproduced by loudspeakers 61L, 61R.

Graphics and audio processor 114 has the ability to communicate with various additional devices that may be present within system 50. For example, a parallel digital bus 130 may be used to communicate with mass storage access device 106 and/or other components. A serial peripheral bus 132 may

5

communicate with a variety of peripheral or other devices including, for example:

- a programmable read-only memory and/or real time clock **134**,
- a modem **136** or other networking interface (which may in turn connect system **50** to a telecommunications network **138** such as the Internet or other digital network from/to which program instructions and/or data can be downloaded or uploaded), and
- flash memory **140**.

A further external bus **142**, which may, by way of example only, be a serial bus, and may be used to communicate with additional expansion memory **144** (e.g., a memory card) or other devices. Connectors may be used to connect various devices to busses **130**, **132**, **142**.

Example Graphics and Audio Processor

FIG. **3** is a block diagram of an example graphics and audio processor **114**. Graphics and audio processor **114** in one example may be a single-chip ASIC (application specific integrated circuit). In this example, graphics and audio processor **114** includes:

- a processor interface **150**,
- a memory interface/controller **152**,
- a 3D graphics processor **154**,
- an audio digital signal processor (DSP) **156**,
- an audio memory interface **158**,
- an audio interface and mixer **160**,
- a peripheral controller **162**, and
- a display controller **164**.

3D graphics processor **154** performs graphics processing tasks. Audio digital signal processor **156** performs audio processing tasks. Display controller **164** accesses image information from main memory **112** and provides it to video encoder **120** for display on display device **56**. Audio interface and mixer **160** interfaces with audio codec **122**, and can also mix audio from different sources (e.g., streaming audio from mass storage access device **106**, the output of audio DSP **156**, and external audio input received via audio codec **122**). Processor interface **150** provides a data and control interface between main processor **110** and graphics and audio processor **114**.

As will be explained in detail below, memory interface **152** provides a data and control interface between graphics and audio processor **114** and memory **112**. In this example, main processor **110** accesses main memory **112** via processor interface **150** and memory interface **152** that are part of graphics and audio processor **114**. Peripheral controller **162** provides a data and control interface between graphics and audio processor **114** and the various peripherals mentioned above. Audio memory interface **158** provides an interface with audio memory **126**.

Example Graphics Pipeline

FIG. **4** shows a graphics processing system including a more detailed view of an exemplary FIG. **3** 3D graphics processor **154**. 3D graphics processor **154** includes, among other things, a command processor **200** and a 3D graphics pipeline **180**. Main processor **110** communicates streams of data (e.g., graphics command streams and display lists) to command processor **200**. Main processor **110** has a two-level cache **115** to minimize memory latency, and also has a write-gathering buffer **111** for uncached data streams targeted for the graphics and audio processor **114**. The write-gathering buffer **111** collects partial cache lines into full cache lines and

6

sends the data out to the graphics and audio processor **114** one cache line at a time for maximum bus usage.

Command processor **200** receives display commands from main processor **110** and parses them—obtaining any additional data necessary to process them from shared memory **112** via memory controller **152**. The command processor **200** provides a stream of vertex commands to graphics pipeline **180** for 2D and/or 3D processing and rendering. Graphics pipeline **180** generates images based on these commands. The resulting image information may be transferred to main memory **112** for access by display controller/video interface unit **164**—which displays the frame buffer output of pipeline **180** on display **56**.

FIG. **5** is a block logical flow diagram portraying illustrative processing performed using graphics processor **154**. Main processor **110** may store graphics command streams **210**, display lists **212** and vertex arrays **214** in main memory **112**, and pass pointers to command processor **200** via processor/bus interface **150**. The main processor **110** stores graphics commands in one or more graphics first-in-first-out (FIFO) buffers **210** it allocates in main memory **110**. The command processor **200** fetches:

- command streams from main memory **112** via an on-chip FIFO memory buffer **216** that receives and buffers the graphics commands for synchronization/flow control and load balancing,
- display lists **212** from main memory **112** via an on-chip call FIFO memory buffer **218**, and
- vertex attributes from the command stream and/or from vertex arrays **214** in main memory **112** via a vertex cache **220**.

Command processor **200** performs command processing operations **200a** that convert attribute types to floating point format, and pass the resulting complete vertex polygon data to graphics pipeline **180** for rendering/rasterization. A programmable memory arbitration circuitry **130** (see FIG. **4**) arbitrates access to shared main memory **112** between graphics pipeline **180**, command processor **200** and display controller/video interface unit **164**.

FIG. **4** shows that graphics pipeline **180** may include:

- a transform unit **300**,
- a setup/rasterizer **400**,
- a texture unit **500**,
- a texture environment unit **600**, and
- a pixel engine **700**.

Transform unit **300** performs a variety of 2D and 3D transform and other operations **300a** (see FIG. **5**). Transform unit **300** may include one or more matrix memories **300b** for storing matrices used in transformation processing **300a**. Transform unit **300** transforms incoming geometry per vertex from object space to screen space; and transforms incoming texture coordinates and computes projective texture coordinates (**300c**). Transform unit **300** may also perform polygon clipping/culling **300d**. Lighting processing **300e** also performed by transform unit **300b** provides per vertex lighting computations for up to eight independent lights in one example embodiment. Transform unit **300** can also perform texture coordinate generation (**300c**) for embossed type bump mapping effects, as well as polygon clipping/culling operations (**300d**).

Setup/rasterizer **400** includes a setup unit which receives vertex data from transform unit **300** and sends triangle setup information to one or more rasterizer units (**400b**) performing edge rasterization, texture coordinate rasterization and color rasterization.

Texture unit **500** (which may include an on-chip texture memory (TMEM) **502**) performs various tasks related to texturing including for example:

- retrieving textures **504** from main memory **112**,
- texture processing (**500a**) including, for example, multi-
texture handling, post-cache texture decompression,
texture filtering, embossing, shadows and lighting
through the use of projective textures, and BLIT with
alpha transparency and depth,
- bump map processing for computing texture coordinate
displacements for bump mapping, pseudo texture and
texture tiling effects (**500b**), and
- indirect texture processing (**500c**).

Texture unit **500** outputs filtered texture values to the texture environment unit **600** for texture environment processing (**600a**). Texture environment unit **600** blends polygon and texture color/alpha/depth, and can also perform texture fog processing (**600b**) to achieve inverse range based fog effects. Texture environment unit **600** can provide multiple stages to perform a variety of other interesting environment-related functions based for example on color/alpha modulation, embossing, detail texturing, texture swapping, clamping, and depth blending.

Pixel engine **700** performs depth (z) compare (**700a**) and pixel blending (**700b**). In this example, pixel engine **700** stores data into an embedded (on-chip) frame buffer memory **702**. Graphics pipeline **180** may include one or more embedded DRAM memories **702** to store frame buffer and/or texture information locally. Z compares **700a'** can also be performed at an earlier stage in the graphics pipeline **180** depending on the rendering mode currently in effect (e.g., z compares can be performed earlier if alpha blending is not required). The pixel engine **700** includes a copy operation **700c** that periodically writes on-chip frame buffer **702** to main memory **112** for access by display/video interface unit **164**. This copy operation **700c** can also be used to copy embedded frame buffer **702** contents to textures in the main memory **112** for dynamic texture synthesis effects. Anti-aliasing and other filtering can be performed during the copy-out operation. The frame buffer output of graphics pipeline **180** (which is ultimately stored in main memory **112**) is read each frame by display/video interface unit **164**. Display controller/video interface **164** provides digital RGB pixel values for display on display **56**.

FIGS. **6A** and **6B** are illustrative block diagrams depicting memory controller **152** (FIGS. **3** and **4**) and various resources coupled thereto which compete for access to main memory **112**. Main memory **112** may, for example, comprise an SRAM, such as a 1T1SRAM, manufactured by Mosys Corporation, which automatically performs internal refresh operations. Memory interface controller **152** provides a data and control interface between main processor **110**, graphics and audio processor **114** and main memory **112**. Although memory controller **152** and graphics memory request arbitration **130** are depicted as separate components in FIG. **4**, in the illustrative implementation described below, memory controller **152** also includes graphics memory request arbitration **130**.

As shown in FIGS. **6A** and **6B**, memory controller **152** is coupled to various competing resources seeking to access main memory **112**. Such competing resources include processor interface (PI) **150** (which is coupled to main processor **110**), audio DSP (DSP) **156**, input/output interface (IO) **802**, video interface (VI) **164**, cache/command processor (CP) **200**, texture unit (TC) **500**, and pixel engine (PE) **700**. In this exemplary embodiment, of these resources, processor interface **150**, audio DSP **156** and IO interface **802** are operable to

both read information from and write information to main memory **112**. IO interface **802** is operable to itself arbitrate and interface with a wide range of input/output devices such as modem, DVD interface and has relatively low memory bandwidth requirements. In the present illustrative embodiment, video interface **164**, cache/command processor **200**, and texture unit **500** are operable to only read information from main memory **112**, and pixel engine **700** is operable to only write information to main memory **112**.

Memory controller **152** performs various memory controller tasks including: 1) arbitrating among, for example, the 7 ports depicted in FIGS. **6A** and **6B** for access to main memory **112**, 2) granting memory access taking into account memory latency and bandwidth requirements of the resources requesting memory access, 3) buffering writes to reduce access turn around, 4) refreshing main memory **112** when necessary, and 5) protecting main memory **112** using programmable registers. Although the illustrative embodiment shown in FIGS. **6A** and **6B**, depicts 7 ports seeking memory access, as will be appreciated by those skilled in the art, there may be greater or fewer than 7 ports in any given implementation. Moreover, the bus/signal line widths shown in FIG. **6B** and other Figures (as well as other implementation details) are presented for illustrative purposes only and should in no way be construed as limiting the scope of the present invention. Memory controller **152** performs arbitration among the identified ports and sends requests to the main memory **112**. In the illustrative embodiment, memory controller **152** and all of its inputs and outputs run at 200 MHz. A 128 bit 200 MHz data path is up clocked at up to 400 MHz through the 4-channel Memory Access Control (MAC) block to permit communication with a 400 MHz external 1T1SRAM memory. The MAC stores data received over respective 32 bit paths and clocks out the data at the appropriate clock rate. The address and control signals shown in FIG. **6B** are directly connected to the IO pins. The particular signaling used to communicate with main memory **112** is not a part of this invention.

In accordance with one exemplary embodiment of the memory controller resource arbitration methodology (and as further described in co-pending application Ser. No. 60/226, 886, entitled "Method and Apparatus For Accessing Shared Resources", which application is hereby incorporated herein by reference), a bandwidth control is uniquely associated with each of the above-identified resources to permit an application programmer to control the bandwidth allocation of, for example, the 3.2 gigabyte's main memory **112** bandwidth. For example, programmable bandwidth control registers are respectively associated with command processor **200** and texture unit **500**, which may be utilized to allocate more of the available main memory bandwidth to the command processor **200** than to texture unit **500**. In this fashion, sophisticated users are able to tune the above-identified competing interface drivers to their particular application needs to get better overall performance. Accordingly, for each of the above-identified competing interfaces, a register is utilized to control its allocation of memory bandwidth to ensure that for every n number of clock cycles, a request for memory arbitration will be granted. Thus, for each interface, a filter is utilized which will, for example, slow down a request for main memory access if a particular interface is generating a large number of requests at a time when other interfaces are likewise generating requests. Alternatively, if main memory **112** is idle, and no other unit is contending for memory access, then such a request for access may be granted. The filter may define the speed at which requests for a given interface may be granted when other requests from different interfaces are being simultaneously entertained.

Memory controller **152** controls a wide range of graphics data related requests for main memory **112** involving for example:

3D graphics processor **154** (specifically, command processor **200**, texture unit **500** and pixel engine **700**), main processor **110** via processor interface **150**, audio DSP **156**, display controller **164**, and peripheral controller **162** for various I/O units (e.g., mass storage access device **106**)

FIG. 7 illustrates some of the typical operations involved in these “requestors” competing for access to main memory. The arrows in FIG. 7 represent the following operations:

1. Loading texture images from mass storage device **62** (e.g., DVD) to main memory **112** for a new image, game sector or level, or other application sequence

2. Loading geometry vertex arrays from mass storage device **62** to main memory for a new image, game sector or level, or other application sequence

3. Dynamic rendering of texture maps by main processor **110** or graphics processor **154**

4. Dynamic generation or modification of vertex arrays by main processor **110**

5. Main processor **110** animating lights and transformation matrices for consumption by graphics processor **154**

6. Main processor **110** generating display lists for consumption by graphics processor **154**

7. Main processor **110** generating graphics command streams

8. 3D graphics processor **154** reading graphics command stream

9. 3D graphics processor **154** reading display lists

10. 3D graphics processor **154** accessing vertices for rendering

11. 3D graphics processor **154** accessing textures for rendering

In the illustrative implementation, the graphics processor **114** has several data memory requirements including alignment requirements for the following types of data: texture and texture lookup table images, display lists, graphics FIFO and the external frame buffer. These data objects should be aligned because the graphics processor **114** is very fast; data from the main memory **112** is transferred in 32-byte chunks. Data alignment allows for simple and fast hardware.

On other data objects, such as vertex, matrix and light arrays, in an exemplary embodiment additional hardware support eliminates the need for coarse alignment (these are 4-byte aligned). There are a large number of these data objects, and the memory consumption of each object is potentially low, so relaxing alignment restrictions helps to conserve memory.

In accordance with the illustrative implementation, multiple processors and hardware blocks can update main memory. In addition, the CPU **110** and graphics processor **114** contain various data caches. Since the hardware does not maintain coherency of the data in main memory and various associated caches, there are various potential sources of coherency problems including when the CPU modifies or generates data destined for the graphics processor **114**, when the CPU writes data through its write-gather buffer to cached memory, and when loading new data destined for the graphics processor **114** from the DVD into main memory. Coherency problems may occur if the main memory used to store the data in these two latter cases were used for other graphics data.

When the DVD loads data, the DVD API automatically invalidates the loaded main memory portion that resides in the CPU data cache. This feature provides a safe method for

programmers to modify the DVD loaded data without worrying about CPU data cache coherency. This DVD API feature activates by default; it can be deactivated by the programmer.

The graphical data loaded by DVD may contain textures and vertices that have been already formatted for the graphics processor **114** to render. Therefore, invalidation of the vertex cache and texture cache regions may be necessary.

The CPU **110** has two means of writing to main memory: the write-gather buffer and the CPU cache hierarchy. The write-gather buffer is normally used to “blast” graphics commands into memory without affecting the cache. As a result, information sent through the write-gather buffer is not cache coherent. Care must be taken when using the write-gather buffer to avoid writing to areas of memory that maybe found in the CPU cache. The cache flushing instructions shown below maybe used to force data areas out of the CPU cache.

If the CPU generates or modifies graphics data through its cache, the following memory types may end up containing stale data:

Main memory.

graphics processor **114** vertex cache and texture cache regions.

To send the correct data to the graphics processor **114**, in accordance with the exemplary embodiment, there is a need to flush the CPU data cache as well as invalidate the graphics processor **114** vertex or texture cache. The CPU typically animates data one frame ahead of the graphics processor **114**, so efficient techniques to maintain data coherency include:

Grouping all the CPU-modified graphics data in main memory sequentially, so that the block data cache flush is efficient.

Invalidating the vertex cache, as well as the entire texture cache, at the beginning of each graphics frame.

These operations are mentioned by way of illustrating some of the many operations involving reading and writing to main memory **112**. Among other things, memory controller **152** arbitrates among the ports involved in main memory reading and writing operations.

FIG. 8 is a more detailed block diagram of memory controller **152**. As shown in FIG. 8, memory controller **152** includes individual “local” interfaces associated with each of the competing resources shown in FIGS. 6A and 6B. A controller pi interface **150I** interfaces with processor interface **150**, controller DSP interface **156I** interfaces with audio DSP **156**, controller io interface **802I** interfaces with input output interface **802**, controller video interface **164I** interfaces with video interface **164**, controller cp interface **200I** interfaces with command processor **200**, controller tc interface **500I** interfaces with texture unit **500**, and interface pe **700I** interfaces with pixel engine **700**. Memory controller **152** is coupled to main memory via external memory control **829**, which is shown in further detail in FIG. 16 described below. External memory control as shown in FIG. 16 generates a read/write control signal which switches the bidirectional memory bus between read and write states.

Focusing, for illustration purposes on the texture coordinate interface **500I**, this interface is coupled to the read only texture unit **500** shown in FIGS. 6A and 6B. TC interface **500I** (like each of the local interfaces coupled to resources which read from main memory) includes a read queue (RQ2 shown in FIG. 9) for queuing read requests and associated memory addresses received from its associated resource, texture unit **500**. Memory controller interfaces pe, dsp, io, and pi also respectively include a local write queue WQ0-4 as shown in FIG. 9 for queuing write requests.

11

Turning back to FIG. 8, arbitration control **825** includes the control logic for implementing the arbitration methodology, which is described in further detail below and in the above-identified co-pending application entitled "Method and Apparatus for Accessing Shared Resources" which has been incorporated herein by reference. Arbitration control **825** is alerted to the presence of, for example, the receipt of a read request in texture interface **500I**. Similarly, interfaces **200I**, **700I**, **150I**, **156I**, **164I**, **802I** and **829** are operatively coupled to arbitration control **825** for arbitration of competing memory access requests. As will be explained further below, arbitration control **825** upon receipt of read requests from, for example, memory TC interface **500I** and DSP interface **156I** (if, for example, **500I** and **156I** were the only competing resources) may award a first memory cycle to texture unit TC and the next memory cycle to DSP **156**, etc. Thus, the read requests may be granted on a round robin basis. Arbitration controller **825** is aware of all pending requests and grants as described in the above-identified co-pending patent application and as set forth further below.

As suggested by the read data path illustrated in FIG. 10, texture unit TC has a high bandwidth requirement (e.g., see the 128 bit GFX data path which is the same width as the main memory data path). The texture unit thus may be granted a request without wasting memory bandwidth. DSP, as shown in FIG. 10, has a 64 bit bandwidth and will be awarded priority by the arbitration control **825** in a manner designed not to waste memory cycles.

The arbitration control **825** may, for example, be a state machine which sequences through states that implement the arbitration methodology described below. As explained in detail in the above-identified copending patent application, the arbitration control **825** is controlled in part by bandwidth dial registers such that when (for example) there is a request for memory access from texture unit **500**, the request may be effectively suppressed. Thus, in a video game in which there is a large amount of texture data, the system may be tuned to adjust the bandwidth to optimize it for that particular game's memory access needs.

More specifically, as stated above, each of the read "masters" (i.e., a resource seeking to access main memory **112**) is associated with a respective corresponding one of read queues RQ1 to RQ6 for queuing read addresses for reading from main memory **112**. Each of the write masters seeking to access main memory **112** is associated with a respective corresponding one of write queues WQ1 to WQ4 for queuing write addresses and corresponding data for writing to main memory **112**. Arbitration control **825** uses a predetermined arbitration process to allocate main memory access among the read queues RQ1 to RQ6 and to control which write requests among the write queues WQ1 to WQ4 are provided to global write buffer WQ0. The rate at which at least some of the requests are fed into this arbitration process is controllable in accordance with the settings of programmable bandwidth dial registers. By appropriately setting the dial registers for a particular operation, sophisticated users can tune the flow of requests to the arbitration process to improve system performance for that operation.

By collecting the write requests into the global write buffer WQ0, read to write and write to read switching may be reduced, thereby minimizing the dead memory cycles that result when the main memory is changed from one type of operation to the other. While write requests are supplied to global write buffer WQ0, read requests are processed in accordance with the arbitration process. The main memory data path is generally switched from a read to a write state when the global write buffer queue WQ0 is filled to a certain

12

level or if a main processor read request matches an entry in the global write buffer. This switchover results in a flushing of the global write buffer WQ0 to write data to specified addresses of main memory **112**.

As mentioned above, the dial registers control the memory bandwidth for the corresponding master. For example, if an accumulator to which the contents of command processor dial register are added every memory cycle is less than 1.00, even if there is a pending command processor request, the arbitration scheme grants memory access to another master until enough cycles elapse so that the contents of the accumulator is equals to or greater than 1.00, or until there is no pending request from any other masters. Memory controller **152** preferably does not permit the main memory **112** to be in an idle state because of dial register settings. The dial registers affect the arbitration scheme by masking requests from masters until the accumulator corresponding to the dial register of that master equals 1.00.

Thus, bandwidth dial registers influence the memory usage by some of the major memory "hogs". The read dials control the frequency with which the masters participate in the arbitration process and access memory. The write dials are for control flow and can slow down the writing device by throttling the writes into global write buffer WQ0. As noted, arbitration preferably does not allow the memory to be idle if there are outstanding read requests that not being allowed due to the settings of the bandwidth dials. In this case, a round robin scheme is used among the requesters that are being throttled.

In the example system, all reads are single cache-line (32 bytes). Thus, it takes two cycles of 200 MHz to read the cache line and a new read can be performed every 10 nanoseconds. Reads from main processor **110** have the highest priority, with round robin arbitration among the rest of the requestors. Memory ownership is changed every 10 nanoseconds among the read requestors and refresh, but the write queue is always written in its entirety. The write queue initiates a request when it is filled to or above a certain level or if a main processor read request matches an entry in the write-buffer.

As shown in FIG. 8, bandwidth dial registers and other registers identified specifically below are embodied in the memory controller's programmable memory registers **823**. These registers, which are identified in detail below, are programmable by main CPU **110** to control a wide range of memory controller functions. Among the registers included in memory controller **152** are memory access performance related registers. For example, performance counter registers identify how many requests are received from particular competing resources. The performance counters are utilized to keep track of wasted memory cycles so that a determination may be made as to how effectively memory bandwidth has been allocated based upon an analysis of the performance counter registers. The performance counters may be utilized to differentiate between cycles which are necessarily lost in switching between read and write operations and idle time. As previously mentioned, cycles are wasted upon switching from a read to write, e.g., two idle cycles may result from such switching. The performance counters may be utilized to determine how well a particular application program is utilizing memory bandwidth by subtracting from performance statistics memory cycles which must necessarily be utilized for read/write switching and refresh operations. By monitoring such performance, application programmers are advantageously enabled to design more efficient programs that make better use of memory.

Turning back to FIG. 9, as stated above, each of the read queues RQ1 to RQ6, is resident in an associated interface in

FIG. 8. Thus, read RQ1, as suggested by the signal line designation in FIG. 9 is resident in CP interface 200I. Similarly, write queue WQ1 (which in the illustrative embodiment queues eight requests) is resident only in PE interface 700I and is referred to herein as a “local” write queue buffer. Similarly, WQ2 through WQ4 are resident in the DSP IO and PI interfaces respectively and are local write queue buffers. WQ0 shown in FIG. 9 is the multiple resource or “global” write buffer and is resident in the FIG. 8 component wrbuf 827. The inputs to write buffer 827 shown in FIG. 8 correspond to the inputs to WQ0 shown in FIG. 9.

If, for example, multiple write requests are received in write buffer 827 at the same time, in accordance with an exemplary embodiment of the present invention, memory write buffer 827 may arbitrate among such write requests. Additionally, a dial register may be utilized in association with the global write buffer embodied in write buffer 827. In this fashion, a write request from PE or PI, through the use of a dial register, may be designated as a lower priority request

e.g., WQ1-WQ4. When the global write buffer WQ0 reaches a state where it is, for example, 75-80% full, memory controller 115 switches to a write state to initiate the flushing of the write buffer WQ0 to main memory 112 resulting in writing to the identified address locations.

Memory controller 152 utilizes three levels of write arbitration. The first level of arbitration occurs whereby write buffer control logic arbitrates with sources seeking to read information from memory. Another level of write arbitration occurs when the write buffers are not full. A third level of arbitration occurs when coherency processing is required, whereby write buffers are flushed to resolve the coherency issue.

With respect to processing read requests, in accordance with an illustrative embodiment, a round robin read is performed among resources based upon resource request arbitration processing in light of, for example, the dial register contents for each resource as explained above.

The following table lists illustrative sizes for each of the read and write queues shown in FIG. 9:

Queue	interface	depth	Width		explanation
			addr,	data, mask	
RQ1	CP (read)	16	21		Match the max latency of a single access.
RQ2	TC (read)	16	21		Match the max latency of a single access.
RQ3	VI (read)	1	21		Single outstanding read request
RQ4	DSP (read)	1	21		Single outstanding read request
RQ5	IO (read)	1	21		Single outstanding read request
RQ6	PI (read)	6	23		Multiple outstanding read request + skid 2 extra address bits to transfer critical oct-byte first.
WQ1	PE (write)	8	21 + 128		Max transfer from WQ1 to WQ0 + skid
WQ2	DSP (write)	4	21 + 128 + 4		Single outstanding write, no skid
WQ3	IO (write)	4	21 + 128		Single outstanding write, no skid
WQ4	PI (write)	8	21 + 128 + 4		Max transfer from WQ4 to WQ0 + skid
WQ0	Global Write buffer	16	24 + 128 + 4		Deep enough to amortize memory data path read/write mode switch turn around . . .

by an application programmer. The global write buffer 827 is operatively coupled to the arbitration control 825 for arbitration of write requests.

The FIG. 8 read requests from the respective read queues are directly coupled to arbitrator control 825 for arbitrating between received read requests. A request bus (which identifies whether a read from or write to main memory 112 is to take place at an associated address) is associated with each of the resources which are seeking access to main memory 112. Memory controller 152 queues up received memory access requests and sends the request result to the requesting resource.

In the case of write requests, flow control is accomplished in part using the local write buffers, e.g., WQ1 to WQ4, such that a signal is sent to the associated resource writing data to main memory 112 when the local write buffer is full (or nearly full) to inform the resource to stop sending data.

Memory controller 152 is advantageously designed to minimize read to write switching, since lost memory cycles result from such switching due to the need to place the bus in the proper read or write state. Memory controller 152 minimizes such read or write switching by gathering the required writes into a global write buffer WQ0 resident in wrbuf 827. While write requests are buffered, read requests are processed by arbitration control 825 from different resources. When the write buffer WQ0 begins to get full, it will arbitrate with the read requests in round robin fashion. Thereafter, multiple writes are processed at essentially the same time from global write buffer WQ0, which is filled from multiple resources,

FIG. 10 shows the read data path from main memory 112 to the identified resource via memory access controllers 804, 806, 808. Even though there are 6 read requesters, there are only 3 read data paths going back to the devices, the 128 bit GFX path, the 64 bit system path, and the 64 bit CPU path. The exemplary implementation does not use a unique data path for each device, since data is not transferred on all data paths at the same time. The exemplary implementation does not use a single 128-bit data path, since 64 bit devices, which take 4 cycles to receive data, are utilized. In-order to reduce the latency for CPU accesses, the CPU port was given its own path, and therefore two 64-bit paths and a 128-bit path have been utilized. The paths are connected as follows:

the GFX path, 128 bits @ 200 MHz is connected to CP 200 and TC 500. The bus bandwidth (BW) is equal to memory BW.

the CPU path, 64 bits @ 200 MHz is connected to the pi only. The bandwidth of this path is 1/2 of the bandwidth of memory 112.

the system bus, 64 bits @ 200 MHz is connected to IO, DSP and VI. All these devices are low BW and can only issue single outstanding transactions. The bus BW is 1/2 of memory BW.

The number and BW of these buses have direct impact on the memory arbitration. For example, GFX path can continuously request data from memory, whereas CPU can request data only every other cache-line cycle (100 Mhz). And the same is true for system bus.

Data read from main memory 112 is sent back to a requesting resource in order. Accordingly, if a first request is fol-

15

lowed by a second and other multiple outstanding requests, after arbitration of these requests, the requests are fulfilled in the order requested. Thus, data requested by requesting resource number 1 is routed followed by the data requested by requesting resource number 2, etc. Reads are expected by the CPU to be processed in order. The present design eliminates the need for hardware or software to perform reordering operations.

The memory controller advantageous is designed to efficiently respond to access requests in order to take full advantage of the main memory 112 use of a static RAM (SRAM) type of memory. As explained above, the example embodiment has a 1TSTRAM that provides near static RAM type access in the context of a high density DRAM. The use of near SRAM access permits, for example, writing data to main memory 112 in the order desired because writing to one location in the SRAM takes the same time as writing to any other location no matter where in SRAM the data is to be stored. In contrast, when using DRAM, writes to memory must be scheduled in accordance with the memory refresh schedule to maximize speed preference. The use of an SRAM permits efficiently fulfilling requests in order at the price of having to maintain data coherency.

With respect to maintaining coherency (processor coherency in the preferred illustrative embodiment, since other resources may rely on flushes to guarantee read/write coherency), if a resource writes to an associated write buffer for thereafter writing data to main memory 112, and almost immediately thereafter an attempt is made to read such data from main memory 112, a coherency problem results due to the potential of reading stale data from main memory 112 instead of the updated data sought. The memory controller 152 addresses the coherency issue by ensuring that, for every read request, a check is made of the address to be read to ensure that such address does not appear in the write buffer. If the address is in the write buffer, then the write buffer needs to be flushed, i.e., copied to main memory, before the read operation is performed.

Certain of the resources such as, for example, the command processor CP 200 is a unidirectional resource such that it only performs read operations from main memory 112 and does not write to main memory 112. In the exemplary implementation, pixel engine PE only writes to main memory 112. Coherency issues particularly need to be addressed with CPU 110, since CPU 110 both reads and writes from and to main memory 112. Thus, with regard to CPU reads, the address to be read is compared to write buffer addresses and, as explained above, if the address is in the write buffer, the write buffer is flushed, and then the read operation is performed. For example, if writes are performed by a particular resource to locations 0, 1, and 2, which addresses are resident in a write buffer, and an attempt is made to read from location 0, since location 0 is in the write buffer, the system should flush the write buffer contents before reading from location 0. Accordingly, in order to ensure against coherency errors within a device, such errors will only occur if the resource has both read and write capability.

However, it is also desirable for the memory controller 152, to ensure against coherency errors among different resources. Thus, if pixel engine 700 receives a command to copy information to main memory 112, the local write buffer associated with pixel engine 700 will contain both the data to be copied and an address location at which to write to main memory 112. If, for example, the video interface 164 as the texture unit 500 thereafter seeks to read data from the same address to which the pixel engine 700 is writing data, the illustrative memory controller 152 synchronizes these operations. Thus,

16

in accordance with an exemplary embodiment of the present invention, any device/resource that is writing to main memory 112 sends a flush signal to memory controller 152 which indicates to memory controller 152 to empty the respective resource's write buffer. Memory controller 152 generates a signal indicating that such operation has been completed to thereby inform CPU 110 to enable, for example, display unit 164 to read data from such a memory location. The indication from memory controller 152 that data written to main memory 112 is actually stored in main memory 112 and not in a buffer gives any competing resource the opportunity to access such data. In accordance with this exemplary embodiment, coherency among devices is guaranteed by the device writing to memory by virtue of the receipt from memory controller 152 of a flush acknowledge handshake signal.

In accordance with an exemplary embodiment of the present invention, since writes are delayed, there are various types of coherency protocols which are performed, several of which have been briefly described above. Such coherency protocols, which are described and summarized below include:

Coherency between writes and reads from the same unit.

Coherency between writes and reads for CPU.

Coherency between writes by CPU and reads by CP in CP FIFO.

Coherency between writes and reads from two different units.

RW Coherency from the Same Unit

In the exemplary implementation, DSP, IO and PI can perform writes and reads. There is no hardware RW coherency for DSP or IO in accordance with an exemplary implementation. If each device needs to read back the data it wrote to main memory 112, it needs to explicitly flush the write-buffer. This is done by issuing a flush write buffer command and waiting for an acknowledge signal. The PI read requests on the other hand are checked against the write-buffer addresses. If there is a match, the write-buffer is flushed. Then the read will proceed. The write-buffer includes the individual write-buffer for the unit and the global write-buffer.

RW Coherency from CPU

In order to handle CPU 110 write and read coherency, bypassing logic and write buffer flushing mechanism is used. For a read request from CPU, the read address is sent immediately to main memory 112 and there's not enough time for RW coherency checking until one cycle later. If there's a match, since the read request has already been sent, the read data from the memory is aborted, then it will flush the write buffer, bypass and merge the write data and read data back to the CPU 110 at the end of the write buffer flush.

In the case that a read is followed by a write for the same address location, these two requests are dispatched into the read queue and write queue separately and memory controller 152 can not distinguish the order of these two requests. Therefore, read data may end up with the new write data instead of the original one as expected. CPU 110 configuration should be set accordingly to guarantee not to issue the write before the read data comes back.

RW Coherency Between Other Units.

In the exemplary implementation, there are 4 units that can write to memory: DSP, IO, PE and PI. Any time a device writes to memory, it needs to flush its write buffers explicitly, before signaling another device for reading the data. Each of these 4 interfaces has a 2-wire flush/acknowledge protocol to accomplish this. DSP, IO or PE will issue a flush at the end of a DMA write, before interrupting the CPU 110. This will guarantee that CPU 110 will access the desired data, upon

read. CPU 110 also needs to perform an explicit flush when it sets up a buffer in main memory 112 and wants to initiate another device for a read DMA. Before starting the DMA, CPU 110 needs to perform a “sync” instruction. This instruction causes a sync bus cycle, which causes the memory controller 152 to flush the write buffer. Upon completion of the flush, the sync instruction is completed and CPU can start up a read DMA operation.

RW Coherency Between CPU/CP for CP FIFO

The memory controller also handles RW coherency between CPU writes and CP read for a command related buffer CP FIFO which is associated with external memory. PI will indicate whether the write request is for CP FIFO and memory controller will send CP the write request when the write data for CP FIFO has actually been committed to the main memory.

Turning back to FIG. 8, memory controller 152 includes a set of memory registers 823 through which the memory controller may be programmably controlled to perform a wide range of memory control and arbitration functions. In the exemplary implementation of the present invention, all registers are written through the processor interface 150. Although a table of a illustrative memory controller registers is set forth below, the following registers may be categorized into groups as follows.

Memory Protection/Interrupt Enable Registers

Four set of registers can be used for memory read, write or read/write protection by setting the read enable and/or write enable bits in MEM_MARR_CONTROL register shown in the illustrative register table below. For example, if a read address is within the range of MEM_MARR0_START and MEM_MARR0_END with MARR0 read disabled, it will set the MARR0 interrupt bit in MEM_INT_STAT register and MEM_INT_ADDRL, MEM_INT_ADDRH will have the read address that caused the interrupt. It can also cause an interrupt to the CPU if MARR0 interrupt enable bit is set in MEM_INT_ENBL register. Note that memory controller 152 is not going to terminate the read/write transaction to main memory 112 that causes the interrupt.

There is also an address interrupt that is generated if the request address is outside the current memory configuration range and within 64 Mbytes address space. If the request address is beyond 64 Mbytes, PI should generate the address interrupt and not send the request to memory controller.

Bandwidth Dial Registers

In the exemplary embodiment, there are dial registers for CP, TC, PE, CPU read and CPU write masters. These dial registers are used to lower the memory bandwidth for the associated master. For example, if the CP dial register contents when added to an associated accumulator is less than one, even if there's a pending CP request, the illustrative arbitration methodology will grant memory access to another master until CP dial register when added to the accumulator equals one or there's no other pending request from any other master. In other words, memory controller 152 never lets memory 112 be in an idle state because of the dial register settings. These dial registers indirectly affect the arbitration scheme by masking the request from that master if the dial register plus accumulator contents does not equal to 1.00. For further details, refer to the methodology described below and in more detail in the copending application entitled “Method and Apparatus For Accessing Shared Resources”, which has been incorporated herein by reference.

Performance Counter Registers

There is a request counter per master except CPU, which has separate read and write request counters. These counters are mainly used for collecting statistics about memory usage and bandwidth for different masters. There are two additional counters: MEM_FI_REQCOUNT for counting number of idle cycles due to read/write bus turnaround overhead and MEM_RF_REQCOUNT for counting number of refresh cycles. All these counters will be clamped to max values when reached.

Data for Turnaround Registers

There are 3 registers used for setting number of idle cycles for the data path turnaround: one for RD to RD from a different memory bank, one for RD to WR switching and one for WR to RD switching.

Memory Refresh and Threshold Registers

When the number of clocks reached the refresh count in refresh counter, a refresh request will be generated. If the memory is idle, memory will be granted to refresh cycles. However, if memory is non-idle, it will be granted only if the total number of refresh requests reaches the threshold value set in the memory refresh threshold register.

For purposes of illustrating an exemplary memory controller 152 register set, the following table shows example memory controller 152 registers.

Register address	Register name	Field	description
0x0 (r, w)	MEM_MARR0_START	[15:0]	Starting address of memory address range register 0 memory address (25:10)
0x2 (r, w)	MEM_MARR0_END	[15:0]	Ending address of memory address range register 0 memory address (25:10)
0x4 (r, w)	MEM_MARR1_START	[15:0]	Starting address of memory address range register 1 memory address (25:10)
0x6 (r, w)	MEM_MARR1_END	[15:0]	Ending address of memory address range register 1 memory address (25:10)
0x8 (r, w)	MEM_MARR2_START	[15:0]	Starting address of memory address range register 2 memory address (25:10)
0xa (r, w)	MEM_MARR2_END	[15:0]	Ending address of memory address range register 2 memory address (25:10)
0xc (r, w)	MEM_MARR3_START	[15:0]	Starting address of memory address range register 3 memory address (25:10)
0xe (r, w)	MEM_MARR3_END	[15:0]	Ending address of memory address range register 3 memory address (25:10)

-continued

Register address	Register name	Field	description
0x10 (r, w)	MEM_MARR_CONTROL	[7:0]	Control register for the MAR registers 3 to 0 0: MARR0 read enable (OK to read between MARR0_START and MARR0_END) ie MARR0_START <= Address < MARR0_END 1: MARR0 write enable(OK to write between MARR0_START and MARR0_END) ie MARR0_START <= Address < MARR0_END 2: MARR1 read enable 3: MARR1 write enable 4: MARR2 read enable 5: MARR2 write enable 6: MARR3 read enable 7: MARR3 write enable Default value: 0xff (okay to write or read)
0x12 (w)	MEM_CP_BW_DIAL	[8:0]	Format is 1.8. Every cycle this number is added to an accumulator that is initialized to 0. When bit 8, is set, then CP request is enabled and CP is allowed in arbitration. When set to 0x1.00, CP request is always enabled Default value: 0x1.00
0x14 (w)	MEM_TC_BW_DIAL	[8:0]	Format is 1.8. Every cycle this number is added to an accumulator that is initialized to 0. When bit 8, is set, then TC request is enabled and TC is allowed in arbitration. When set to 0x1.00, TC request is always enabled Default value: 0x1.00
0x16 (w)	MEM_PE_BW_DIAL	[8:0]	Format is 1.8. Every cycle this number is added to an accumulator that is initialized to 0. When bit 8, is set, then PE write request is enabled and PE write can be transferred from the first queue to the WQ0. When set to 0x1.00, PE write is always enabled Default value: 0x1.00
0x18 (w)	MEM_CPUR_BW_DIAL	[8:0]	Format is 1.8. Every cycle this number is added to an accumulator that is initialized to 0. When bit 8, is set, then CPU request is enabled and CPU read is allowed in arbitration. When set to 0x1.00, CPU read request is always enabled Default value: 0x1.00
0x1a (w)	MEM_CPUW_BW_DIAL	[8:0]	Format is 1.8. Every cycle this number is added to an accumulator that is initialized to 0. When bit 8, is set, then CPU write data is written into the write-buffer. When set to 0x1.00, CPU write data is accepted immediately Default value: 0x1.00
0x1c (r, w)	MEM_INT_ENBL	[4:0]	Interrupt enable register for MARRs and address out of range error 0: MARR0 interrupt enable 0 for disabled, 1: enabled 1: MARR1 interrupt enable 2: MARR2 interrupt enable 3: MARR3 interrupt enable 4: Address Error interrupt enable Default value: 0x00 (disable)
0x1e (r)	MEM_INT_STAT	[4:0]	Interrupt status register 0: MARR0 interrupt 1: MARR1 interrupt 2: MARR2 interrupt 3: MARR3 interrupt 4: Address Error interrupt Reset value: 0x00
0x20 (w)	MEM_INT_CLR		Interrupt clear. Writing to register clears all interrupts.
0x22 (r)	MEM_INT_ADDRL	[15:0]	Bits 15:0 of the memory address that caused the interrupt.
0x24 (r)	MEM_INT_ADDRH	[9:0]	Bits 25:16 of the memory address that caused the interrupt.
0x26 (r, w)	MEM_REFRESH	[7:0]	Number of cycles between memory refresh Default value: 0x80 (128 cycles) If it is zero, it is a special case for not generating any refresh cycles. This must be used with mem_refresh_thhdA to have a minimum value of 1.
0x2c (r, w)	MEM_RDTORD	[0]	For back to back read in the memory development system: 0: One idle cycle asserted when switching between the two. 1: Two idle cycles asserted when switching between the two. Default value: 0
0x2e (r, w)	MEM_RDTOWR	[0]	For a read followed by a write: 0: Two idle cycles asserted for turn around. 1: Three idle cycles asserted for turn around. Default value: 0
0x30 (r, w)	MEM_WRTORD	[0]	For a write followed by a read: 0: No idle cycle asserted. 1: One idle cycle asserted. Default value: 0

-continued

Register address	Register name	Field	description
0x32(r, w)	MEM_CP_REQCOUNTH	[15:0]	Upper 16 bits of the 32 bits counter for CP memory requests processed (31:16). Write 0 to clear counter.
0x34(r, w)	MEM_CP_REQCOUNTL	[15:0]	Lower 16 bits of the 32 bits counter for CP memory requests processed (15:0). Write 0 to clear counter.
0x36(r, w)	MEM_TC_REQCOUNTH	[15:0]	Upper 16 bits of the 32 bits counter for TC memory requests processed (31:16). Write 0 to clear counter.
0x38(r, w)	MEM_TC_REQCOUNTL	[15:0]	Lower 16 bits of the 32 bits counter for TC memory requests processed (15:0). Write 0 to clear counter.
0x3a(r, w)	MEM_CPUR_REQCOUNTH	[15:0]	Upper 16 bits of the 32 bits counter for CPU read requests processed (31:16). Write 0 to clear counter.
0x3c(r, w)	MEM_CPUR_REQCOUNTL	[15:0]	Lower 16 bits of the 32 bits counter for CPU read requests processed (15:0). Write 0 to clear counter.
0x3e(r, w)	MEM_CPUW_REQCOUNTH	[15:0]	Upper 16 bits of the 32 bits counter for CPU write requests processed (31:16). Write 0 to clear counter.
0x40(r, w)	MEM_CPUW_REQCOUNTL	[15:0]	Lower 16 bits of the 32 bits counter for CPU write requests processed (15:0). Write 0 to clear counter.
0x42(r, w)	MEM_DSP_REQCOUNTH	[15:0]	Upper 16 bits of the 32 bits counter for DSP write/read requests processed (31:16). Write 0 to clear counter.
0x44(r, w)	MEM_DSP_REQCOUNTL	[15:0]	Lower 16 bits of the 32 bits counter for DSP write/read requests processed (15:0). Write 0 to clear counter.
0x46(r, w)	MEM_IO_REQCOUNTH	[15:0]	Upper 16 bits of the 32 bits counter for IO write/read requests processed (31:16). Write 0 to clear counter.
0x48(r, w)	MEM_IO_REQCOUNTL	[15:0]	Lower 16 bits of the 32 bits counter for IO Write/read requests processed (15:0). Write 0 to clear counter.
0x4a(r, w)	MEM_VI_REQCOUNTH	[15:0]	Upper 16 bits of the 32 bits counter for VI memory requests processed (31:16). Write 0 to clear counter.
0x4c(r, w)	MEM_VI_REQCOUNTL	[15:0]	Lower 16 bits of the 32 bits counter for VI memory requests processed (15:0). Write 0 to clear counter.
0x4e(r, w)	MEM_PE_REQCOUNTH	[15:0]	Upper 16 bits of the 32 bits counter for PE memory requests processed (31:16). Write 0 to clear counter.
0x50(r, w)	MEM_PE_REQCOUNTL	[15:0]	Lower 16 bits of the 32 bits counter for PE memory requests processed (15:0). Write 0 to clear counter.
0x52(r, w)	MEM_RF_REQCOUNTH	[15:0]	Upper 16 bits of the 32 bits counter for memory refresh requests processed (31:16). Write 0 to clear counter.
0x54(r, w)	MEM_RF_REQCOUNTL	[15:0]	Lower 16 bits of the 32 bits counter for memory refresh requests processed (15:0). Write 0 to clear counter.
0x56(r, w)	MEM_FI_REQCOUNTH	[15:0]	Upper 16 bits of the 33 bits counter for memory forced idle requests processed (32:17). Write 0 to clear counter. Increment by one every idle cycle.
0x58(r, w)	MEM_FI_REQCOUNTL	[15:0]	Lower 16 bits of the 33 bits counter for memory forced idle requests processed (16:1). Write 0 to clear counter. Increment by one every idle cycle.
0x5a (r, w)	MEM_DRV_STRENGTH	[10:0]	Drive Strength
0x5c (r, w)	MEM_REFRSH_THHD	[2:0]	Threshold for generating the refresh request when the total number of outstanding refresh requests exists. Default value: 0x2 In order to generate zero refresh cycles, this register must be set to be non-zero together with mem_refresh set to 0x0.

Turning back to the FIG. 8 memory controller block diagram, as set forth above, memory controller 152 includes arbitration control 825 which operates to arbitrate memory access requests between the competing resources identified above. For further details regarding the arbitration control, reference should be made to copending application Ser. No. 60/226,886, entitled "Method and Apparatus For Accessing Shared Resources", which has been incorporated herein by reference. All reads are single cache-line (32 bytes). It takes 2 cycles of 200 Mhz to read the cache-line. Thus a new read can be performed every 10 nsec. CPU reads will have the highest priority, with round robin arbitration among the rest of the requestors. Memory ownership is changed every 10 nsec among the read requestors and refresh, but the write queue is always written in its entirety. Write queue initiates a request when it gets above a certain level or if a CPU read request address matches an entry in the write-buffer. In accordance with the illustrative embodiment, there are the following restrictions as to the frequency of requests:

Two CPU reads can not occur back to back

Two System reads can not occur back to back.

45

During a 10-nsec refresh cycle, 2 rows are refreshed. One every 5 nsec.

BW Dials

As described above, BW dials are provided via the BW registers referenced above to influence the memory usage by some of the major memory users. There are dials for the following devices:

CPU read
CP read
TC read
CPU write
PE write

55

The read dials control the frequency of the units to participate in arbitration and access memory. The write dials are for control flow and can slow down the writing device by throttling the writes into the main write buffer.

60

The arbitration methodology will not allow the memory 112 to be idle if there are outstanding read requests that are not being allowed due to the BW dial. In this case a round robin scheme is used among the requestors that are being throttled.

65

Read Queues Arbitration

CPU read has the highest priority except the following conditions:

CPU was the master for the previous access

CPU read dial knob does not equal to 1.00 and there are other requests by other masters with dial knob equals 1.00

Write Buffer is completely full and it is in the middle of the write cycles

Previous CPU read address matches a valid CPU write address in the PI local write buffer or global write buffer which will cause a write buffer flush

CP (or TC) read has the same priority as any other system masters (DSP, IO and VI) and hence arbitrates the memory in the round robin fashion with the system masters except the following conditions:

DSP, IO or VI was the master for the previous access which then cannot arbitrate again,

CP (or TC) read dial knob does not equal to 1.00 and there are other requests by other masters with dial knob equals to 1.00, it will then have a lowest priority

DSP (or IO or VI) read has the same priority as any other GFX masters (CP and TC) and hence arbitrates the memory in the round robin fashion with the GFX masters except the following conditions:

DSP (or IO or VI) was the master for the previous access which then cannot arbitrate again.

Write Buffer has lower priority then CPU, GFX or system masters except the following conditions:

Write Buffer is completely full and it will arbitrate with others in the round-robin fashion

CPU read address matches a write address in write buffer and it will have the highest priority

Any other masters with higher priority have the dial knob less than 1.00

Refresh has the lowest priority except the following conditions:

Number of total refresh requests reaches the threshold value, its priority will be bumped up to just below CPU read.

Any other masters with higher priority have the dial knob less than 1.00

Write Queues Arbitration

CPU, PE, DSP and IO are the four masters in the write queue. CPU writes has the highest priority and the other three masters arbitrate in the round-robin fashion except the following condition:

CPU write dial knob does not equal to 1.00 and there are other write masters with dial knob equals to 1.00

All these together will form the write buffer queue arbitrating the memory bandwidth with the read masters.

Each of the interfaces depicted in FIG. 6A with memory controller 152 will now be described in further detail. FIG. 11 is a block diagram showing an exemplary set of communication signals exchanged between memory controller 152 and processor interface (PI) 150. The interface shown in FIG. 11 allows reads and writes to main memory 112 from CPU 110.

This interface supports multiple outstanding read requests. In the illustrative embodiment, a new read request can be issued every cycle and a new write request can be issued every 4 clocks (4 cycles to transfer the cache-line on the bus). The memory controller 152 performs flow control by asserting mem_pi_reqfull. Write data are not acknowledged. Read data are acknowledged with the transfer of the first oct-byte of the cache. If the request address is not 32B aligned, critical double word will be returned first. All read data are processed in-order. Write data are buffered and delayed to increase memory efficiency. pi_mem_flush is asserted for one cycle to flush the write buffer. mem_pi_flush_ack is issued for one cycle to signal that the write buffer is flushed.

All interface control signals should be registered to any avoid timing problem due to long wire. For example, memory controller 152 should register the pi_mem_req signal first, and the generated mem_pi_ack signal should also be registered on both the memory controller 152 side and the Module 150 side.

However, due to the memory bandwidth and CPU performance reasons, pi_mem_addr will not be registered and will be sent immediately to the main memory, this will reduce one cycle of latency.

The signals exchanged in the illustrative embodiment between the memory controller 152 and the processor interface 150 are shown in the table below.

signal	description
pi_mem_addr[25:1]	Address of cache-line for read/write. Read is always double word aligned (critical double word first). Write is always 32 byte aligned. For main memory read, pi_mem_addr[25:3] will be used. For main memory write, pi_mem_addr[25:5] will be used. For memory register read/write, pi_mem_addr[8:1] will be used.
pi_mem_req	Asserted for one cycle to issue a cache-line read/write request. pi_mem_addr, pi_mem_fifoWr and pi_mem_rd are valid for that cycle. For a write request, the first Oct-byte of the data is also valid on the pi_mem_data bus in this cycle.
pi_mem_rd	0 is write; 1 is read
pi_mem_reg	0: memory access; 1: register access
pi_mem_fifoWr	During register writes the lower 8 bits of the address holds the register address and pi_mem_data[63:48] hold the register value.
mem_pi_reqfull	1: Memory writes for CP FIFO, valid only during pi_mem_req cycle.
mem_pi_ack	When this signal is asserted to 1, two more read and writes requests can be issued. Asserted for one cycle to signal return of data from memory during read. Bytes 0 to 7 of the cache-line are sent in that cycle. Bytes 8-15, 16-23 and 24-31 are sent in the following cycles on the mem_pi_data bus. If the read address is not 32B aligned, critical double word will be returned first. No acknowledge signal will be asserted for memory writes. All read requests are processed in-order.
mem_pi_data[63:0]	8 byte bus to transfer data from memory. A cache-line is transferred on this bus in 4 back-to-back clocks. Critical double word will come first.
pi_mem_data[63:0]	8 byte bus to transfer data to memory. A cache-line is transferred on this bus in 4 back-to-back clocks. The pi_mem_msk[1:0] bits determine validity of the two 32-bit words.

-continued

signal	description
pi_mem_msk[1:0]	32-bit word write mask bits for pi_mem_data[63:0]. pi_mem_msk[1] is write mask for pi_mem_data[63:32]. pi_mem_msk[0] is write mask for pi_mem_data[31:0]. Mask equals 0 for write enable.
pi_mem_flush	Asserted by the PI for one cycle to flush the write buffer in memory controller.
mem_pi_flush_ack	Asserted by mem for one cycle, when the write buffer is flushed.
mem_pi_int	Interrupt from mem to pi.
pi_mem_memrstb	Pi_mem_memrstb caused by power-on-reset or software-reset. Disabled by software writing to memrstb register in PI.

Turning next to the audio DSP **156**/memory controller interface **152**, the following table illustrates exemplary signals exchanged between these two components together with ¹⁵ a signal description.

Signal Name	description
dsp_memAddr[25:5]	address of cache-line for read/write. Bits (4:0) are 0 and are not transmitted.
dsp_memReq	Asserted for one cycle to issue a cache-line read/write request. dsp_memAddr is valid for that cycle.
dsp_memRd	0 is write; 1 is read
mem_dspAck	Asserted for one cycle to signal return of data from memory during read. Bytes 7 to 0 of the cache-line are sent in that cycle. Bytes 15-8, 23-16 and 31-24 are sent in the following cycles on the mem_dspData bus.
mem_dspData[63:0]	8 byte bus to transfer data from memory. A cache-line is transferred on this bus in 4 back-to-back clocks.
dsp_memData[63:0]	8 byte bus to transfer data to memory. A cache-line is transferred on this bus in 4 back-to-back clocks. The dsp_memMsk[1:0]bits determine validity of the two 32-bit words. Write enable when mask bit equals zero.
dsp_memMsk[1:0]	32-bit word write mask bits for dsp_memData[63:0]. dsp_memMsk[1] is write mask for dsp_memData[63:32]. dsp_memMsk[0] is write mask for dsp_memData[31:0]. Mask equals zero means write enable.
dsp_memFlushWrBuf	At the end of a write burst. This signal is asserted for one cycle, and causes the memory controller to flush the write buffer.
mem_dspFlushWrAck	This signal is asserted for one cycle when the memory controller has completed flushing the write buffer in response to the assertion of dsp_memFlushWrBuf.

In the exemplary implementation, with respect to the DSP/memory controller **152** interface, at most one outstanding transfer is permitted, i.e.; the next transfer cannot start until the previous transfer completes (with mem_dspAck signal). There are at least two levels of write buffering on the memory controller **152** side to buffer the write data. That is, the interface should be able to buffer the write data from the Module **156** and delay issuing the ack signal if the buffer is full.

All interface control signals should be registered to avoid timing problem due to long wire. For example, memory con-

troller **152** should register the dsp_memReq signal first, and the generated mem_dspAck signal should also be registered on both the memory controller side and the Module **156** side. Accordingly, there is a minimum of one clock delay between dsp_memReq and mem_dspAck and between mem_dspAck and the next dsp_memReq.

⁴⁵ Turning next to the input-output interface **802**/memory controller interface **152**, the following table illustrates exemplary signals exchanged.

Signal name	Description
io_memAddr[25:5]	Address of cache-line for read/write. Bits (4:0) are 0 and are not transmitted.
io_memReq	Asserted for one cycle to issue a cache-line read/write request. io_memAddr is valid for that cycle.
io_memRd	0 is write; 1 is read
mem_ioAck	Asserted for one cycle to signal return of data from memory during read. Bytes 7 to 0 of the cache-line are sent in that cycle. Bytes 15-8, 23-16 and 31-24 are sent in the following cycles on the mem_ioData bus.
mem_ioData[63:0]	8 byte bus to transfer data from memory. A cache-line is transferred on this bus in 4 back-to-back clocks.
io_memData[63:0]	8 byte bus to transfer data to memory. A cache-line is transferred on this bus in 4 back-to-back clocks.
io_memFlushWrBuf	At the end of a write burst. This signal is asserted for one cycle, and causes the memory controller to flush the write buffer.
mem_ioFlushWrAck	This signal is asserted for one cycle when the memory controller has completed flushing the write buffer in response to the assertion of io_memFlushWrBuf.

27

With respect to the I/O interface **802**/memory controller **152** signals, at most one outstanding transfer is permitted in the exemplary embodiment, i.e., the next transfer cannot start until the previous transfer completes (with mem_ioAck signal). There are at least two levels of write buffering on the memory controller side to buffer the write data. That is, the interface should be able to buffer the write data from the Module **802** and delay issuing the acknowledge signal if the buffer is full.

FIG. **12** is a block diagram showing an exemplary set of communication signals exchanged between memory controller **152** and video interface **164**. The interface signals are described in the table below.

This interface allows reads from main memory from the video interface. All reads are cache-line sized (32 bytes) and are transferred over a 64-bit bus.

signal	description
vi_mem_addr[25:5]	Address of cache-line for read.
vi_mem_req	Asserted for one cycle to issue a cache-line read request. Pi_mem_addr is valid for that cycle.
mem_vi_ack	Asserted for one cycle to signal return of data from memory. Bytes 7 to 0 of the cache-line are sent in that cycle. Bytes 15-8, 23-16 and 31-24 are sent in the following cycles on the mem_pi_data bus. All read requests are processed in-order
mem_vi_data[63:0]	8 byte bus to transfer data from memory. A cache-line is transferred on this bus in 4 back-to-back clocks.

This memory controller **152**/video interface **164** supports single outstanding read requests. A new read request can be issued after the acknowledge for the last one is received.

All interface control signals should be registered to avoid timing problem due to long wire. For example, memory controller **152** should register the vi_mem_req signal first, and the generated mem_vi_ack signal should also be registered on both the memory controller side and the Module **164** side.

Byte ordering of data on the read and write buses is shown below.

	63	0
cycle0	B0 B1 B2 B3 B4 B5 B6 B7	
cycle1	B8 B9 B10 B11 B12 B13 B14 B15	
cycle2	B16 B17 B18 B19 B20 B21 B22 B23	
cycle3	B24 B25 B26 B27 B28 B29 B30 B31	

FIG. **13** is a block diagram showing an exemplary set of communication signals exchanged between memory controller **152** and cache/command processor **200**. The table below illustrates exemplary signals exchanged between these components.

Name:	Description
pe_mem_addr (25:5)	Address of the cache-line for write, bit 4 to bit 0 are always zero.
pe_mem_req	Asserted for one cycle to issue a cache-line write request. pe_mem_addr is valid for that cycle. The first 1/2 of the cache-line is on the data bus in this cycle.

28

Name:	Description
cp_mem_addr (25:5)	Address of cache-line for read. Bits (4:0) are 0 and are not transmitted.
cp_mem_req	Asserted for one cycle to issue a cache-line read request. cp_mem_addr is valid for that cycle.
mem_cp_reqFull	When asserted, the read request queue is almost full. Only 2 more requests can be sent.
mem_cp_ack	Asserted for one cycle to signal return of data from memory. Bytes 15 to 0 of the cache-line are sent in the next cycle. Bytes 31-16 are sent after two cycles.
mem_cp_fifoWr	Asserted for one cycle indicating a new data has been written to CP FIFO in the main memory by the CPU for CP to access.
mem_cp_data (127:0)	16 byte bus to transfer data from memory. A cache-line is transferred on this bus in 2 back-to-back clocks.

FIG. **14** is a block diagram showing an exemplary set of communication signals exchanged between memory controller **152** and the texture unit **500**. The table below illustrates exemplary signals exchanged between these components.

name:	format:	description:
mem_tc_reqFull	1	When asserted, the read request queue is almost full. Only 2 more requests can be sent.
mem_tc_ack	1	Asserted for one cycle to signal return of requested data from memory. Bytes 0 to 15 of the cache-line are sent in the next cycle. Bytes 16 to 31 are sent the cycle after that.
mem_tc_data	128	16-byte bus to transfer data from memory. A cache-line is transferred on this bus in 2 back-to-back clocks.
tc_mem_req	1	Asserted for one cycle to issue a cache-line read request tc_mem_addr is valid for that cycle.
tc_mem_addr[25:5]	21	Address of cache-line for read. 21 bits maps 32 B into 64 MB address space.

FIG. **15** is a block diagram showing an exemplary set of communication signals exchanged between memory controller **152** and the pixel engine (PE) **700**. It is used to transfer filtered frame buffer images to main memory for display. It also converts frame buffer format to texture format and writes it into main memory **112**. The table below illustrates exemplary signals exchanged between these components.

-continued

Name:	Description
pe_mem_data (127:0)	Data bus. The first ½ of the cache-line is transferred when pe_mem_req is asserted. The second ½ will be transferred in the next cycle. The 2½ cache-lines are always transferred in back to back cycles
pe_mem_flush	At the end of a write burst. This signal is asserted for one cycle, so that the memory controller will flush the write buffer.
mem_pe_flushAck	Memory controller will asserted this signal for one cycle after receiving pe_mem_flush and flushing the write buffer.
mem_pe_reqFull	When asserted, the write queue is almost full. If the signal is asserted in the same cycle as request, no more requests will come until the signal is de-asserted. When the signal is asserted in the cycle after request, one more request can be issued.

The memory controller **152** sends address and control signals directly to external memory. Among the control signals shown are the control signals for switching the bus between a read to a write state. The following table illustrates exemplary signals exchanged between these components. Included among the signals are the read/write signals which are needed to switch the bidirectional memory bus from a read to write state.

Name	Direction	Bits	Description
Mema_topad	O	22	Memory address, bit 0 is always zero
Memrw_topad	O	1	0: Write 1: Read
Memadsb_topad	O	2	Bit 1 selects development memory, bit 0 selects main memory, active low
Memrfsh_topad	O	1	Refresh cycle
memdrvctl_topad	O	3	Drive strength control for address pads
memateb_topad	O	1	Active Terminator Enable, active low

Other Example Compatible Implementations

Certain of the above-described system components **50** could be implemented as other than the home video game console configuration described above. For example, one could run graphics application or other software written for system **50** on a platform with a different configuration that emulates system **50** or is otherwise compatible with it. If the other platform can successfully emulate, simulate and/or provide some or all of the hardware and software resources of system **50**, then the other platform will be able to successfully execute the software.

As one example, an emulator may provide a hardware and/or software configuration (platform) that is different from the hardware and/or software configuration (platform) of system **50**. The emulator system might include software and/or hardware components that emulate or simulate some or all of hardware and/or software components of the system for which the application software was written. For example, the emulator system could comprise a general purpose digital computer such as a personal computer, which executes a software emulator program that simulates the hardware and/or firmware of system **50**.

Some general purpose digital computers (e.g., IBM or Macintosh personal computers and compatibles) are now equipped with 3D graphics cards that provide 3D graphics pipelines compliant with DirectX or other standard 3D graphics command APIs. They may also be equipped with stereophonic sound cards that provide high quality stereophonic

sound based on a standard set of sound commands. Such multimedia-hardware-equipped personal computers running emulator software may have sufficient performance to approximate the graphics and sound performance of system **50**. Emulator software controls the hardware resources on the personal computer platform to simulate the processing, 3D graphics, sound, peripheral and other capabilities of the home video game console platform for which the game programmer wrote the game software.

FIG. **16A** illustrates an example overall emulation process using a host platform **1201**, an emulator component **1303**, and a game software executable binary image provided on a storage medium **62**. Host **1201** may be a general or special purpose digital computing device such as, for example, a personal computer, a video game console, or any other platform with sufficient computing power. Emulator **1303** may be software and/or hardware that runs on host platform **1201**, and provides a real-time conversion of commands, data and other information from storage medium **62** into a form that can be processed by host **1201**. For example, emulator **1303** fetches “source” binary-image program instructions intended for execution by system **50** from storage medium **62** and converts these program instructions to a target format that can be executed or otherwise processed by host **1201**.

As one example, in the case where the software is written for execution on a platform using an IBM PowerPC or other specific processor and the host **1201** is a personal computer using a different (e.g., Intel) processor, emulator **1303** fetches one or a sequence of binary-image program instructions from storage medium **1305** and converts these program instructions to one or more equivalent Intel binary-image program instructions. The emulator **1303** also fetches and/or generates graphics commands and audio commands intended for processing by the graphics and audio processor **114**, and converts these commands into a format or formats that can be processed by hardware and/or software graphics and audio processing resources available on host **1201**. As one example, emulator **1303** may convert these commands into commands that can be processed by specific graphics and/or or sound hardware of the host **1201** (e.g., using standard DirectX, OpenGL and/or sound APIs).

An emulator **1303** used to provide some or all of the features of the video game system described above may also be provided with a graphic user interface (GUI) that simplifies or automates the selection of various options and screen modes for games run using the emulator. In one example, such an emulator **1303** may further include enhanced functionality as compared with the host platform for which the software was originally intended.

FIG. **16B** illustrates an emulation host system **1201** suitable for use with emulator **1303**. System **1201** includes a processing unit **1203** and a system memory **1205**. A system bus **1207** couples various system components including sys-

31

tem memory **1205** to processing unit **1203**. System bus **1207** may be any of several types of bus structures including a memory bus or memory controller, a peripheral bus, and a local bus using any of a variety of bus architectures. System memory **1207** includes read only memory (ROM) **1252** and random access memory (RAM) **1254**. A basic input/output system (BIOS) **1256**, containing the basic routines that help to transfer information between elements within personal computer system **1201**, such as during start-up, is stored in the ROM **1252**. System **1201** further includes various drives and associated computer-readable media. A hard disk drive **1209** reads from and writes to a (typically fixed) magnetic hard disk **1211**. An additional (possible optional) magnetic disk drive **1213** reads from and writes to a removable "floppy" or other magnetic disk **1215**. An optical disk drive **1217** reads from and, in some configurations, writes to a removable optical disk **1219** such as a CD ROM or other optical media. Hard disk drive **1209** and optical disk drive **1217** are connected to system bus **1207** by a hard disk drive interface **1221** and an optical drive interface **1225**, respectively. The drives and their associated computer-readable media provide nonvolatile storage of computer-readable instructions, data structures, program modules, game programs and other data for personal computer system **1201**. In other configurations, other types of computer-readable media that can store data that is accessible by a computer (e.g., magnetic cassettes, flash memory cards, digital video disks, Bernoulli cartridges, random access memories (RAMs), read only memories (ROMs) and the like) may also be used.

A number of program modules including emulator **1303** may be stored on the hard disk **1211**, removable magnetic disk **1215**, optical disk **1219** and/or the ROM **1252** and/or the RAM **1254** of system memory **1205**. Such program modules may include an operating system providing graphics and sound APIs, one or more application programs, other program modules, program data and game data. A user may enter commands and information into personal computer system **1201** through input devices such as a keyboard **1227**, pointing device **1229**, microphones, joysticks, game controllers, satellite dishes, scanners, or the like. These and other input devices can be connected to processing unit **1203** through a serial port interface **1231** that is coupled to system bus **1207**, but may be connected by other interfaces, such as a parallel port, game port Fire wire bus or a universal serial bus (USB). A monitor **1233** or other type of display device is also connected to system bus **1207** via an interface, such as a video adapter **1235**.

System **1201** may also include a modem **1154** or other network interface means for establishing communications over a network **1152** such as the Internet. Modem **1154**, which may be internal or external, is connected to system bus **123** via serial port interface **1231**. A network interface **1156** may also be provided for allowing system **1201** to communicate with a remote computing device **1150** (e.g., another system **1201**) via a local area network **1158** (or such communication may be via wide area network **1152** or other communications path such as dial-up or other communications means). System **1201** will typically include other peripheral output devices, such as printers and other standard peripheral devices.

In one example, video adapter **1235** may include a 3D graphics pipeline chip set providing fast 3D graphics rendering in response to 3D graphics commands issued based on a standard 3D graphics application programmer interface such as Microsoft's DirectX 7.0 or other version. A set of stereo loudspeakers **1237** is also connected to system bus **1207** via a sound generating interface such as a conventional "sound

32

card" providing hardware and embedded software support for generating high quality stereophonic sound based on sound commands provided by bus **1207**. These hardware capabilities allow system **1201** to provide sufficient graphics and sound speed performance to play software stored in storage medium **62**.

While the invention has been described in connection with what is presently considered to be the most practical and preferred embodiment, it is to be understood that the invention is not to be limited to the disclosed embodiment, but on the contrary, is intended to cover various modifications and equivalent arrangements included within the scope of the appended claims.

We claim:

1. In a graphics system including a main processor; a graphics processing system including a command processor, a texture unit and a pixel engine for generating graphics images on a display in cooperation with said main processor; an audio processor; a video interface; an input/output interface; and a main memory, a memory controller comprising:

a plurality of main memory read queues each operatively coupled to a respective read requester, said plurality of main memory read queues including a first main memory read queue which is operatively coupled to receive read requests from said command processor, a second main memory read queue which is operatively coupled to receive read requests from said texture unit, a third main memory read queue which is operatively coupled to receive read requests from said audio processor, a fourth main memory read queue which is operatively coupled to receive read requests from said input/output interface, and a fifth main memory read queue which is operatively coupled to receive read requests from said video interface;

a plurality of main memory write queues each operatively coupled to a respective write requester, said plurality of main memory write queues including a first main memory write queue which is operatively coupled to receive write requests from said pixel engine, a second main memory write queue which is operatively coupled to receive write requests from said audio processor and a third main memory write queue which is operatively coupled to receive write requests from said input/output interface;

a global write queue coupled to said plurality of main memory write queues for storing write requests for main memory access transferred thereto from said plurality of main memory write queues; and

a control circuit for controlling the transfer of write requests to said global write queue, wherein said control circuit is operable to control the transfer of write requests from said plurality of main memory write queues to said global write queue to reduce the frequency of switching from main memory write operations to main memory read operations,

wherein said control circuit further comprises an arbitration circuit for arbitrating access to said main memory from among said main processor, said plurality of main memory read queues and said global write queue.

2. A memory controller according to claim 1, wherein said arbitration circuitry is operable to control the frequency with which one or more of said read and write requesters are enabled to participate in the arbitrating for main memory access.

33

3. A memory controller according to claim 1, further including a memory access control register associated with one of said read and write requesters, wherein said arbitration circuit is responsive to the contents of said memory access control register for determining a frequency that said one of said read and write requesters is permitted to participate in the arbitrating for main memory access.

4. A memory controller according to claim 1, further including a set of control registers, said control registers being programmable by said main processor.

5. A memory controller according to claim 4, wherein said control registers include a plurality of memory bandwidth control registers which are accessed by said arbitration circuit in determining which read or write requester will be granted main memory access.

34

6. A memory controller according to claim 5, wherein each of said memory bandwidth control registers is respectively associated with one of said read and write requesters seeking main memory access.

7. A memory controller according to claim 4, wherein said control registers include at least one register associated with a read or write requester for storing data for said requester indicative of at least one of memory usage and memory bandwidth for that requester.

10 8. A memory controller according to claim 1, wherein a write requester that is writing to main memory generates a flush signal for initiating the flushing of that write requester's main memory write queue.

* * * * *